



# White Lightning® Vinyl Spackling Compound

## Physical Properties:

Type:	Vinyl
Color:	White
Shelf Life:	24 Months
Flash Point:	>499° F
Flammability:	N/A Water-based
Cure Time:	24 Hours
Tack Free Time:	12 Minutes
Application Temperature:	Above 40° F
VOC Level:	.23 lb/gal
Odor:	Low/None
Shrinkage:	Minimal
Vehicle:	Water
Weight/Gallon:	14.7-15.1 lbs/gal

## Performance Data:

Weight/Gallon	15.20 lbs
Freeze-Thaw Stability:	Stable through 5 cycles
Clean-up:	Warm Water
Resistance to Dirt Pickup:	Good
Painting:	30 Minutes

## Application:

**DIRECTIONS:** Surfaces to be filled should be clean and dry. Apply vinyl spackle directly from container using a finger or putty knife. Trowel very large patches. After the vinyl spackle dries, sand smooth if desired. Apply in temperatures above 40°F.

**PAINTING:** Confirm product is dry. Use a latex primer before applying a quality latex or oil based paint.

**CLEAN-UP:** Clean excess spackling compound with warm water.

## Specifications:

Meets requirements of Federal Specification SS-P-00450A, Type II.

## Precautions:

Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:**

In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

**DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure.

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

**Country of Origin:**

USA

**Packaging:**

**Color Order#**  
White WL060115

**UPC Code**  
0-23275-60115-4

**Size**  
½ Pint

Rev 06/17