SAFETY DATA SHEET

83224

Section 1. Identification

Product name	: DURA SEAL® WOOD PUTTY Maple Ash Pine
Product code	: 83224
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	ne substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: MINWAX Company 10 Mountainview Road Upper Saddle River, NJ 07458
Emergency telephone number of the company	: (800) 424-9300
Product Information Telephone Number	: (800) 364-1359
Regulatory Information Telephone Number	: (216) 566-2902
Transportation Emergency	: (800) 424-9300

Section 2. Hazards identification

Telephone Number

Disposal

OSHA/HCS status	material is considered hazardous by the OSHA H CFR 1910.1200).	Hazard Communication Standard
Classification of the substance or mixture	CIFIC TARGET ORGAN TOXICITY (REPEATED) EXPOSURE) - Category 1
GHS label elements		
Hazard pictograms	^	
Signal word	ger	
Hazard statements	ses damage to organs through prolonged or repe	ated exposure. (lungs)
Precautionary statements		
Prevention	ot breathe vapor. Do not eat, drink or smoke wh oughly after handling.	en using this product. Wash
Response	medical advice or attention if you feel unwell.	
Storage	applicable.	

 Dispose of contents and container in accordance with all local, regional, national and international regulations.

Date of issue/Date	e of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version	:8	1/12
83224	DURA SEAL® WOO Maple Ash Pine	OD PUTTY			SHW-85	NA-GHS-U	IS

Section 2. Hazards identification

Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Calcium Carbonate	≥50 - ≤75	471-34-1
Calcium Carbonate	≥25 - ≤50	1317-65-3
Talc	≤10	14807-96-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necess	ary first aid measures
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 9/13/20	23 Date of previous issue : 6/10/2023
83224 DURA SEAL® WOOD PUTTY Maple Ash Pine	

Section 4. First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important symptoms/e	effects, acute and delayed
Potential acute health effe	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>otoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Date of issue/Date of revision	: 9/13/2023 Date of previous issue : 6/10/2023 Version : 8 3/12

Date of issue/Date	of revision	9/13/2023	Date of previous issue	: 6/10/2023	Version	:8	3,
83224	DURA SEAL® WOOD Maple Ash Pine	PUTTY			SHW-85-N	IA-GHS-US	

Section 6. Accidental release measures

Personal precautions, protect	tive e	equipment and emergency procedures
For non-emergency personnel	E ei P	o action shall be taken involving any personal risk or without suitable training. vacuate surrounding areas. Keep unnecessary and unprotected personnel from ntering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. rovide adequate ventilation. Wear appropriate respirator when ventilation is adequate. Put on appropriate personal protective equipment.
For emergency responders	S	specialized clothing is required to deal with the spillage, take note of any information in ection 8 on suitable and unsuitable materials. See also the information in "For non-mergency personnel".
Environmental precautions	a	void dispersal of spilled material and runoff and contact with soil, waterways, drains nd sewers. Inform the relevant authorities if the product has caused environmental ollution (sewers, waterways, soil or air).
Methods and materials for co	ontair	nment and cleaning up
Small spill	if pl	top leak if without risk. Move containers from spill area. Dilute with water and mop up water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and lace in an appropriate waste disposal container. Dispose of via a licensed waste isposal contractor.
Large spill	u s di (s al	top leak if without risk. Move containers from spill area. Approach release from pwind. Prevent entry into sewers, water courses, basements or confined areas. Wash pillages into an effluent treatment plant or proceed as follows. Contain and collect pillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or iatomaceous earth and place in container for disposal according to local regulations see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated bsorbent material may pose the same hazard as the spilled product. Note: see ection 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	 Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

ate of issue/Date of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version : 8	4/12
224 DURA SEAL Maple Ash P	® WOOD PUTTY			SHW-85-NA-GHS-U	S

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Calcium Carbonate	471-34-1	NIOSH REL (United States, 10/2020). [calcium carbonate] TWA: 5 mg/m ³ 10 hours. Form: Respirable fraction TWA: 10 mg/m ³ 10 hours. Form: Total
Calcium Carbonate	1317-65-3	OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust NIOSH REL (United States, 10/2020). [calcium carbonate] TWA: 5 mg/m ³ 10 hours. Form: Respirable fraction TWA: 10 mg/m ³ 10 hours. Form: Total
Talc	14807-96-6	NIOSH REL (United States, 10/2020). TWA: 2 mg/m ³ 10 hours. Form: Respirable fraction ACGIH TLV (United States, 1/2023). TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
talc (none asbestiform)	14807-96-6	 CA British Columbia Provincial (Canada, 6/2022). Notes: the value is for particulate matter containing no asbestos and less than 1% crystalline silica. TWA: 2 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). TWAEV: 2 mg/m³ 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m³ 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m³ 8 hours. Form: Respirable particulate CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
None.		

Date of previous issue

Biological exposure indices (United States)

: 9/13/2023

No exposure indices known.

Biological exposure indices (Canada)

Date of issue/Date	of revision	: 9/13/2
83224	DURA SEAL® WOOD	PUTTY
	Maple Ash Pine	

Section 8. Exposure controls/personal protection

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering controls Environmental exposure	loca airb	ser operations generate dust, fumes, gas, vapor or mist, use process enclosures, al exhaust ventilation or other engineering controls to keep worker exposure to orne contaminants below any recommended or statutory limits. ssions from ventilation or work process equipment should be checked to ensure
controls	they case	<i>i</i> comply with the requirements of environmental protection legislation. In some es, fume scrubbers, filters or engineering modifications to the process equipment be necessary to reduce emissions to acceptable levels.
Individual protection measu	<u>es</u>	
Hygiene measures	eati App Wa	sh hands, forearms and face thoroughly after handling chemical products, before ng, smoking and using the lavatory and at the end of the working period. propriate techniques should be used to remove potentially contaminated clothing. sh contaminated clothing before reusing. Ensure that eyewash stations and safety wers are close to the workstation location.
Eye/face protection	ass gas	ety eyewear complying with an approved standard should be used when a risk essment indicates this is necessary to avoid exposure to liquid splashes, mists, es or dusts. If contact is possible, the following protection should be worn, unless assessment indicates a higher degree of protection: safety glasses with side- elds.
Skin protection		
Hand protection	wor nec duri note glov	emical-resistant, impervious gloves complying with an approved standard should be in at all times when handling chemical products if a risk assessment indicates this is essary. Considering the parameters specified by the glove manufacturer, check ing use that the gloves are still retaining their protective properties. It should be ed that the time to breakthrough for any glove material may be different for different we manufacturers. In the case of mixtures, consisting of several substances, the ection time of the gloves cannot be accurately estimated.
Body protection	perf	sonal protective equipment for the body should be selected based on the task being formed and the risks involved and should be approved by a specialist before dling this product.
Other skin protection	bas	ropriate footwear and any additional skin protection measures should be selected ed on the task being performed and the risks involved and should be approved by a cialist before handling this product.
Respiratory protection	app resp	ed on the hazard and potential for exposure, select a respirator that meets the ropriate standard or certification. Respirators must be used according to a biratory protection program to ensure proper fitting, training, and other important ects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	:	Liquid.
Color	1	Not available.
Odor	1	Not available.
Odor threshold	:	Not available.
рН	:	Not applicable.
Melting point/freezing point	:	Not available.

Date of issue/Date	of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version : 8	6/12
83224	DURA SEAL® WOOD I Maple Ash Pine	PUTTY			SHW-85-NA-GHS-US	

Section 9. Physical and chemical properties

: Not	available.	
: Clos	sed cup: Not applicable.	
: Not	available.	
: 2.2		
:		
	Result	
	Not soluble	
	: Clos : Not : Not : Not : Not : Not : 2.2	: Result

	cold water		Not soluble		
	artition coefficient: n- ctanol/water	:	Not applicable.	1	
A	uto-ignition temperature	:	Not available.		
D	ecomposition temperature	1	Not available.		
V	'iscosity	1	Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)		
N	Iolecular weight	:	Not applicable.		
	Heat of combustion	:	2.185 kJ/g		

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
Calcium Carbonate	LD50 Oral	Rat	6450 mg/kg	-

Irritation/Corrosion

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Calcium Carbonate	Eyes - Severe irritant	Rabbit	-	24 hours 750	-
	Skin - Moderate irritant	Rabbit	-	ug 24 hours 500	-
Talc	Skin - Mild irritant	Human	-	mg 72 hours 300 ug l	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Talc	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	•••	Route of exposure	Target organs
Talc	Category 1	inhalation	lungs

Aspiration hazard

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effe	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the p	hysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
to a set of a set	A NEW YORK THE

Ingestion	: No specific data
-----------	--------------------

Date of issue/Da	te of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version : 8	8/12
83224	DURA SEAL® WO Maple Ash Pine	DOD PUTTY			SHW-85-NA-GHS-	US

Section 11. Toxicological information

Delayed and immediate ef	fects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health e	ffects
Not available.	
General	: Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Numerical measures of to	<u>xicity</u>

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
		Fish - <i>Gambusia affinis</i> - Adult Fish - <i>Rhamdia quelen</i>	96 hours 🥆 30 days

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

<u>Mobility in soil</u>

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Special precautions	conside mode o suitably to shipn of the p dangero	odal shipping descriper odal shipping descriper f transport (sea, air, for that mode of tran nent, and compliance erson offering the propus goods must be the all actions in case of	e presence of a ship etc.), does not indic nsport. All packaging e with the applicable oduct for transport. rained on all of the ri	oping description for ate that the product g must be reviewed regulations is the s People loading and sks deriving from th	a particular is packaged for suitability prior ole responsibility unloading
ransport in bulk ac IMO instruments	cording : Not avail	able.			

Proper shipping name

: Not available.

Date of issue/Dat	te of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version : 8	10/12
83224	DURA SEAL® WOOD) PUTTY			SHW-85-NA-GHS-US	
	Maple Ash Pine					

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.


Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Justification	
SPECIFIC TARGET ORG	Calculation method	
History		
Date of printing	: 9/13/2023	
Date of issue/Date of revision	: 9/13/2023	
Date of previous issue	: 6/10/2023	
Version	: 8	

Date of issue/Date	of revision	: 9/13/2023	Date of previous issue	: 6/10/2023	Version : 8	11/12
83224	DURA SEAL® WOOD Maple Ash Pine	PUTTY			SHW-85-NA-GHS-US	

Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
	as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.