

# 14-198

## Woodcraft Semi-Transparent Oil Stain - White Base



### INTENDED USES:

A decorative and protective water repellent stain finish for exterior wood siding. Semi-Transparent Stain enhances the natural beauty of the wood. The pigmentation provides protection from the ultra violet light while maintaining the natural colour. Widely used by producers of pre-finished siding. Contains no creosote to prevent subsequent painting at a later date.

### PRODUCT DESCRIPTION

A selected blend of oils containing penetrating solvents, fungicidal agents and a water repellent additive.

---

### TECHNICAL INFORMATION:

#### Finish:

Flat

#### Tint Range:

Woodcraft semi transparent stain colours

#### Theoretical Coverage:

18-28 m<sup>2</sup>/3.7L (200-290 ft<sup>2</sup>/3.7L)

#### Typical Specific Gravity:

0.9

#### Application Thinner:

Not normally required.

#### Standard Colours:

White (14-198), Natural (14-199), Neutral Base (14-151)

#### Recommended # of coats:

1-2 at recommended coverage

#### Typical Volume Solids:

18%

#### Flash point:

58°C (136°F)

#### Clean-up Thinner:

Mineral Spirits

---

### SURFACE PREPARATION:

Wood must be clean, dry (less than 12% Moisture) and free from dust, grease, mildew and wax and not previously painted or varnished.

### APPLICATION:

Brush (preferred\*), Air Spray, Airless Spray or Dipping.

Airless Tips: .011" - .015"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch: 12 hours minimum

To Handle: 18 hours

To Overcoat: 18 hours minimum

### PRODUCT HAZARDS AND SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

### ADDITIONAL DATA:

Stir thoroughly before and during use. \*Brushing preferred to work stain into surfaces and to achieve a more uniform appearance. Caution: To avoid lap marks, keep a "wet edge" by stopping only at natural breaks such as windows, casings, door jambs or the course of the siding. If mildew is present, the surface should be washed with a chlorine bleach solution (20% household bleach and 1% liquid detergent in warm water) and thoroughly rinsed prior to painting. For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 10-25°C and 40-60% respectively, at the time of application and for four hours afterward.

### Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.