

58-030

HP2000 Interior/Exterior Eggshell Coating



INTENDED USES:

A fast drying, high performance eggshell latex finish for interior and exterior applications in high wear and institutional areas where high maintenance is required. Suitable for use on new drywall and suitably primed surfaces. The product is suitable for use in areas where moisture and condensation occur or any areas where a very durable finish is required.

PRODUCT DESCRIPTION

A pigmented 100% acrylic latex containing a fungicidal agent to inhibit mildew growth on the surface of the coating.

TECHNICAL INFORMATION:

Finish:

Eggshell

Tint Range:

Full range of colours

Theoretical Coverage:

31-41 m²/3.7L (330-440 ft²/3.7L)

Typical Specific Gravity:

1.4

Application Thinner:

Not required for brush or roller application.
Use water if required for spraying

Standard Colours:

White

Recommended # of coats:

1-2 at recommended coverage

Typical Volume Solids:

41%

Flash point:

Not Applicable

Clean-up Thinner:

Water

SURFACE PREPARATION:

Surfaces must be clean, dry and free from dust, grease, mildew and wax. Remove any loose and peeling paint and repair with patching compound. Ensure all joints and seams are filled with a paintable caulking to prevent moisture ingress. Prime as required below. Surface repairs should be spot primed.

New Wood: Prime with Exterior Alkyd Primer or Latex Wood Primer.

New Drywall: Prime with Latex Sealer.

Previously Painted Surfaces: Glossy surfaces should be sanded to a dull finish to provide good adhesion.

Concrete and Masonry: Allow to age 28 days. No primer required. Latex Block Filler can be used to reduce texture on rough surfaces.

Metal and Other Surfaces: Consult your GP Paint Pro.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .013" - .017"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch: 15 to 30 minutes

To Handle: 2 hours

To Overcoat: 4 hours minimum

PRODUCT HAZARDS AND SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.

58030

DATE OF ISSUE: Nov 2, 2016.

If mildew is present, the surface should be washed with a chlorine bleach solution (20% household bleach and 1% liquid detergent in warm water) and thoroughly rinsed prior to painting. For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for four hours afterward. Complies with MPI# 138.

Canadian Food Inspection Agency: Accepted construction materials for coating walls and ceilings.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.