

60-034



Baseline Interior / Exterior Waterborne Alkyd Primer

INTENDED USES:

An interior / exterior waterborne alkyd / acrylic hybrid primer designed to be used on a wide variety of substrates including new wood, aged alkyds, prepared galvanized steel, aluminum, masonry, concrete, plaster and drywall. This product was benchmarked against the leading branded waterbased primer sealers with outstanding performance results in adhesion, stain blocking, and hide with a quick re-coat window.

PRODUCT DESCRIPTION:

A blend of water dispersed alkyd and acrylic resins pigmented to provide opacity, holdout, adhesion and a suitable base for subsequent coatings.

TECHNICAL INFORMATION:

Finish:

Eggshell

Tint Range:

Light Colours

Theoretical Coverage:

29-39 m²/3.7L (310-420 ft²/3.7L)

Typical Specific Gravity:

1.2

Application Thinner:

Not normally required. Up to 5% water may be used, if required, for spraying.

Standard Colours:

Off White

Recommended # of coats:

1-2 at recommended coverage

Typical Volume Solids:

39%

Flash point:

Not Applicable

Clean-up Thinner:

Water (A final rinse with Mineral Spirits may be required)

SURFACE PREPARATION:

Wood must be clean, dry (less than 15% moisture content) and free from dust, grease, mildew and wax.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .009" - .013"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch: 15 to 30 minutes

To Handle: 2 hours

To Overcoat: 4 hours minimum

PRODUCT HAZARDS AND SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for 4 hours afterward.

Designed to block tannin bleed but for maximum performance on heavily tannin containing wood, use an Alkyd Primer.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.