

60-050

Baseline Plastic Primer



INTENDED USES:

A fast drying latex primer for use on non-porous interior surfaces such as plastic, previously painted wood or metal surfaces, vinyl wall coverings, glass and various "factory finishes"* which often present recoating problems.

PRODUCT DESCRIPTION

A high quality acrylic vehicle combined with suitable pigments.

TECHNICAL INFORMATION:

Finish:

Flat

Tint Range:

Light Colours

Theoretical Coverage:

27-36 m²/3.7L (290-380 ft²/3.7L)

Typical Specific Gravity:

1.4

Application Thinner:

Not normally required. Up to 10% water may be added if necessary.

Standard Colours:

White

Recommended # of coats:

1-2 at recommended coverage

Typical Volume Solids:

36%

Flash point:

Not Applicable

Clean-up Thinner:

Water

SURFACE PREPARATION:

Surfaces must be clean, dry and free from dust, grease, mildew and wax. Remove any loose and peeling paint and repair with patching compound. Surface repairs should be spot primed.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .013" - .017"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch: 15-30 minutes

To Handle: 2 hours

To Overcoat: 3 hours minimum

*NOTE (Allow 24 hrs. if top coating with a solvent based finish).

PRODUCT HAZARDS AND SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for four hours afterward. Sanding of glossy surfaces will provide optimum adhesion and application properties. *As some factory finishes contain wax or silicone surface treatments, a test area should be carried out to ensure that adhesion will be satisfactory. A minimum of 7 days will be required before testing adhesion since the adhesive properties progressively improve for up to 28 days.

Complies with the requirements of MPI #17.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.

60050

DATE OF ISSUE: Nov 2, 2016.