60-077 Baseline Drywall Primer



INTENDED USES:

A drywall undercoat for interior application on walls and ceilings. Ideal for use under flat or low sheen finishes.

PRODUCT DESCRIPTION

A pigmented latex undercoat designed for professional painters.

TECHNICAL INFORMATION:	
Finish:	Standard Colours:
Flat	Toned White
Tint Range:	Recommended # of coats:
Light Colours	1-2 at recommended coverage
Theoretical Coverage:	Typical Volume Solids:
25-33 m²/3.7L (260-350 ft²/3.7L)	33%
Typical Specific Gravity:	Flash point:
1.4	Not Applicable
Application Thinner:	Clean-up Thinner: Water
Do not thin	
SURFACE PREPARATION:	

Surfaces must be clean, dry and free from loose material. Drywall joints and patched areas must be dry and free from sanding dust.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .013" - .017"

Dry times at 21°C / 70°F and 60 minutes 40%-60% R.H.: To Touch: 2 hours To Handle: 6 hours To Overcoat:

PRODUCT HAZARDS AND SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for four hours afterward. If mildew is present, the surface should be washed with a chlorine bleach solution (20% household bleach and 1% liquid detergent in warm water) and thoroughly rinsed prior to painting. A curing period of 7-10 days is required before the optimum properties are achieved. *Can be tinted with up to 4 ounces of colorant, however this will increase the VOC levels and may add some odour to the paint.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.