73-310



Standard Colours:

Field Marking Paint - White

INTENDED USES:

A fast dry, environmentally friendly coating suitable for application to grass for line marking.

PRODUCT DESCRIPTION:

A fast dry latex pigmented with durable pigments.

TECHNICAL INFORMATION: Finish:

Flat White

Tint Range: Recommended # of coats:

N/A 1-2 at recommended coverage

Theoretical Coverage: Typical Volume Solids:

20-27 m²/3.7L (220-290 ft²/3.7L) 27%

Typical Specific Gravity: Flash point:

Not Applicable 1.4 **Clean-up Thinner: Application Thinner:**

Not normally required - use water if necessary. Water

SURFACE PREPARATION:

Grass should be dry and free from any loose materials. Only apply when the temperature is above 10°C (50°F) and humidity < 80% within 4 hours of application.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .011" - .015"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch: 15 to 30 minutes

To Handle: 2 hours

4 hours minimum To Overcoat:

PRODUCT HAZARDS SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

Do not apply if dew is expected within 4 hours after painting.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.

73 310 DATE OF ISSUE: October 22, 2016