# **SAFETY DATA SHEET**

GC26116

#### Section 1. Identification **Product name** : Geocel® Pro Flex® Tripolymer Sealant Earthtone **Product code** : GC26116 Other means of : Not available. identification : Liquid. **Product type** Relevant identified uses of the substance or mixture and uses advised against Paint or paint related material. Manufacturer : Geocel Products Group A Business Unit of the Sherwin-Williams Company 101 W. Prospect Avenue Cleveland, Ohio 44115 : Sherwin-Williams Canada Inc. **National contact** 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada **Emergency telephone** : US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year number of the company **Product Information** : US / Canada: (800) 348-7615 Mexico: Not Available **Telephone Number Regulatory Information** : US / Canada: (216) 566-2902 **Telephone Number** Mexico: Not Available **Transportation Emergency** : US / Canada: (800) 424-9300 **Telephone Number** Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

### Section 2. Hazards identification

<b>Classification of the</b>	: SKIN CORROSION/IRRITATION - Category 2
substance or mixture	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B
	CARCINOGENICITY - Category 1B
	TOXIC TO REPRODUCTION - Category 2
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 15% <a>(oral)</a> , 62.6% (dermal), 62.6% (inhalation)

<u>GHS label elements</u> Hazard pictograms



Version : 12 1/15 SHW-85-NA-GHS-CA

## Section 2. Hazards identification

Signal word	: Danger
Hazard statements	<ul> <li>Causes skin and eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.</li> </ul>
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash thoroughly after handling.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

## Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

#### CAS number/other identifiers

Ingredient name	% by weight	CAS number	
Tetrachloroethylene	47.6	127-18-4	
Hydrocarbon Polymer	17.23	-	
Isobutylene Polymer	7.8	9003-27-4	
Styrene-Hydrocarbon Copolymer	7.23	9011-11-4	
Light Aromatic Hydrocarbons	0.48	64742-95-6	
trimethylbenzene	0.25	25551-13-7	
Light Stabilizer	0.15	52829-07-9	
1,3,5-Trimethylbenzene	0.1	108-67-8	
1,2,4-Trimethylbenzene	0.1	95-63-6	

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Date of issue/Date	of revision	: 10/15/2021	Date of previous issue	: 10/2/2021	Version : 12	2/15
GC26116	Geocel® Pro Flex® Tri Earthtone	polymer Sealan	t		SHW-85-NA-GHS-C	A

## Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Earthtone

GC26116	Geocel® Pro Flex® 1	ripolymer Sealant SHW-85-NA-GHS-CA
Date of issue/Date	of revision	: 10/15/2021 Date of previous issue : 10/2/2021 Version : 12
		dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations
		respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue
Inhalation	:	pain or irritation watering redness Adverse symptoms may include the following:
Eye contact	:	Adverse symptoms may include the following:
<u>Over-exposur</u>	<u>e signs/symptor</u>	<u>ns</u>
Ingestion	:	Can cause central nervous system (CNS) depression.
Skin contact	: :	Causes skin irritation.
Inhalation	:	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Eye contact	:	Causes eye irritation.
Potential acut	e health effects	

.021	Version . 12
	SHW-85-NA-GH

### Section 4. First aid measures

Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency<br/>personnel: No action shall be taken involving any personal risk or without suitable training.<br/>Evacuate surrounding areas. Keep unnecessary and unprotected personnel from<br/>entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist.<br/>Provide adequate ventilation. Wear appropriate respirator when ventilation is<br/>inadequate. Put on appropriate personal protective equipment.

Date of issue/Date	of revision	: 10/15/2021	Date of previous issue	: 10/2/2021	Version : 12	4/15
GC26116	Geocel® Pro Flex® Tri Earthtone	polymer Sealan	t		SHW-85-NA-GHS-C	;А

### Section 6. Accidental release measures

For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

**Control parameters** 

**Occupational exposure limits (OSHA United States)** 

: 10/2/2021

# Section 8. Exposure controls/personal protection

Ingredient name	CAS #	Exposure limits
Tetrachloroethylene	127-18-4	ACGIH TLV (United States, 1/2021). TWA: 25 ppm 8 hours. TWA: 170 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 685 mg/m <sup>3</sup> 15 minutes. OSHA PEL Z2 (United States, 2/2013). TWA: 100 ppm 8 hours. CEIL: 200 ppm AMP: 300 ppm 5 minutes.
Hydrocarbon Polymer Isobutylene Polymer Styrene-Hydrocarbon Copolymer Light Aromatic Hydrocarbons trimethylbenzene	9003-27-4 9011-11-4 64742-95-6 25551-13-7	None. None. None. <b>ACGIH TLV (United States, 1/2021).</b> TWA: 25 ppm 8 hours. TWA: 123 mg/m <sup>3</sup> 8 hours.
Light Stabilizer 1,3,5-Trimethylbenzene	52829-07-9 108-67-8	None. ACGIH TLV (United States, 1/2021). TWA: 25 ppm 8 hours. TWA: 123 mg/m <sup>3</sup> 8 hours. NIOSH REL (United States, 10/2020). TWA: 25 ppm 10 hours. TWA: 125 mg/m <sup>3</sup> 10 hours.
1,2,4-Trimethylbenzene	95-63-6	ACGIH TLV (United States, 1/2021). TWA: 25 ppm 8 hours. TWA: 123 mg/m <sup>3</sup> 8 hours. NIOSH REL (United States, 10/2020). TWA: 25 ppm 10 hours. TWA: 125 mg/m <sup>3</sup> 10 hours.

#### Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Tetrachloroethylene	127-18-4	<ul> <li>CA Alberta Provincial (Canada, 6/2018).</li> <li>15 min OEL: 678 mg/m<sup>3</sup> 15 minutes.</li> <li>15 min OEL: 100 ppm 15 minutes.</li> <li>8 hrs OEL: 25 ppm 8 hours.</li> <li>8 hrs OEL: 170 mg/m<sup>3</sup> 8 hours.</li> <li>CA British Columbia Provincial (Canada, 1/2021).</li> <li>TWA: 25 ppm 8 hours.</li> <li>STEL: 100 ppm 15 minutes.</li> <li>CA Ontario Provincial (Canada, 6/2019).</li> <li>TWA: 25 ppm 8 hours.</li> <li>STEL: 100 ppm 15 minutes.</li> <li>CA Quebec Provincial (Canada, 7/2019).</li> <li>TWAEV: 25 ppm 8 hours.</li> <li>STEV: 100 ppm 15 minutes.</li> <li>STEV: 685 mg/m<sup>3</sup> 15 minutes.</li> <li>STEV: 685 mg/m<sup>3</sup> 15 minutes.</li> <li>TWA: 25 ppm 8 hours.</li> <li>STEL: 100 ppm 15 minutes.</li> <li>TWA: 25 ppm 8 hours.</li> </ul>

#### Occupational exposure limits (Mexico)

Date of issue/Date	of revision	: 10/15/2021	Date of previous issue	: 10/2/2021	Version	:12	6/15
GC26116	Geocel® Pro Flex® Tri Earthtone	polymer Sealan	t		SHW-85-	NA-GHS-CA	

## Section 8. Exposure controls/personal protection

Ingredient name	CAS #	Exposure limits	
Tetrachloroethylene	127-18-4	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 25 ppm 8 hours. STEL: 100 ppm 15 minutes.	

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance		
Physical state	1	Liquid.
Color	1	Not available.
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not applicable.
Melting point/freezing point	:	Not available.

Date of issue/Date	of revision	: 10/15/2021	Date of previous issue	: 10/2/2021	Version	:12	7/15
GC26116	Geocel® Pro Flex® Trip Earthtone	oolymer Sealant			SHW-85-1	NA-GHS-CA	

## Section 9. Physical and chemical properties

• •	
: 121°C (249.8°F)	
: Closed cup: Not applicable.	
: 2.59 (butyl acetate = 1)	
: Not available.	
: Not available.	
: 2.4 kPa (18 mm Hg)	
: 5.83 [Air = 1]	
: 1.19	
: Not available.	
: Not applicable.	
: Not available.	
: Not available.	
: Kinematic (40°C (104°F)): <20.5 mm²/s (<20.5 cSt)	
: Not applicable.	
: 2.501 kJ/g	
	<ul> <li>Closed cup: Not applicable.</li> <li>2.59 (butyl acetate = 1)</li> <li>Not available.</li> <li>Not available.</li> <li>2.4 kPa (18 mm Hg)</li> <li>5.83 [Air = 1]</li> <li>1.19</li> <li>Not available.</li> <li>Not available.</li> <li>Not applicable.</li> <li>Not available.</li> </ul>

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Tetrachloroethylene	LD50 Oral	Rat	2629 mg/kg	-
Light Aromatic Hydrocarbons	LD50 Oral	Rat	8400 mg/kg	-
trimethylbenzene	LD50 Oral	Rat	8970 mg/kg	-
Light Stabilizer	LC50 Inhalation Vapor	Rat	500 mg/m <sup>3</sup>	4 hours
1,3,5-Trimethylbenzene	LC50 Inhalation Vapor	Rat	24000 mg/m <sup>3</sup>	4 hours
, , , , , , , , , , , , , , , , , , ,	LD50 Oral	Rat	5000 mg/kg	-
1,2,4-Trimethylbenzene	LC50 Inhalation Vapor	Rat	18000 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	5 g/kg	-

#### Irritation/Corrosion

Date of issue/Date	of revision	: 10/15/2021	Date of previous issue	: 10/2/2021	Version	:12	8/15
GC26116	Geocel® Pro Flex® Trip Earthtone	polymer Sealant	t		SHW-85-	NA-GHS-CA	

## Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Tetrachloroethylene	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Mild irritant	Rabbit	-	162 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
	Skin - Severe irritant	Rabbit	_	mg 24 hours 810	_
		Rabbit		mg	
Light Aromatic Hydrocarbons	Eyes - Mild irritant	Rabbit	-	24 hours 100	-
				uL	
trimethylbenzene	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Moderate irritant	Rabbit	-	24 hours 500	-
				mg	
1,3,5-Trimethylbenzene	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	

#### **Sensitization**

Not available.

#### Mutagenicity

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Tetrachloroethylene	-	2A	Reasonably anticipated to be a human carcinogen.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Tetrachloroethylene	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects
Light Aromatic Hydrocarbons	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects
1,3,5-Trimethylbenzene	Category 3	-	Respiratory tract irritation
1,2,4-Trimethylbenzene	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Date of issue/	Date of revision	: 10/15/2021	Date of previous issue	: 10/2/2021	Version : 12	9/15
GC26116	GC26116 Geocel® Pro Flex® Tripolymer Sealant			SHW-85-NA-GHS-CA		
	Earthtone					

# Section 11. Toxicological information

Name		Route of exposure	Target organs
	Category 2 Category 2	-	-

#### **Aspiration hazard**

Name	Result
trimethylbenzene 1,3,5-Trimethylbenzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	1	Not available.
Potential acute health eff	ects	
Eye contact	:	Causes eye irritation.
Inhalation	:	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	:	Causes skin irritation.
Ingestion	:	Can cause central nervous system (CNS) depression.
Symptoms related to the	phy	sical, chemical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
<u>Delayed and immediate e</u> <u>Short term exposure</u>	ffec	ts and also chronic effects from short and long term exposure
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Date of issue/Date of revision           GC26116         Geocel® Pro F           Earthtone         Earthtone	lex®	: 10/15/2021Date of previous issue: 10/2/2021Version: 1210/15Tripolymer SealantSHW-85-NA-GHS-CA

## Section 11. Toxicological information

Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	<u>fects</u>
Not available.	
General	: May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: Suspected of damaging fertility.

#### Numerical measures of toxicity

Acute toxicity estimates	
Route	ATE value
Oral	4692.89 mg/kg

## Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Tetrachloroethylene	Acute EC50 504 ppm Marine water Acute EC50 3.64 mg/l Fresh water	Algae - Skeletonema costatum Algae - Chlamydomonas	96 hours 72 hours
		reinhardtii - Exponential growth phase	
	Acute LC50 3.5 mg/l Marine water	Crustaceans - Elminius modestus	
	Acute LC50 3.40071 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 4000 μg/l Fresh water	Fish - Jordanella floridae - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic EC10 1.77 mg/l Fresh water	Algae - Chlamydomonas reinhardtii - Exponential growth phase	72 hours
	Chronic NOEC 0.4 mg/l Fresh water Chronic NOEC 500 µg/l Fresh water	Daphnia - Daphnia magna Fish - Pimephales promelas - Larvae	21 days 32 days
Isobutylene Polymer	Acute LC50 >5600000 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
trimethylbenzene	Acute LC50 5600 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
1,3,5-Trimethylbenzene	Acute LC50 13000 μg/l Marine water	Crustaceans - Cancer magister - Zoea	48 hours
	Acute LC50 12520 µg/l Fresh water	Fish - Carassius auratus	96 hours
	Chronic NOEC 400 µg/l Fresh water	Daphnia - Daphnia magna	21 days
1,2,4-Trimethylbenzene	Acute LC50 4910 µg/l Marine water	Crustaceans - Elasmopus pectenicrus - Adult	48 hours
	Acute LC50 7720 μg/l Fresh water	Fish - Pimephales promelas	96 hours

#### Persistence and degradability

Date of issue/Date	of revision	: 10/15/2021	Date of previous issue	: 10/2/2021	Version : 12	11/15
GC26116	Geocel® Pro Flex® Tri Earthtone	polymer Sealan	t		SHW-85-NA-GHS-CA	

## Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Light Aromatic Hydrocarbons	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Tetrachloroethylene	-	49	low
Isobutylene Polymer	-	314 to 1882	high
Light Aromatic Hydrocarbons	-	10 to 2500	high
1,3,5-Trimethylbenzene	-	161	low
1,2,4-Trimethylbenzene	-	243	low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	UN1897	UN1897	UN1897	UN1897	UN1897
UN proper shipping name	Tetrachloroethylene mixture	Tetrachloroethylene mixture	Tetrachloroethylene mixture	Tetrachloroethylene mixture	Tetrachloroethylene mixture. Marine pollutant (Tetrachloroethylene)
Transport hazard class(es)	6.1	6.1	6.1	6.1	6.1
Packing group	III	111	111	111	
Date of issue/Date of rev GC26116 Geoc Earth	el® Pro Flex® Tripolymer Se		ssue : 10/2/202 <sup>-</sup>		on : 12 12/15 85-NA-GHS-CA

Environmental hazards	No.	No.	No.	Yes. The environmentally hazardous substance mark is not required.	Yes.
Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.26-2.36 (Class 6).	-	The environmentally hazardous substance mark may appear if required by other transportation regulations.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Emergency</u> <u>schedules</u> F-A, S A
	ERG No.	ERG No.	ERG No.		
	160	160	160		
Special precaution	cons mod suita prior resp unlo	i-modal shipping descrip sider container sizes. Th e of transport (sea, air, bbly for that mode of tran to shipment, and comp onsibility of the person of ading dangerous goods stances and on all actior	e presence of a etc.), does not in nsport. All packa liance with the a offering the prod must be trained	a shipping description for ndicate that the produc aging must be reviewed applicable regulations is duct for transport. Peop d on all of the risks deriv	or a particular t is packaged I for suitability s the sole le loading and
ransport in bulk a IMO instruments		vailable.			
	Prope	er shipping name	: Not availab	le.	

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B	Calculation method
CARCINOGENICITY - Category 1B	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPEČIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method

Date of printing	: 10/15/2021
Date of issue/Date of revision	: 10/15/2021
Date of previous issue	: 10/2/2021
Version	: 12
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations</li> </ul>

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements

Date of issue/Da	te of revision	: 10/15/2021	Date of previous issue	: 10/2/2021	Version : 12	14/15
GC26116 Geocel® Pro Flex® Tripolymer Sealant				SHW-85-NA-GHS-CA	<b>\</b>	
	Earthtone					

### Section 16. Other information

are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.