SAFETY DATA SHEET

40.10200-

Section 1. Identification

Product name	: H&C® INFUSION™ Reactive Concrete Stain Wenge Wood
Product code	: 40.10200-
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	f the substance or mixture and uses advised against
Paint or paint related materia	al.
Supplier	: Compania Sherwin-Williams S.A. de C.V. Poniente 140 No.595 Col. Industrial Vallejo, Del. Azcapotzalco C.P. 02300, Ciudad de México, México
Emergency telephone number of the company	: US/Canada: (800) 424-9300 Mexico: CHEMTREC Mexico 800-681-9531. Available 24 hours and 365 days per year
Product Information Telephone Number	: US/Canada: (800) 867-8246 Mexico: 800-717-3123 / 55-5333-1501

Transportation Emergency	: US/Canada: (800) 424-9300
Telephone Number	Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Section 2. Hazards identification

Classification of the substance or mixture	 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 3 SKIN CORROSION/IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 1 CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 4.5% (oral), 19% (dermal), 19% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Danger

Section 2. Hazards identification

Hazard statements	 H302 - Harmful if swallowed. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H331 - Toxic if inhaled. H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. H340 - May cause genetic defects. H350 - May cause cancer. H360 - May damage fertility or the unborn child. H372 - Causes damage to organs through prolonged or repeated exposure.
Precautionary statements	
General	 P103 - Read label before use. P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	 P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves, protective clothing and eye or face protection. P284 - Wear respiratory protection. P271 - Use only outdoors or in a well-ventilated area. P260 - Do not breathe vapor. P270 - Do not eat, drink or smoke when using this product. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing must not be allowed out of the workplace.
Response	 P308 + P313 - IF exposed or concerned: Get medical advice or attention. P304 + P340, P310 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor. P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. P303 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: P405 - Store locked up.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Date of issue/Date	of revision	: 9/19/2023	Date of previous issue	: 6/13/2023	Version	:7	2/16
40.10200-	H&C® INFUSION™ R Wenge Wood	eactive Concret	e Stain		SHW-85-	NA-GHS-MX	C

Section 3. Composition/information on ingredients

Ingredient name	% by weight	CAS number
Sodium Dichromate	≥10 - ≤25 ≥10 - ≤15 ≤4.7	13446-34-9 10588-01-9 7647-01-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necess	ary first aid measures
Eye contact	: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In the event of any complaints or symptoms, avoid further exposure.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important sy	mptoms/effects	<u>s, acute and</u>	<u>d delayed</u>			
Potential acute he	<u>ealth effects</u>					
Eye contact	: (Causes serio	ous eye damage.			
Inhalation		Γoxic if inhal nhaled.	ed. May cause allerg	y or asthma symptoms	or breathing difficulties if	
Skin contact	: (Causes seve	ere burns. May cause	an allergic skin reaction	on.	
Ingestion	: +	Harmful if sw	vallowed.			
<u>Over-exposure si</u>	gns/symptoms					
Eye contact	k k	Adverse sym oain vatering edness	ptoms may include th	e following:		
Date of issue/Date of re	evision	: 9/19/2023	Date of previous issue	: 6/13/2023	Version : 7	3/16
	C® INFUSION™ Rea nge Wood	active Concrete	e Stain		SHW-85-NA-GHS-MX	

Section 4. First aid measures

Inhalation	: Adverse symptoms may include the following: wheezing and breathing difficulties asthma reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Section 5. Fire-fighting measures				
Extinguishing media				
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.			
Unsuitable extinguishing media	: None known.			
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.			
Hazardous thermal decomposition products	: Decomposition products may include the following materials: halogenated compounds metal oxide/oxides			
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.			
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.			

See toxicological information (Section 11)

C aatian _ Eiro fighting massures

Section 6. Accidental release measures

Personal precautions, protec	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). The spilled material may be neutralized with sodium carbonate, sodium bicarbonate or sodium hydroxide. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handlin	1	
Protective measures	: Put on appropriate personal protective equipment (see Section history of skin sensitization problems or asthma, allergies or or respiratory disease should not be employed in any process in Avoid exposure - obtain special instructions before use. Avoid pregnancy. Do not handle until all safety precautions have be Do not get in eyes or on skin or clothing. Do not breathe vapor Use only with adequate ventilation. Wear appropriate respiration inadequate. Keep in the original container or an approved alto compatible material, kept tightly closed when not in use. Keep Empty containers retain product residue and can be hazardou	chronic or recurrent which this product is used. d exposure during een read and understood. or or mist. Do not ingest. tor when ventilation is ernative made from a p away from alkalis.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas we handled, stored and processed. Workers should wash hands drinking and smoking. Remove contaminated clothing and prentering eating areas. See also Section 8 for additional inform measures.	and face before eating, rotective equipment before
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original conditional direct sunlight in a dry, cool and well-ventilated area, away from (see Section 10) and food and drink. Store locked up. Separ container tightly closed and sealed until ready for use. Contain opened must be carefully resealed and kept upright to preven unlabeled containers. Use appropriate containment to avoid a contamination. See Section 10 for incompatible materials before the section of th	om incompatible materials rate from alkalis. Keep iners that have been at leakage. Do not store in environmental
Date of issue/Date of revision	: 9/19/2023 Date of previous issue : 6/13/2023	Version : 7 5/16
40.10200- H&C® INFUSION Wenge Wood	™ Reactive Concrete Stain	SHW-85-NA-GHS-MX

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Manganese Dichloride Tetrahydrate	13446-34-9	OSHA PEL (United States, 5/2018). [Manganese compounds (as Mn)] CEIL: 5 mg/m ³ , (as Mn) NIOSH REL (United States, 10/2020). [manganese compounds and fume as Mn] TWA: 1 mg/m ³ , (as Mn) 10 hours. Form: Fume STEL: 3 mg/m ³ , (as Mn) 15 minutes. Form: Fume ACGIH TLV (United States, 1/2023). [Manganese and inorganic compounds Inhalable fraction / Respirable fraction, as Mn] TWA: 0.1 mg/m ³ , (as Mn) 8 hours. Form: Inhalable fraction TWA: 0.02 mg/m ³ , (as Mn) 8 hours. Form: Respirable fraction
Sodium Dichromate	10588-01-9	NIOSH REL (United States, 10/2020). [chromic acid and chromates] TWA: 0.0002 mg/m ³ 8 hours. ACGIH TLV (United States, 1/2023). [inorganic chromium VI compounds as Cr (VI)] TWA: 0.0002 mg/m ³ , (measured as Cr) 8 hours. Form: Inhalable fraction STEL: 0.0005 mg/m ³ , (measured as Cr) 15 minutes. Form: Inhalable fraction OSHA PEL (United States, 5/2018). [Chromium (VI) compounds] TWA: 0.005 mg/m ³ , (as Cr) 8 hours.
Hydrochloric acid	7647-01-0	ACGIH TLV (United States, 1/2023). C: 2 ppm NIOSH REL (United States, 10/2020). CEIL: 5 ppm CEIL: 7 mg/m ³ OSHA PEL (United States, 5/2018). CEIL: 5 ppm CEIL: 7 mg/m ³

Occupational exposure limits (Canada)

Ingredien	t name		CAS #	Exposure limi	ts		
Manganes	e Dichloride Tetra	hydrate	13446-34-9	6/2022). [mang inorganic com TWA: 0.02 mg Respirable TWA: 0.2 mg/ CA Quebec Pr [Manganese-1 compounds]	lumbia Provincia ganese - Elemer pounds as Mn] g/m³, (as Mn) 8 h 'm³, (as Mn, Tota covincial (Canad fumes, dusts an mg/m³, (as Mn) 8	ntal & nours. Form: nl) 8 hours. la, 6/2022). d	
ate of issue/L	Date of revision	: 9/19/2023	Date of previous issue	: 6/13/2023	Version	:7	6/16
0.10200-	H&C® INFUSION Wenge Wood	I™ Reactive Concre	te Stain		SHW-85-N	A-GHS-MX	

		CA Alberta Provincial (Canada, 6/2018). [Manganese, elemental & inorganic compounds as Mn] 8 hrs OEL: 0.2 mg/m ³ , (as Mn) 8 hours. CA Ontario Provincial (Canada, 6/2019). [Manganese elemental and inorganic compounds as Mn] TWA: 0.2 mg/m ³ , (as Mn) 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). [Manganese and inorganic compounds as Mn] STEL: 0.6 mg/m ³ , (measured as Mn) 15 minutes. TWA: 0.2 mg/m ³ , (measured as Mn) 8 hours.
Sodium dichromate	10588-01-9	CA British Columbia Provincial (Canada, 6/2022). [hexavalent chromium compounds Inhalable. for water-soluble only] Absorbed through skin. Skin sensitizer. Inhalation sensitizer. Notes: No British Columbia exposure limit at this time
		CA Alberta Provincial (Canada, 6/2018). [Water-soluble Cr VI compounds as Cr] 8 hrs OEL: 0.05 mg/m ³ , (as Cr) 8 hours. CA British Columbia Provincial (Canada, 6/2022). [hexavalent chromium compounds - Water soluble as Cr(VI), Total] Absorbed through skin. Skin sensitizer. Inhalation sensitizer. TWA: 0.025 mg/m ³ , (as Cr(VI), Total) 8 hours. C: 0.1 mg/m ³ , (as Cr(VI), Total) CA Quebec Provincial (Canada, 6/2022). [Chromium VI, water soluble inorganic compounds] Skin sensitizer. Inhalation sensitizer. TWAEV: 0.05 mg/m ³ , (as Cr) 8 hours. CA Ontario Provincial (Canada, 6/2019). [Chromium and inorganic compounds, Water-soluble Cr VI compounds as Cr] TWA: 0.05 mg/m ³ , (as Cr) 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). [Chromium (VI) inorganic water soluble compounds as Cr] STEL: 0.15 mg/m ³ , (measured as Cr) 15 minutes. TWA: 0.05 mg/m ³ , (measured as Cr) 8 hours.
Hydrochloric acid 10,2 N	7647-01-0	CA Alberta Provincial (Canada, 6/2018). C: 3 mg/m ³ C: 2 ppm CA British Columbia Provincial (Canada, 6/2022). C: 2 ppm CA Ontario Provincial (Canada, 6/2019). Ceiling Limit: 2 ppm CA Quebec Provincial (Canada, 6/2022).
	previous issue	: 6/13/2023 Version : 7 7/16
40.10200- H&C® INFUSION™ Reactive Concrete Stain Wenge Wood		SHW-85-NA-GHS-MX

STEV: 2 ppm 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013).
CEIL: 2 ppm

Occupational exposure limits (Mexico)

Ingredient name	CAS #	Exposure limits
Manganese Dichloride Tetrahydrate	13446-34-9	NOM-010-STPS-2014 (Mexico, 4/2016). [Manganese and inorganic compounds] TWA: 0.2 mg/m ³ , (as Mn) 8 hours.
Sodium Dichromate	10588-01-9	NOM-010-STPS-2014 (Mexico, 4/2016). [Chromium compounds of Cr VI water soluble]
		TWA: 0.05 mg/m ³ 8 hours. Form: soluble in water
Hydrochloric acid	7647-01-0	NOM-010-STPS-2014 (Mexico, 4/2016). CEIL: 2 ppm

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

Ingredient name	Exposure indices
Sodium Dichromate	Official Mexican STANDARD NOM- 047-SSA1-2011, Environmental Health- Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012) [chromium(VI) compounds] BEI: 10 μg/I, total chrome [in urine]. Form: fume. Sampling time: increases during the work shift. BEI: 25 μg/I, total chrome [in urine]. Form: fume. Sampling time: at the end of the shift at the end of the work week.

Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measured	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Date of issue/Date	of revision	: 9/19/2023	Date of previous issue	: 6/13/2023	Version	:7	8/16
40.10200-	H&C® INFUSION™ R Wenge Wood	eactive Concrete	e Stain		SHW-85-	NA-GHS-M)	¢

Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Ap	pe	a	an	се
_				

Physical state	: Liqu	uid.	
Color	: Not	available.	
Odor	: Not	available.	
Odor threshold	: Not	available.	
рН	: 2		
Melting point/freezing point	: Not	available.	
Boiling point, initial boiling point, and boiling range	: 93°	C (199.4°F)	
Flash point	: Clos	sed cup: Not applicable.	
Evaporation rate	: 0.09	9 (butyl acetate = 1)	
Flammability	: Not	available.	
Lower and upper explosion limit/flammability limit	: Not	available.	
Vapor pressure	: 55.′	1 kPa (413.6 mm Hg)	
Relative vapor density	: 1[A	sir = 1]	
Relative density	: 1.23	3	
Solubility(ies)	:		
Media		Result	1
cold water		Not soluble	
Dertition coefficient: n	• Not	annliaghla	T

Partition coefficient: n-octanol/water

: Not applicable.

Section 9. Physical and chemical properties

Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Molecular weight	: Not applicable.
Heat of combustion	: 0 kJ/g

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: Attacks many metals producing extremely flammable hydrogen gas which can form explosive mixtures with air. Reactive or incompatible with the following materials: alkalis
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Manganese Dichloride Tetrahydrate	LD50 Oral	Rat	1484 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Hydrochloric acid	Eyes - Mild irritant	Rabbit	-	0.5 minutes 5	-
	Skin - Mild irritant	Human	-	mg 24 hours 4 %	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Sodium Dichromate	+	1	Known to be a human carcinogen.
Hydrochloric acid	-	3	-

Date of issue/Date of revision : 9/19/2023 40.10200- H&C® INFUSION™ Reactive Concr		Date of previous issue	: 6/13/2023	Version	:7	10/16
			SHW-85-	NA-GHS-M	X	

Section 11. Toxicological information

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Sodium Dichromate	Category 3	-	Respiratory tract irritation
Hydrochloric acid	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Sodium Dichromate	Category 1	-	-

Aspiration hazard

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effe	<u>cts</u>
Eye contact	: Causes serious eye damage.
Inhalation	: Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.
	physical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: wheezing and breathing difficulties asthma reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Section 11. Toxicological information

Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate eff	fects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	ifects
Not available.	
General	: Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: May cause genetic defects.
Teratogenicity	: May damage the unborn child.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: May damage fertility.
-	

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	646.12 mg/kg
Dermal	6144.83 mg/kg
Inhalation (vapors)	2.79 mg/l

Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
Sodium Dichromate	Acute LC50 32.3 µg/l Fresh water	Crustaceans - Simocephalus vetulus	48 hours
	Acute LC50 0.0113 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 4000 µg/l Fresh water	Fish - Salmo salar	4 days
	Chronic NOEC 0.0125 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days
	Chronic NOEC 1280 µg/l Fresh water	Fish - <i>Pimephales promelas</i> - Embryo	32 days
Hydrochloric acid	Acute LC50 240000 μg/l Marine water	Crustaceans - Carcinus maenas - Adult	48 hours
	Acute LC50 282 ppm Fresh water	Fish - <i>Gambusia affinis</i> - Adult	96 hours

Date of issue/Date	of revision	: 9/19/2023	Date of previous issue	: 6/13/2023	Version	:7	12/16
40.10200-	H&C® INFUSION™ R Wenge Wood	eactive Concret	e Stain		SHW-85-	NA-GHS-MX	<u>(</u>

Section 12. Ecological information

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition: Not available.coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	UN3066	UN3066	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT. Marine pollutant (Sodium Dichromate)
Transport	8	8	8	8	8
hazard class(es)	CORRIGHE Ø	e e	1 1 1	15 22 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Packing group	111	111	ш	Ш	111
Environmental hazards	No.	No.	No.	Yes. The environmentally hazardous substance mark is not required.	Yes.
	vision : 9/19/20 ® INFUSION™ Reactive Co ge Wood		issue : 6/13/202		on : 7 13/1 -85-NA-GHS-MX

Additional	-		-	The	The marine
information				environmentally hazardous substance mark may appear if required by other transportation regulations.	pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Emergency</u> <u>schedules</u> F-A, S- B
	ERG No.	ERG No.	ERG No.		
	153	153	153		
Special precautio				ded for informational pu	
	mo su to of da	ode of transport (sea, itably for that mode o shipment, and compl the person offering th	air, etc.), does not f transport. All pack iance with the appli ne product for transp be trained on all of	a shipping description fo indicate that the product aging must be reviewed cable regulations is the s port. People loading and the risks deriving from the uations.	is packaged for suitability prior sole responsibility unloading
Transport in bulk a to IMO instrument		available.			
	Pro	per shipping name	: Not availab	ole.	
Section 15.	Regulatory	information	1		
International reg	gulations				
Montreal Proto	<u>col</u>				
Not listed.					


Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification Justifi	cation
ACUTE TOXICITY (oral) - ACUTE TOXICITY (inhala SKIN CORROSION/IRRIT SERIOUS EYE DAMAGE/ RESPIRATORY SENSITIZ SKIN SENSITIZATION - C GERM CELL MUTAGENIC CARCINOGENICITY - Cat TOXIC TO REPRODUCTI SPECIFIC TARGET ORG	 Category 3 N - Category 1 IRRITATION - Category 1 ON - Category 1 ON - Category 1 Calculation meth 	od data data od od od od od
<u>History</u> Date of printing Date of issue/Date of	9/19/2023 9/19/2023	
revision Date of previous issue Version	6/13/2023 7	
Key to abbreviations	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Che IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations	

✓ Indicates information that has changed from previously issued version.

Notice to reader

Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buver/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.