



# H&C® SHARKGRIP® SLIP-RESISTANT ADDITIVE



## PRODUCT DESCRIPTION

H&C® SHARKGRIP® Slip-Resistant Additive is a micronized polymer for addition to H&C coatings for slip resistance, fine texturing, and gloss reduction. Due to its low oil absorption and high solvent resistance, it will stir easily into most oil-based and latex-based paints and other coatings with minimal effect on the coating's viscosity. Its low density allows it to stay well suspended in thin materials such as stains.

## FEATURES & BENEFITS

- Add to latex-based and oil-based coatings, stains and sealers
- Spherical-shaped particles provide easier cleanability and are smooth to the touch
- Improves slip-resistance on concrete surfaces
- Does not effect the color the top coat

## RECOMMENDED USES

H&C® SHARKGRIP® Slip-Resistant Additive is formulated for use on concrete and masonry surfaces including inclined Surfaces, Driveways, Garages, Steps, Patios and Pool Decks.

## JOBSITE TEST SECTION

Due to the wide variety of substrates, preparation methods, application methods and environments, it is important to test the product in an inconspicuous spot for adhesion and compatibility prior to full-scale application.

## LIMITATIONS

H&C® SHARKGRIP® Slip-Resistant Additive will increase the coefficient of friction on the coated surface, but due to its small particle size, the coating that this is added to should be considered **slip-resistant but not non-skid**.  
Not for use with wood stains.

## INSTRUCTIONS

Add contents of one 3.2 oz container into one gallon of H&C® Concrete Stain or Sealer. H&C® SHARKGRIP® Slip-Resistant Additive should be mixed into the final topcoat. Mix well and apply with a roller.

**\*Refer to Stain or Sealer label and data page for detailed product guidelines.**

## PHYSICAL PROPERTIES

Physical Properties and Characteristics		
Property	Test Method	Value
Melting Point	ASTM D127	330-335°F

## ORDERING INFORMATION

Clear	Part Number/SMIS
3.2 OZ	50.155004-16/ 6507-12276
16 OZ	50.155005-20/ 6507-12284
19 lb.	50.155008-99/ 6507-12292

## TECHNICAL SERVICES

The information and recommendations set forth in this product data sheet are based on tests conducted by or on behalf of H&C Products Group and The Sherwin-Williams® Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your H&C or Sherwin-Williams representative to obtain the most recent product data sheet.

For technical assistance, call 1-800-867-8246 or visit [www.hcconcrete.com](http://www.hcconcrete.com).

## CAUTION

**CAUTIONS** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area.

**FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room or physician immediately. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

## LIMITED WARRANTY

Seller's and manufacturer's only obligations shall be to replace such quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the applicator's inability to use the product for his/her intended use. The user assumes all risk and liability.