



- Durable high gloss finish
- Seals and protects cement surfaces
- Waterproofs and helps prevent stain damage
- Suitable for driving surfaces

H&C® Wet Look High Gloss Sealer



PRODUCT DESCRIPTION

H&C® Wet Look High Gloss Sealer is designed to add deep penetrating protection to exterior concrete such as driveways, patios, walkways, garage floors and masonry walls. Designed for use over bare concrete or previously stained concrete. This wet look clear protects against UV rays, water seepage and common chemicals.

FEATURES & BENEFITS

- Seals and protects to extend the life of concrete and masonry surfaces.
- Imparts a beautiful high-gloss finish.
- Won't peel, fade, or yellow over time.
- Resists damage from salt, UV rays oil, acids, pool chemicals and heavy traffic.

RECOMMENDED USES

H&C® Wet Look High Gloss Sealer is formulated for use on exterior concrete and masonry surfaces including driveways, walkways, patios, pool decks, garage floors, and block and stucco walls.

COVERAGE RATES

Substrate	sq ft/gal
Concrete floors	200-250
Porous concrete	150-200
Concrete block	125-150
Split-faced block	100-125
Fluted block	75-100
Brick (clay)	100-150

JOBSITE TEST SECTION

Due to the wide variety of substrates, preparation methods, application methods and environments, it is important to test the product in an inconspicuous spot for adhesion and compatibility prior to full-scale application.

LIMITATIONS

Only use on interior surfaces, such as garage floors, if the area allows for good ventilation. Strong solvents, such as gasoline or brake fluid, will dull the cured film. Do not use on wood surfaces.

SURFACE PREPARATION

Bare Concrete: Newly poured concrete must be at least 28 days old. All concrete should be clean, dry and free of laitance, grease, oil, paint and sealers. A high pressure water wash is recommended. * To remove light soil from the surface, use a cleaner degreaser mixed to a 50/50 ratio with water. To remove heavy oil and grease stains, use the cleaner full strength. Before applying product, all horizontal concrete surfaces must be etched first with an etching solution or muriatic acid, following label directions. For very smooth troweled surfaces with no porosity, use etching solution at full strength. For smooth-troweled concrete with some porosity, use 1 part etching solution to 2 parts water. **DO NOT ETCH PAINTED SURFACES.** If mold, mildew or fungus is present, kill and remove with a solution of one cup household bleach to one gallon of water. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution. Prepared concrete should have a pH level of 6 to 10. Allow to dry 24 hours before sealing.

***WARNING:** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. To avoid exposure to lead dust, wear proper protective equipment, such as a properly fitted respirator (NIOSH approved) and follow proper containment and cleanup procedures. For more information, call the National Lead Information Center at 1-800-424-LEAD (in U.S.) or contact your local health authority.

Repair: For the best waterproofing protection on vertical and horizontal concrete and masonry surfaces, use a patch and repair to address spalled concrete. Please note that patching compounds will generally be visible through clear coatings.

TOOLS REQUIRED

- Natural bristle brush
- Lamb's wool or synthetic roller (3/8 inch nap)
- Airless sprayer (pressure 500 to 1000 psi; tip .011 to .013 inch)

APPLICATION INSTRUCTIONS

Wait at least 24 hours after washing surface or after rain before applying H&C® Wet Look High Gloss Sealer. Only apply under dry conditions. Air and concrete surface temperatures should be above 50°F and below 95°F for 24 hours following application.

How to Apply: Stir thoroughly before and during application. Do not shake or whip air into sealer, and do not reduce. When using more than one gallon, intermix all gallons together to ensure color uniformity. Apply with a brush, roller, or airless sprayer. When applying by roller, maintain a wet edge, going in the same direction during the entire application. When spraying, back roll sealer to remove excess, which will ensure an even finish. Do not overapply.

Additional Coats: One coat of H&C® Wet Look High Gloss Sealer is normally sufficient. For best coverage, apply second coat crosswise to the first coat. Two coats are usually sufficient. However, extremely porous surfaces may require a third coat for a uniform appearance. Allow 12 hours dry time between each coat. Allow 72 to 96 hours under good drying conditions before using the surface for heavy traffic or vehicle traffic.

SLIP RESISTANCE

Some surfaces such as inclined driveways, garages, steps and patios may require a slip-resistant additive for safety. Add a slip-resistant additive to the final coat, following label directions. This additive should not be used in place of a nonskid finish.

CLEANUP

Clean spills and spatters immediately with xylene. Clean tools immediately after use with xylene. Use "waterless" hand cleaner to remove dried material from skin. Follow manufacturer's safety recommendations when using any solvent cleaner.

MAINTENANCE

Clean light to moderately soiled surfaces with a 50/50 solution of a Cleaner Degreaser and water or with another neutral-based cleaner, following the manufacturer's directions for use. Use the cleaner full strength for heavy soiling, such as oil and grease stains.

PHYSICAL PROPERTIES

Physical Properties and Characteristics		
Property	Test Method	Value
Dry Time (@ 77°F, 50% RH)	Dry-to-touch	15 mins.
	Foot traffic	1 hour
	Heavy traffic	72-96 hours
	Light Traffic/Recoat	12 hours
VOC	Need to get method	<250 g/L
Finish	ASTM D523	Gloss
QUV Weather Test	ASTM-G151-97	1,000 hours, no effect
Chemical Resistance (after one hour exposure/24 hours recovery) ASTM D1308	2% NaOH	No effect
	5% Tide detergent	No effect
	Gasoline	Dulling
	Brake fluid	Dulling
	Transmission fluid	No effect
	Motor oil	No effect
Volume Solids	ASTM D2832	22% ± 2%
Weight Solids	ASTM D2832	23% ± 2%
Weight per Gallon	ASTM D1475	8.80 lbs.

ORDERING INFORMATION

Clear	Part Number
1 gallon	71.000012-16
5 gallons	71.000013-20

TECHNICAL SERVICES

The information and recommendations set forth in this product data sheet are based on tests conducted by or on behalf of H&C® Products Group and The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your H&C® or Sherwin-Williams representative to obtain the most recent product data sheet.

For technical assistance, call 1-800-867-8246 or visit www.hcconcrete.com.

CAUTION

CAUTIONS: CONTAINS VOLATILE ORGANIC COMPOUNDS.

Contents are **FLAMMABLE**. Vapors may cause flash fires. Keep away from heat, sparks, and open flame. During use and until all vapors are gone: Keep area ventilated - Do not smoke- Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM**

LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

LIMITED WARRANTY

Seller's and manufacturers only obligations shall be to replace such quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the applicator's inability to use the product for his/her intended use. The user assumes all risk and liability.