



QUIK-MARK™ WATER-BASED OVERHEAD MARKING PAINT

Quik-Mark™ Overhead Marking Paint sprays in an upright position, penetrates, and adheres to uneven surfaces. It's the easiest way to mark overhead surfaces in mines, excavation sites, underground utilities and bridges. These high solids, water-based colors give four times greater visibility than conventional paints.

- ✓ Mine marking, excavation & bridge marking
- ✓ Fluorescent colors
- ✓ Fast drying

INDUSTRIAL USE ONLY!

krylonindustrial.com
1-800-247-3266

RECOMMENDED USES

- Marking mines
- Underground utilities
- Construction
- Excavation sites
- Bridges

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. For more information, contact your local health authority. No surface preparation is necessary. Apply directly to desired surface.

CLEAN-UP

After Job Completion: Avoid clogging by turning can upside down and spray until only clear gas appears. Wipe any paint off spray button opening.

TECHNICAL DATA

Vehicle	Water-based: VT Alkyd
Flash Point	-20°F
Weight/Gallon	7.34 lb/gal
VOC/MIR	.66
Spread Rate	664 linear ft(1") for 17 oz.
Shelf life	60 months
Dry Heat Resistance	120°F
Drying Time	To Touch: >10 mins To Recoat: Anytime
Clean-up	Mineral Spirits
Net Wt. / Can Size	12 oz. / 16 oz. 17 oz. / 20 oz.

APPLICATION

APPLICATION CONDITIONS

For best results use when can is between 40°F to 90°F. Shake can vigorously for one minute after mixing ball rattles and occasionally during use. With can in upright position, press the sprayhead to the side and spray 8" to 10" from surface.

CAUTIONS

FOR INDUSTRIAL USE ONLY. Thoroughly review product label and SDS for safety and cautions prior to using this product. Please direct any questions or comments to your local Krylon Industrial Representative.

Note: The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, Krylon Products Group cannot make any warranties as to the end result. Please direct any questions or comments to 1-800-247-3266.

The information and recommendations set forth in the Product Data Sheet are based upon tests conducted by or on behalf of Krylon® Industrial. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Krylon® Industrial dealer or representative to obtain the most recent Product Data Sheet.