# **SAFETY DATA SHEET**

K1100663-

### Section 1. Identification

Dark Machine Gray

Product name	: KRYLON® Industrial IRON GUARD™ DTM Water-Based Anti-Rust Acrylic Coating Dark Machine Gray
Product code	: K1100663-
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: Krylon Products Group
	101 Prospect Avenue NW
	Cleveland, OH 44115
Emergency telephone	: US/Canada: (800) 424-9300
number of the company	Mexico: CHEMTREC Mexico 800-681-9531. Available 24 hours and 365 days per year
Product Information	: US/Canada: (800) 247-3266
Telephone Number	Mexico: Not Available
Transportation Emergency	: US/Canada: (800) 424-9300
Telephone Number	Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Section 2. Hazard	s identification

#### **OSHA/HCS** status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). : CARCINOGENICITY - Category 2 **Classification of the** substance or mixture **GHS** label elements Hazard pictograms Signal word : Warning **Hazard statements** : Suspected of causing cancer. **Precautionary statements Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Response : IF exposed or concerned: Get medical advice or attention. Storage Store locked up. ε. **Disposal** ÷. Dispose of contents and container in accordance with all local, regional, national and international regulations. Supplemental label WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. elements This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details. Date of issue/Date of revision 1/12 : 2/4/2024 Date of previous issue : 9/13/2023 Version : 21 K1100663-KRYLON® Industrial IRON GUARD™ DTM Water-Based Anti-Rust Acrylic Coating SHW-85-NA-GHS-US

### Section 2. Hazards identification

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

Hazards not otherwise classified

: None known.

### Section 3. Composition/information on ingredients

: Mixture

Other means of identification

: Not available.

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Titanium Dioxide	≤10	13463-67-7
Propylene Glycol	≤3	57-55-6
Carbon Black	≤1	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute healt	h effects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	levimptome

#### Over-exposure signs/symptoms

Date of issue/Date	of revision	: 2/4/2024	Date of previous issue	: 9/13/2023	Version	: 21	2/12
K1100663-	KRYLON® Industrial IRON GL Dark Machine Gray	JARD™ DTM Water	-Based Anti-Rust Acrylic Coating		SHW-85-	NA-GHS-US	

## Section 4. First aid measures

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Indication of immediate me	lical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protect	ve equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	<ul> <li>This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.</li> <li>Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).</li> </ul>

Date of issue/Dat	e of revision	: 2/4/2024	Date of previous issue	: 9/13/2023	Version : 21	3/12
K1100663-	KRYLON® Industrial IRON G Dark Machine Gray	GUARD™ DTM Wate	r-Based Anti-Rust Acrylic Coating		SHW-85-NA-GHS-US	

### Section 6. Accidental release measures

Methods and materia	als for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### Control parameters

#### **Occupational exposure limits (OSHA United States)**

Ingredient name	CAS #	Exposure limits		
Titanium Dioxide	13463-67-7	OSHA PEL (United States, 5/2018). TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dus ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirab fraction, finescale particles		
Propylene Glycol	57-55-6	OARS WEEL (United States, 4/2022). TWA: 10 mg/m <sup>3</sup> 8 hours.		
Carbon Black	1333-86-4	NIOSH REL (United States, 10/2020). TWA: 3.5 mg/m <sup>3</sup> 10 hours. OSHA PEL (United States, 5/2018). TWA: 3.5 mg/m <sup>3</sup> 8 hours. ACGIH TLV (United States, 1/2023).		
	/2024 Date of previous issue	: 9/13/2023 Version : 21 4/12 SHW-85-NA-GHS-US		

## Section 8. Exposure controls/personal protection

	TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction
--	--

#### Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Carbon black	1333-86-4	<ul> <li>CA British Columbia Provincial (Canada, 6/2022). TWA: 3 mg/m<sup>3</sup> 8 hours. Form: Inhalable</li> <li>CA Ontario Provincial (Canada, 6/2019). TWA: 3 mg/m<sup>3</sup> 8 hours. Form: Inhalable</li> <li>particulate matter.</li> <li>CA Quebec Provincial (Canada, 6/2022). TWAEV: 3 mg/m<sup>3</sup> 8 hours. Form: inhalable</li> <li>dust</li> <li>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m<sup>3</sup> 8 hours.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 7 mg/m<sup>3</sup> 15 minutes. TWA: 3.5 mg/m<sup>3</sup> 8 hours.</li> </ul>

#### **Occupational exposure limits (Mexico)**

	CAS #	Exposure limits
None.		

#### **Biological exposure indices (United States)**

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

Appropriate eng controls	gineering :	local exhau	ations generate dus st ventilation or othe ntaminants below a	er engineering	controls to keep w	vorker ex		,
Environmental controls	exposure :	This prodution for details.	ict contains a TSC	A regulated c	hemical. See Sec	tion 15	of the US S	DS
		they comply cases, fum	from ventilation or w y with the requireme e scrubbers, filters o essary to reduce em	ents of environr	mental protection l modifications to th	egislatio	on. In some	
Individual prote	ection measures							
Hygiene meas	ures :	eating, smo Appropriate Wash conta	ls, forearms and fac oking and using the e techniques should aminated clothing be e close to the works	lavatory and at be used to ren efore reusing.	the end of the wo nove potentially co Ensure that eyew	orking pe ontamina	riod. ated clothing.	
Eye/face prote	ection :	assessmer gases or du	vear complying with it indicates this is ne usts. If contact is po ment indicates a hig	ecessary to avo	bid exposure to liques owing protection s	uid splas hould be	shes, mists, e worn, unles	S
Date of issue/Date o	f revision	: 2/4/2024	Date of previous issu	e : 9/13/2	2023	Version	:21	5/12
	KRYLON® Industrial IRON G Dark Machine Gray	UARD™ DTM Wate	r-Based Anti-Rust Acrylic Coatin	g		SHW-85-	NA-GHS-US	

## Section 8. Exposure controls/personal protection

Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Molecular weight	÷	Not	applicable.
Viscosity	÷		ematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Decomposition temperature	÷		available.
Auto-ignition temperature			available.
Partition coefficient: n- octanol/water	:	Not a	applicable.
cold water			Partially soluble
Media			Result
Solubility(ies)	:		
Relative density	:	1.11	
Relative vapor density	:	1 [Ai	ir = 1]
Vapor pressure	:	2.3 k	κΡa (17.5 mm Hg)
Lower and upper explosion limit/flammability limit	:		er: 0.6% er: 20.4%
Flammability	:	Not a	available.
Evaporation rate	1	0.09	(butyl acetate = 1)
Flash point	:	Clos	ed cup: Not applicable.
Boiling point, initial boiling point, and boiling range	:	100°	°C (212°F)
Melting point/freezing point	:	Not a	available.
рН	:	9	
Odor threshold	÷	Not a	available.
Odor	:	Not a	available.
Color	:	Not a	available.
Physical state	÷.	Liqui	id.

Date of issue/Date	e of revision	: 2/4/2024	Date of previous issue	: 9/13/2023	Version : 21	6/12
K1100663-	KRYLON® Industrial IRON G	UARD™ DTM Wate	r-Based Anti-Rust Acrylic Coating		SHW-85-NA-GHS-US	

### Section 9. Physical and chemical properties

Heat of combustion : 1.877 kJ/g

### Section 10. Stability and reactivity

Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Incompatible materials	: No specific data.
Conditions to avoid	: No specific data.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propylene Glycol	LD50 Dermal LD50 Oral		20800 mg/kg 20 g/kg	-
Carbon Black	LD50 Oral	Rat	>15400 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
Propylene Glycol	Eyes - Mild irritant	Rabbit	-	100 mg	-
19 - 9	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
	Skin - Mild irritant	Human	-	mg 168 hours 500 mg	-
	Skin - Mild irritant	Woman	-	96 hours 30 %	-
	Skin - Moderate irritant	Child	-	96 hours 30 % C	-
	Skin - Moderate irritant	Human	-	72 hours 104 mg l	-

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Date of issue/Date	of revision	: 2/4/2024
K1100663-	KRYLON® Industrial IRON Dark Machine Gray	N GUARD™ DTM W

### Section 11. Toxicological information

	U		
Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide Carbon Black	-	2B 2B	

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

## Information on the likely : Not available. routes of exposure

Potential acute	<u>health effects</u>	
Eve contact		No known sie

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to	the physical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health e	ffects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.

Date of issue/Date	of revision	: 2/4/2024	Date of previous issue	: 9/13/2023	Version	:21	8/12
K1100663-	KRYLON® Industrial IRON GU Dark Machine Gray	ARD™ DTM Water-I	Based Anti-Rust Acrylic Coating		SHW-85-	NA-GHS-US	

### Section 11. Toxicological information

Developmental effects Fertility effects : No known significant effects or critical hazards.

ts : No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates Not available.

### Section 12. Ecological information

Tox	ici	tv
_		-

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
Propylene Glycol	Acute EC50 >110 ppm Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 1020000 μg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 710000 µg/l Fresh water	Fish - Pimephales promelas	96 hours

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Propylene Glycol	-	-	Readily

#### **Bioaccumulative potential**

Not available.

#### Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods	: This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.
	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

9/12

Date of issue/Date	of revision	: 2/4/2024	Date of previous issue	: 9/13/2023	Version	:21
K1100663-	KRYLON® Industrial IRON GU Dark Machine Gray	JARD™ DTM Water-I	Based Anti-Rust Acrylic Coating		SHW-85-	NA-GHS-US

### Section 14. Transport information

UN number		Classification	Mexico Classification	ΙΑΤΑ	IMDG
	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Special precautions	conside mode o suitably to shipn of the p dangero and on a	odal shipping descrip r container sizes. Th f transport (sea, air, for that mode of tran nent, and compliance erson offering the pr ous goods must be to all actions in case of	e presence of a shi etc.), does not indic nsport. All packaging e with the applicable oduct for transport. rained on all of the r	pping description fo ate that the product g must be reviewed regulations is the s People loading and isks deriving from t	r a particular is packaged for suitability prior sole responsibility unloading
ransport in bulk acc o IMO instruments	Ŭ				
	Proper s Regulatory in	hipping name	: Not available.		

U.S. Federal regulations : TSCA 5(a)2 proposed significant new use rules: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

TSCA 5(a)2 final significant new use rules: Sodium Nitrite

List name	Chemical name	<u>Notes</u>
United States - TSCA 5(a) 2 - Final significant new use rules	Sodium Nitrite	40 CFR 721.4740

#### SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

#### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

#### International regulations

#### **Montreal Protocol**

Date of issue/Date	of revision	: 2/4/2024	Date of previous issue	: 9/13/2023	Version	:21	10/12
K1100663-	KRYLON® Industrial IRON GI Dark Machine Gray	JARD™ DTM Water	Based Anti-Rust Acrylic Coating		SHW-85-	NA-GHS-US	

### Section 15. Regulatory information

Not listed.


Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

### Section 16. Other information

#### Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Dark Machine Grav

	Justification			
CARCINOGENICITY - Cat	Calculation method			
<u>History</u>				
Date of printing	: 2/4/2024			
Date of issue/Date of revision	: 2/4/2024			
Date of previous issue	: 9/13/2023			
Version	: 21			
Key to abbreviations	ation and Labelling of Chemicals s n coefficient vention of Pollution From Ships, 1973 marine pollution)			
Date of issue/Date of revision	: 2/4/2024 Date of previous issue : 9/13/202	3 Version : 21 11/12		
1100663- KRYLON® Industria	IRON GUARD™ DTM Water-Based Anti-Rust Acrylic Coating	SHW-85-NA-GHS-US		

### Section 16. Other information

#### Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.