

# FOOD GRADE PENETRATING OIL



## LU<sup>TM</sup>104

- 

NSF® Nonfood Compounds Program Listed H1 Rated (Registration # 145288)
- 

For use in extreme pressure applications
- 

Minimum - Maximum operational temperature range: Low -40°F (-40°C) • High 475°F (246°C)
- 

Dielectric Strength Value: 39,000 volts
- 

Non-Flammable
- 

Features SPRAY ANYWAY™ Nozzle
- 

HMIS Hazard Rating:  
Health (1) • Flammability (0) • Reactivity (0)

- Quick penetration
- Non-flammable
- Use to loosen rust, scale & corrosion



**PRESERVE. PROTECT. PREVENT.®**

Sprayon® LU<sup>TM</sup>104 Food Grade Penetrating Oil is a synthetic heavy-duty rust penetrant that quickly penetrates nuts and bolts. Its accelerated action loosens rust while penetrating grease, dirt and corrosion. Specifically developed to meet the demands of a safe, low HMIS rating, non-flammable lubricant for food processing areas, LU<sup>TM</sup>104 Food Grade Penetrating Oil can be used to loosen rust, scale and corrosion around fasteners and hose fittings on food processing equipment.

# LUBRICANTS

## FOR USE ON

- Rusted or Frozen Lugs
- Bolts • Repair Work
- Food Plant Equipment
- Tight-Fitting Parts
- General Overhaul
- Scales • Fans • Carts
- Galleys • Bottlers • Chutes
- Conveyors • Racks
- Ovens • Stoves • Fillers
- Mixers • Freezers • Rails
- Cooking Appliances

## FOR USE BY

- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors



LU104

## APPLICATION

Shake well before using. For best results use at room temperature 70°F. Spray in a well ventilated area away from open flame. Apply a thin film and allow to soak in. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth.

## PERFORMANCE

PLASTIC SAFE: Yes (Always test before using)

TEMPERATURE RANGE:

HIGH: 475 °F

LOW: -40 °F

LOAD CAPACITY: Extreme

DIELECTRIC STRENGTH: 39.0 kV

FALEX LOAD (ASTM D-3233A): 3,000 lbs.

DELIVERY: SPRAY ANYWAY™ Nozzle

## PACKAGING

STOCK #: S00104000

UPC CODE: 0-75577-00617-5

FILL WT.: 11.75 oz.

PER CASE: 12

CARTON DIMENSIONS:

L 11.13" x W 8.44" x H 9.94"

## SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

## RESOURCES

MSDS/EDS/PRODUCT DATA

SHEETS: [Sprayon.com](http://Sprayon.com)

CUSTOMER SERVICE:

800-777-2966

TECHNICAL INFORMATION:

800-251-2486

## PROPERTIES

APPEARANCE: Clear

BASE: Synthetic

FILM TYPE: Wet

ODOR: Low

CONTAINS P.T.F.E: No

PROPELLANT: CO<sub>2</sub>

WT./GAL.: 6.67

SPECIFIC GRAVITY: 0.80

% VOC AEROSOL: 0

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

HEAVY METALS: No

FLAMMABLE: No

FLASH POINT: >200°F

SARA 313: None

PROP 65: None

HAPS: None

HAZARD RATING: 1, 0, 0

SHELF LIFE: 3 years from date of manufacture

## NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145288



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.



Scan this code with your mobile phone to download the NSF® Registration Letter for this product

Distributed by:

PRESERVE. PROTECT. PREVENT.®



**Sprayon® Products**

101 Prospect Ave. NW

Cleveland, OH 44115

[Sprayon.com](http://Sprayon.com)

800-777-2966