

FOOD GRADE LOW TEMP LUBRICANT



LUTM 214



NSF® Nonfood Compounds Program Listed H1 Rated (Registration #145775)



For use in high pressure applications



Minimum operational temperature: -78°F (-61°C)



HMS Hazard Rating:
Health (1) • Flammability (2) • Reactivity (0)

- Non-Staining
- Excellent low temperature performance
- Reduces friction and wear



PRESERVE. PROTECT. PREVENT.®

Sprayon® LUTM214 Food Grade Low Temperature Lubricant is a multi-service lubricant for extended service under extremely low temperature conditions (as low as -78 °F). Its blend of quality, pure synthetic oils are treated with the most effective extreme pressure, corrosion inhibitors, anti-oxidant, anti-foam and anti-wear additives. This unique combination provides maximum equipment protection in extremely low temperature applications.

LUBRICANTS

FOR USE ON

General Purpose Oiling of Food Processing Equipment Exposed to Cold Temperatures such as:

- Spirial Freezers
- Freezer Bearings • Fans
- Chains • Gear Boxes
- Conveyers • Rollers
- Bottle & Carton Filling Machinery

FOR USE BY

- Bakeries • Bottlers
- Breweries • Canneries
- Dairies • Egg Processors
- Meat & Poultry Processors



LU214

APPLICATION

Shake Well Before using. Do not apply while equipment is running. For best results use at room temperature 70 °F. Spray in a well ventilated area away from open flame. Apply a thin film and allow to set. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth.

PERFORMANCE

PLASTIC & RUBBER SAFE: Yes
(always test before using)
TEMPERATURE RANGE:
HIGH: 478 °F
LOW: -78 °F
LOAD CAPACITY: High
CORROSION PREVENTION (ASTM D-1743): Pass
4-BALL WEAR SCAR (ASTM D-2266): 0.35 mm

PACKAGING

STOCK #: S00214000
UPC CODE: 0-75577-00631-1
FILL WT.: 15 oz.
PER CASE: 12
CARTON DIMENSIONS:
L 11.13" x W 8.44" x H 9.94"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: Sprayon.com
CUSTOMER SERVICE: 800-777-2966
TECHNICAL INFORMATION: 800-251-2486

PROPERTIES

APPEARANCE: Clear
BASE: Synthetic
FILM TYPE: Wet (ISO 68)
ODOR: Low
CONTAINS P.T.F.E: No
PROPELLANT: Hydrocarbon
WT./GAL.: 6.27
SPECIFIC GRAVITY: 0.75
% VOC AEROSOL: 20%
V.O.C. COMPLIANT CALIFORNIA: Yes
(For use in manufacturing process only)
V.O.C. COMPLIANT OTC STATES: Yes
SARA 313: No
PROP 65: No
HAPS: No
FLAMMABLE: Yes
FLASH POINT: >200 F
HAZARD RATING: 1, 2, 0
SHELF LIFE: 3 years from date of manufacture

NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145775



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.



Scan this code with your mobile phone to download the NSF® Registration Letter for this product

Distributed by:

PRESERVE. PROTECT. PREVENT.®



Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
800-777-2966