ANTI-STATIC SPRAY



\$P[™]610



- Neutralizes static electricity
- Safe on plastic, paper & fabric
- Dries instantly
- Clear non-staining film



PRESERVE. PROTECT. PREVENT.

Sprayon[®] SP[™]610 Anti-Static Spray neutralizes static electricity generated by friction and low humidity conditions. A light coating eliminates static charges immediately. This film remains on the surface to suppress static accumulation. It also repels lint and dust. Effective on plastic, paper, cellophane, rubber, leather, nylon, cloth and thread.

SPECIALTY PRODUCTS

USES

- Printing and bindery equipment
- Sheet cutters
- Textile equipment
- Rewinders
- Paper and packing machinery
- Production feeders
- Slitters

APPLICATION

Use in a well ventilated area. Shake can for 1 minute. Hold container upright 8-10" from surface. Do not apply in continuous spray. Apply several light coats. For best results, use at room temperature (70°F-90°F). Occasional repeat applications will maintain efficiency.

PERFORMANCE

- NSF Registration Number 130080; P1 Rated
- A fast and effective way to remove static charge from a variety of surfaces
- · Will not harm or discolor fabrics
- DRYING TIME @ 70°F @ 50% R.H. TO TOUCH: 5-10 minutes

PACKAGING

STOCK #: S00610

UPC CODE: 0-75577-90610-9

FILL WT.: 11.5 oz.
PER CASE: 12
CARTON DIMENSIONS:

L 11.13" x W 8.44" x H 8.38"

PROPERTIES

BASE TYPE: Solvent
APPEARANCE: Clear
ODOR: Vanilla

PROPELLANT: Hydrocarbon

WT./GAL.: 5.90 SPECIFIC GRAVITY: 0.71 % V.O.C.: 95.50%

V.O.C. COMPLIANT CALIFORNIA: Yes V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes
FLASH POINT: < 0 °F
HAZARD RATING: 3,4,0

SHELF LIFE: 3 years from date of manufacture



RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: sprayon.com CUSTOMER SERVICE: 1-800-777-2966 TECHNICAL INFORMATION: 1-800-251-2486

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



SP610

© 2010 Sprayon® Products Made in U.S.A.



Distributed by:



Sprayon® Products

101 Prospect Ave. NW Cleveland, OH 44115 Sprayon.com 1-800-777-2966