

FOOD GRADE ANTI-SEIZE



LUTM621

**NSF
H1**

NSF® Nonfood Compounds Program Listed H1 Rated (Registration # 145280)

**HIGH
PRESSURE**

For use in high pressure applications

**MAX
TEMP
1800°F/
982°C**

Maximum Operational Temperature:
1,800 °F (982 °C)

**CONTAINS
P.T.F.E.**

Contains P.T.F.E.
(polytetrafluoroethylene)

**MIL SPEC
MIL-A-907E**

Military Specification: MIL-A-907E

**H 2
F 3
R 0**

HMIS Hazard Rating:
Health (2) • Flammability (3) • Reactivity (0)

- Water & Steam resistant
- Superior leak proof seal
- Effective to 1800 °F
- Meets MIL-A-907E



PRESERVE. PROTECT. PREVENT.®

Sprayon® LUTM621 Food Grade Anti-Seize is a premium, synthetic, food grade, non-drying thread sealant and anti-seize compound. Formulated with a balanced blend of P.T.F.E. and other lubricating solids, LUTM621 has been engineered to provide a superior leak-proof seal for the life of the connection while at the same time maintaining its anti-seize capabilities allowing for easy disassembly without thread damage.

LUBRICANTS

FOR USE ON

- Brass, Black Iron, Galvanized Steel, Stainless Steel, Aluminum, Copper, PVC & Fiberglass Reinforced Pipes
- Threaded Fittings • Pins
- Bushings • Valve Shafts
- Flanges • Plugs • Chains
- Manifold Studs & Bolts
- Sprockets • Splines
- Worm Gears • Brake Cams
- Rig Drives • Winches

FOR USE BY

- Bakeries • Bottlers
- Breweries • Canners
- Dairies • Egg Processors
- Meat & Poultry Processors



LU621

APPLICATION

Shake well before using. Do not apply while equipment is running. For best results use at room temperature 70 °F. Spray in a well ventilated area away from open flame. Apply a thin film and allow to set. Only use necessary amount to achieve desired results. Wipe off excess with clean cloth.

PERFORMANCE

PLASTIC & RUBBER SAFE: Yes

(Always test before using)

TEMPERATURE RANGE:

HIGH: 1800 °F

LOW: 5 °F

LOAD CAPACITY: High

CORROSION PREVENTION (ASTM D-1743): Pass

WORKED PENETRATION (ASTM D-217)

60 Strokes: 310

10k Strokes: 340

PACKAGING

STOCK #: S00621000

UPC CODE: 0-75577-00625-0

FILL WT.: 15 oz.

PER CASE: 12

CARTON DIMENSIONS:

L 11.13" x W 8.44" x H 9.94"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

RESOURCES

MSDS/EDS/PRODUCT DATA

SHEETS: Sprayon.com

CUSTOMER SERVICE:

800-777-2966

TECHNICAL INFORMATION:

800-251-2486

PROPERTIES

APPEARANCE: White

BASE: Synthetic

FILM TYPE: Grease Like (NLGI 1)

ODOR: Low / Sweet

CONTAINS P.T.F.E: Yes

PROPELLANT: Hydrocarbon Blend

WT./GAL.: 6.22

SPECIFIC GRAVITY: 0.75

% VOC AEROSOL: 64

V.O.C. COMPLIANT CALIFORNIA: Yes

(For use in manufacturing process only)

V.O.C. COMPLIANT OTC STATES: Yes

SARA 313: None

HAPS: None

FLAMMABLE: Yes

FLASH POINT: <0 °F

HAZARD RATING: 2, 3, 0

SHELF LIFE: 3 years from date of manufacture

NSF® NONFOOD COMPOUNDS PROGRAM LISTED

H1 Rated - Registration #145280



This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas.

Scan this code with your mobile phone to download the NSF® Registration Letter for this product

