

CARTON STENCIL INK - RED

SPTM 3106



HMIS Hazard Rating:
Health (2) • Flammability (3) • Reactivity (0)

RED

Coating Color: Red

FS595

STD.31136

Federal Standard 595 Color: STD.31136

QUICK
DRY

15 MIN.

Dry to touch time: 15 minutes

MAX
TEMP

200°F/
93°C

Maximum operational temperature:
200 °F (93 °C)



Features EZ-Touch® comfort nozzle

- Meets MIL-A-A-208B requirements
- Match Federal 595 Standards
- New & improved formula and spray package
- Waterproof and weather resistant



PRESERVE. PROTECT. PREVENT.™

Sprayon® SPTM 3106 Carton Stencil Ink (Red) is highly opaque and fast drying. Specifically formulated for stenciling and marking a wide variety of surfaces. Bold, high-contrast color leaves a sharp, clean edge without smearing, smudging or rippling. Temporarily marks slightly-oily surfaces. Excellent durability and adhesion to hot surfaces. Ideal for color coding and marking of steel coils.

USES

- Cartons
- Corrugated boxes
- Fiber drums
- Lumber
- Wood crates
- Steel coils
- Metals
- Paper
- Fabrics
- Plaster
- Stone
- Glass
- Asphalt
- Concrete
- Virtually any porous or non-porous surface



SP3106

© 2010 Sprayon® Products Made in U.S.A.

SPECIALTY PRODUCTS

APPLICATION

Surface must be free of grease, dirt, and oil. Use in a well ventilated area. Shake can until ball rattles for 1 minute. Hold container upright 6-8" from the surface. Do not apply in continuous spray. To avoid runs, apply several thin coats allowing paint film to become tacky between coats. For best results, use at room temperature (70°F-90°F). After spraying, turn can upside down and spray until clear propellant comes out.

PERFORMANCE

DRY HEAT RESISTANCE: 180°F - 200°F

- Meets MIL-A-A-208B
- Matches Federal Standard 595 colors.
- Fast drying
- Will not smear
- Excellent for product coding & stenciling
- Equipped with EZ TOUCH® Standard Nozzle

DRYING TIME @ 70°F @ 50%R.H.:

TO TOUCH: 5 minutes

TO HANDLE: 15 minutes

FULL CURE: 1 hours

RECOAT: Anytime

CLEAN UP: Mineral Spirits

PACKAGING

STOCK #: S03106

UPC CODE: 0-75577-93106-4

FILL WT.: 12 oz.

PER CASE: 12

CARTON DIMENSIONS:

L 11.13" x W 8.44" x H 8.38"

PROPERTIES

RESIN TYPE: Alkyd

APPEARANCE: Red

PROPELLANT: Hydrocarbon

SHEEN: Flat

% SOLIDS: 8.20%

WT./GAL.: 6.07

SPECIFIC GRAVITY: 0.73

H.A.P.S.: No

SARA 313: No

%V.O.C.: 31.00%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: < 0 °F

COVERAGE PER AEROSOL (THEORETICAL):

10 sq. ft. per can

HAZARD CODE: 2,3,0

SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA

SHEETS: sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966