

FOOD GRADE SILICONE LUBRICANT



LUTM210

- 
Light Pressure Lubricant
- 
NSF[®] Registered; H2 Rated (Lubricants with no contact) (Registration # 115089)
- 
Minimum - Maximum operational temperature range: Low -40 °F (-40 °C) • High 450 °F (232 °C)
- 
5% Silicone
- 
Features Spray AnywayTM nozzle
- 
HMIS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Meets FDA regulations
- Safe on styrene and urethanes
- Stops sticking without transfer



PRESERVE. PROTECT. PREVENT.TM

Sprayon[®] LUTM210 Food Grade Silicone Lubricant is a 5% low-viscosity silicone formula that is compatible with most surfaces. Meets FDA regulation described in Title 21 paragraph 178.3570, when no more than 1 ppm is imparted. NSF H1 rated for use in federally-inspected meat and poultry plants. Effective from -40°F to +450°F. Repels water and is non-corrosive to metals. An excellent lubricant on plastic, fiber gears, extruded parts, wood-to-wood sliding applications and on rubber.

LUBRICANTS

USES

- Slides
- Food and drug processing equipment
- Guides
- Knives
- Food racks
- Slicers
- Heat sealing equipment
- Saws
- Overhead drives
- Grinders
- Belts
- Mixers
- Bottling machines
- Conveyors
- Chutes



LU210

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70F.) Shake well before using. Spray at a distance of 10" to 14" from surface.

PERFORMANCE

PLASTIC SAFE: Yes

TEMPERATURE RANGE:

LOW: -40°F

HIGH: 450°F

LOAD CAPACITY: Light

- NSF Registration Number 115089, H1 Rated
- Penetrant
- Water-Displacer
- Rust Inhibitor
- Equipped with SPRAY ANYWAY™ valve
- Equipped with an extension tube for hard-to-reach areas

PACKAGING

Stock #: S00210

UPC Code: 0-75577-90210-1

Fill Wt.: 10 oz.

Per Case: 12

Carton Dimensions:

L 11.13" x W 8.44" x H 8.38"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

PHYSICAL

APPEARANCE: Clear liquid

ODOR: Slight solvent

PROPELLANT: Hydrocarbon

WT./GAL.: 5.42

SPECIFIC GRAVITY: 0.65

VISCOSITY: Low

PAINTABLE: No

% VOC AEROSOL: 95.00%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING: 2,4,0

SHELF LIFE: 3 years from date of manufacture

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

PRESERVE. PROTECT. PREVENT.



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-LU210