

# FOOD GRADE SILICONE LUBRICANT




## LU™ 910



For use in light pressure applications



3.5% Silicone



Minimum - Maximum operational temperature range: Low -58 °F (-50 °C) • High 575 °F (302 °C)



Features Spray Anyway® Nozzle



HMS Hazard Rating:  
Health (2) • Flammability (3) • Reactivity (0)

- Formulated Without Methylene Chloride
- Works from -58°F to +575°F
- Meets FDA Regulations
- Low Viscosity - No Buildup



PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 910 Food Grade Silicone Lubricant is a low viscosity silicone that is colorless, odorless and tasteless. Sprayon's formula is effective from -58°F (-50°C) to 575°F (302°C). Prevents "sticking" without transferring to end products. LU™ 910 Food Grade Silicone Lubricant can be used in proximity to foods where petroleum products and other organics would contaminate. Meets FDA regulations when no more than 1 PPM residual is imparted.

## USES

- Slides
- Guide rails
- Knives
- Slicers
- Saws
- Grinders
- Dough mixers
- Guards
- Heat sealing equipment
- Conveyors
- Food racks
- Ovens
- Bottling machines
- All food and drug processing



LU910

© 2010 Sprayon® Products Made in U.S.A.

## LUBRICANTS

### APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature. Shake well before using. Spray at a distance of 10" to 12" from surface.

**NOTE:** May harm certain plastics (styrene or urethane types), elastomers and air-dried painted surfaces. Test product on non-essential similar material prior to application.

### PERFORMANCE

PLASTIC SAFE: No

TEMPERATURE RANGE:

LOW: -58°F

HIGH: 575°F

LOAD CAPACITY: Light

- Penetrant
- Water-Displacer
- Rust Inhibitor
- Meets FDA regulations when no more than 1 ppm is applied
- Equipped with SPRAY ANYWAY™ valve
- Equipped with an extension tube for hard-to-reach areas

### PHYSICAL

APPEARANCE: Clear liquid

ODOR: Chlorinated

PROPELLANT: Hydrocarbon

WT./GAL.: 6.4

SPECIFIC GRAVITY: 0.77

VISCOSITY: Low

PAINTABLE: No

% VOC AEROSOL: 50.00%

V.O.C. COMPLIANT CALIFORNIA: Yes

V.O.C. COMPLIANT OTC STATES: Yes

FLAMMABLE: Yes

FLASH POINT: <0°F

HAZARD RATING: 2,3,0

SHELF LIFE: 3 years from date of manufacture

### PACKAGING

Stock #: S00910000

UPC Code: 0-75577-75931-6

Fill Wt.: 12 oz.

Per Case: 12

Carton Dimensions:

L 11.13" x W 8.44" x H 8.38"

### RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:

sprayon.com

CUSTOMER SERVICE:

1-800-777-2966

TECHNICAL INFORMATION:

1-800-251-2486

### SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



Distributed by:

PRESERVE. PROTECT. PREVENT.



**Sprayon® Products**

101 Prospect Ave. NW  
Cleveland, OH 44115  
Sprayon.com  
1-800-777-2966

310-PDS-LU910