

# SAFETY DATA SHEET

SC0941000

## Section 1. Identification

**Product name** : WL™941 Dry Weld Spatter Protectant Aerosol  
**Product code** : SC0941000  
**Other means of identification** : Not available.  
**Product type** : Aerosol.  
**Relevant identified uses of the substance or mixture and uses advised against**  
Paint or paint related material.

**Manufacturer** : Sprayon Products Group  
101 W. Prospect Avenue,  
Cleveland, Ohio 44115  
**National contact** : Sprayon Products  
180 Brunel Road  
Mississauga, Ontario L4Z 1T5 Canada

**Emergency telephone number of the company** : US / Canada: (800) 424-9300  
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

**Product Information Telephone Number** : US / Canada: (800) 247-3266  
Mexico: Not Available


**Transportation Emergency Telephone Number** : US / Canada: (800) 424-9300  
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

## Section 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE AEROSOLS - Category 1  
GASES UNDER PRESSURE - Compressed gas  
ACUTE TOXICITY (inhalation) - Category 4  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
CARCINOGENICITY - Category 1B  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1  
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 13.8% (oral), 69.2% (dermal), 13.8% (inhalation)

### GHS label elements

#### Hazard pictograms



**Signal word** : Danger

**Date of issue/Date of revision** : 2/5/2024 **Date of previous issue** : 1/23/2024

SC0941000 WL™941 Dry Weld Spatter Protectant Aerosol

**Version** : 16.01 1/18

SHW-85-NA-GHS-CA

Section 2. Hazards identification

- Hazard statements

: Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

Causes serious eye irritation.

Harmful if inhaled.

May cause drowsiness or dizziness.

May cause cancer.

Causes damage to organs through prolonged or repeated exposure. (lungs)
- Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.

Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage

: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.  
  
Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.
- Hazards not otherwise classified

: None known.
- Section 3. Composition/information on ingredients
- Substance/mixture

: Mixture

Other means of identification

: Not available.
- CAS number/other identifiers
- | Ingredient name       | % by weight | CAS number |
|-----------------------|-------------|------------|
| Tetrachloroethylene   | 55.4        | 127-18-4   |
| Propane               | 13.77       | 74-98-6    |
| Butane                | 13.23       | 106-97-8   |
| Acetone               | 10          | 67-64-1    |
| Talc                  | 7.06        | 14807-96-6 |
| Xylene, mixed isomers | 0.12        | 1330-20-7  |
- Any concentration shown as a range is to protect confidentiality or is due to batch variation.
- There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.
- Date of issue/Date of revision

: 2/5/2024

Date of previous issue

: 1/23/2024

Version

: 16.01

2/18

SC0941000

WL™941 Dry Weld Spatter Protectant Aerosol

SHW-85-NA-GHS-CA

## Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness

## Section 4. First aid measures

**Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

**Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
halogenated compounds  
carbonyl halides  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Remark** : Flammable aerosol.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put

## Section 6. Accidental release measures

on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid breathing gas. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### [Control parameters](#)

#### [Occupational exposure limits \(OSHA United States\)](#)

| Ingredient name       | CAS #      | Exposure limits   |
|-----------------------|------------|---|
| Tetrachloroethylene   | 127-18-4   | <b>ACGIH TLV (United States, 1/2023).</b><br>TWA: 25 ppm 8 hours.<br>TWA: 170 mg/m <sup>3</sup> 8 hours.<br>STEL: 100 ppm 15 minutes.<br>STEL: 685 mg/m <sup>3</sup> 15 minutes.<br><b>OSHA PEL Z2 (United States, 2/2013).</b><br>TWA: 100 ppm 8 hours.<br>CEIL: 200 ppm<br>AMP: 300 ppm 5 minutes.                          |
| Propane               | 74-98-6    | <b>NIOSH REL (United States, 10/2020).</b><br>TWA: 1000 ppm 10 hours.<br>TWA: 1800 mg/m <sup>3</sup> 10 hours.<br><b>OSHA PEL (United States, 5/2018).</b><br>TWA: 1000 ppm 8 hours.<br>TWA: 1800 mg/m <sup>3</sup> 8 hours.<br><b>ACGIH TLV (United States, 1/2023). Oxygen Depletion [Asphyxiant]. Explosive potential.</b> |
| Butane                | 106-97-8   | <b>NIOSH REL (United States, 10/2020).</b><br>TWA: 800 ppm 10 hours.<br>TWA: 1900 mg/m <sup>3</sup> 10 hours.<br><b>ACGIH TLV (United States, 1/2023). [Butane isomers] Explosive potential.</b><br>STEL: 1000 ppm 15 minutes.  |
| Acetone               | 67-64-1    | <b>ACGIH TLV (United States, 1/2023).</b><br>TWA: 250 ppm 8 hours.<br>STEL: 500 ppm 15 minutes.<br><b>NIOSH REL (United States, 10/2020).</b><br>TWA: 250 ppm 10 hours.<br>TWA: 590 mg/m <sup>3</sup> 10 hours.<br><b>OSHA PEL (United States, 5/2018).</b><br>TWA: 1000 ppm 8 hours.<br>TWA: 2400 mg/m <sup>3</sup> 8 hours. |
| Talc                  | 14807-96-6 | <b>NIOSH REL (United States, 10/2020).</b><br>TWA: 2 mg/m <sup>3</sup> 10 hours. Form: Respirable fraction<br><b>ACGIH TLV (United States, 1/2023).</b><br>TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction  |
| Xylene, mixed isomers | 1330-20-7  | <b>OSHA PEL (United States, 5/2018). [Xylenes (o-, m-, p-isomers)]</b><br>TWA: 100 ppm 8 hours.<br>TWA: 435 mg/m <sup>3</sup> 8 hours.<br><b>ACGIH TLV (United States, 1/2023). [p-xylene and mixtures containing p-xylene] Ototoxicant.</b><br>TWA: 20 ppm 8 hours.  |

#### [Occupational exposure limits \(Canada\)](#)

## Section 8. Exposure controls/personal protection

| Ingredient name     | CAS #    | Exposure limits  |
|---------------------|----------|--|
| Tetrachloroethylene | 127-18-4 | <b>CA Alberta Provincial (Canada, 6/2018).</b><br>15 min OEL: 678 mg/m <sup>3</sup> 15 minutes.<br>15 min OEL: 100 ppm 15 minutes.<br>8 hrs OEL: 25 ppm 8 hours.<br>8 hrs OEL: 170 mg/m <sup>3</sup> 8 hours.<br><b>CA British Columbia Provincial (Canada, 6/2022).</b><br>TWA: 25 ppm 8 hours.<br>STEL: 100 ppm 15 minutes.<br><b>CA Ontario Provincial (Canada, 6/2019).</b><br>TWA: 25 ppm 8 hours.<br>STEL: 100 ppm 15 minutes.<br><b>CA Quebec Provincial (Canada, 6/2022).</b><br>TWAEV: 25 ppm 8 hours.<br>TWAEV: 170 mg/m <sup>3</sup> 8 hours.<br>STEV: 100 ppm 15 minutes.<br>STEV: 685 mg/m <sup>3</sup> 15 minutes.<br><b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br>STEL: 100 ppm 15 minutes.<br>TWA: 25 ppm 8 hours. |
| Normal propane      | 74-98-6  | <b>CA Alberta Provincial (Canada, 6/2018).</b><br>8 hrs OEL: 1000 ppm 8 hours.<br><b>CA Quebec Provincial (Canada, 6/2022).</b><br>TWAEV: 1000 ppm 8 hours.<br>TWAEV: 1800 mg/m <sup>3</sup> 8 hours.<br><b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br>STEL: 1250 ppm 15 minutes.<br>TWA: 1000 ppm 8 hours.<br><b>CA British Columbia Provincial (Canada, 6/2022). Oxygen Depletion [Asphyxiant]. Explosive potential.</b><br><br><b>CA Ontario Provincial (Canada, 6/2019). Oxygen Depletion [Asphyxiant]. Explosive potential.</b>  |
| Butane              | 106-97-8 | <b>CA Alberta Provincial (Canada, 6/2018).</b><br>8 hrs OEL: 1000 ppm 8 hours.<br><b>CA Quebec Provincial (Canada, 6/2022).</b><br>TWAEV: 800 ppm 8 hours.<br>TWAEV: 1900 mg/m <sup>3</sup> 8 hours.<br><b>CA Saskatchewan Provincial (Canada, 7/2013). [Butane all isomers]</b><br>STEL: 1250 ppm 15 minutes.<br>TWA: 1000 ppm 8 hours.<br><b>CA British Columbia Provincial (Canada, 6/2022). [butane, all isomers] Explosive potential.</b><br>STEL: 1000 ppm 15 minutes.<br><b>CA Ontario Provincial (Canada, 6/2019). [Butane, All isomers] Explosive potential.</b><br>STEL: 1000 ppm 15 minutes.  |
| acetone             | 67-64-1  | <b>CA Alberta Provincial (Canada, 6/2018).</b><br>8 hrs OEL: 1200 mg/m <sup>3</sup> 8 hours.   |



## Section 8. Exposure controls/personal protection

|                         |            |   |
|-------------------------|------------|---|
|                         |            | <p>15 min OEL: 1800 mg/m<sup>3</sup> 15 minutes.<br/>8 hrs OEL: 500 ppm 8 hours.<br/>15 min OEL: 750 ppm 15 minutes.<br/><b>CA British Columbia Provincial (Canada, 6/2022).</b><br/>TWA: 250 ppm 8 hours.<br/>STEL: 500 ppm 15 minutes.<br/><b>CA Ontario Provincial (Canada, 6/2019).</b><br/>TWA: 250 ppm 8 hours.<br/>STEL: 500 ppm 15 minutes.<br/><b>CA Quebec Provincial (Canada, 6/2022).</b><br/>TWA: 250 ppm 8 hours.<br/>STEL: 500 ppm 15 minutes.<br/><b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br/>STEL: 750 ppm 15 minutes.<br/>TWA: 500 ppm 8 hours.</p>   |
| talc (none asbestiform) | 14807-96-6 | <p><b>CA British Columbia Provincial (Canada, 6/2022).</b> Notes: the value is for particulate matter containing no asbestos and less than 1% crystalline silica.<br/>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable<br/><b>CA Quebec Provincial (Canada, 6/2022).</b><br/>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable dust.<br/><b>CA Alberta Provincial (Canada, 6/2018).</b><br/>8 hrs OEL: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate<br/><b>CA Ontario Provincial (Canada, 6/2019).</b><br/>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate matter.<br/>TWA: 2 f/cc 8 hours.<br/><b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br/>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</p>   |
| Xylene                  | 1330-20-7  | <p><b>CA Alberta Provincial (Canada, 6/2018).</b><br/><b>[Dimethylbenzene (o,m &amp; p isomers)]</b><br/>8 hrs OEL: 100 ppm 8 hours.<br/>15 min OEL: 651 mg/m<sup>3</sup> 15 minutes.<br/>15 min OEL: 150 ppm 15 minutes.<br/>8 hrs OEL: 434 mg/m<sup>3</sup> 8 hours.<br/><b>CA British Columbia Provincial (Canada, 6/2022).</b> [Xylene (o, m &amp; p isomers)]<br/>TWA: 100 ppm 8 hours.<br/>STEL: 150 ppm 15 minutes.<br/><b>CA Quebec Provincial (Canada, 6/2022).</b><br/><b>[Xylene (o-,m-,p- isomers)]</b><br/>TWA: 100 ppm 8 hours.<br/>TWA: 434 mg/m<sup>3</sup> 8 hours.<br/>STEL: 150 ppm 15 minutes.<br/>STEL: 651 mg/m<sup>3</sup> 15 minutes.<br/><b>CA Ontario Provincial (Canada, 6/2019).</b><br/><b>[Xylene (o-, m-, p-isomers)]</b><br/>STEL: 150 ppm 15 minutes.<br/>TWA: 100 ppm 8 hours.<br/><b>CA Saskatchewan Provincial (Canada,</b></p> |



## Section 8. Exposure controls/personal protection

7/2013). [Xylene (o, m-, p-isomers)]  
 STEL: 150 ppm 15 minutes.  
 TWA: 100 ppm 8 hours.

### Occupational exposure limits (Mexico)

| Ingredient name     | CAS #    | Exposure limits  |
|---------------------|----------|--|
| Tetrachloroethylene | 127-18-4 | <b>NOM-010-STPS-2014 (Mexico, 4/2016).</b><br>TWA: 25 ppm 8 hours.<br>STEL: 100 ppm 15 minutes.  |
| Acetone             | 67-64-1  | <b>NOM-010-STPS-2014 (Mexico, 4/2016).</b><br>TWA: 500 ppm 8 hours.<br>STEL: 750 ppm 15 minutes. |

### Biological exposure indices (United States)

| Ingredient name       | Exposure indices  |
|-----------------------|---|
| Tetrachloroethylene   | <b>ACGIH BEI (United States, 1/2023)</b><br>BEI: 3 ppm, tetrachloroethylene [in end-exhaled air]. Sampling time: prior to shift.<br>BEI: 0.5 mg/l, tetrachloroethylene [in blood]. Sampling time: prior to shift. |
| Acetone               | <b>ACGIH BEI (United States, 1/2023)</b><br>BEI: 25 mg/l, acetone [in urine]. Sampling time: end of shift.  |
| Xylene, mixed isomers | <b>ACGIH BEI (United States, 1/2023) [xylenes (technical or commercial grade)]</b><br>BEI: 1.5 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.                                      |

### Biological exposure indices (Canada)

No exposure indices known.

### Biological exposure indices (Mexico)

| Ingredient name     | Exposure indices  |
|---------------------|---|
| Tetrachloroethylene | <b>Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)</b><br>BEI: 0.5 mg/L, tetrachlorethylene [in blood]. Sampling time: before work shift.<br>BEI: 3 ppm, tetrachlorethylene [in final exhaled breath]. Sampling time: before work shift.          |
| Acetone             | <b>Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)</b><br>BEI: 50 mg/L [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.], acetone [in urine]. Sampling time: at the end of the work shift. |

## Section 8. Exposure controls/personal protection

|  |  |
|--|--|
| <b>Appropriate engineering controls</b>      | : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.  |
| <b>Environmental exposure controls</b>       | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.   |
| <b><u>Individual protection measures</u></b> |  |
| <b>Hygiene measures</b>                      | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.  |
| <b>Eye/face protection</b>                   | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.   |
| <b><u>Skin protection</u></b>                |  |
| <b>Hand protection</b>                       | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| <b>Body protection</b>                       | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.  |
| <b>Other skin protection</b>                 | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |
| <b>Respiratory protection</b>                | : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.   |

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### **Appearance**

|                                     |                   |
|-------------------------------------|-------------------|
| <b>Physical state</b>               | : Liquid.         |
| <b>Color</b>                        | : Not available.  |
| <b>Odor</b>                         | : Not available.  |
| <b>Odor threshold</b>               | : Not available.  |
| <b>pH</b>                           | : Not applicable. |
| <b>Melting point/freezing point</b> | : Not available.  |

## Section 9. Physical and chemical properties

|  |   |
|--|---|
| <b>Boiling point, initial boiling point, and boiling range</b> | : Not available.  |
| <b>Flash point</b>   | : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup] |
| <b>Evaporation rate</b>  | : 5.6 (butyl acetate = 1)                                 |
| <b>Flammability</b>  | : Flammable aerosol.                                      |
| <b>Lower and upper explosion limit/flammability limit</b>      | : Lower: 1.9%<br>Upper: 12.8%                             |
| <b>Vapor pressure</b>  | : 101.3 kPa (760 mm Hg)                                   |
| <b>Relative vapor density</b>                                  | : 1.55 [Air = 1]  |
| <b>Relative density</b>  | : 0.99  |
| <b>Solubility(ies)</b>   | :   |

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

|   |   |
|---|---|
| <b>Partition coefficient: n-octanol/water</b> | : Not applicable.                                   |
| <b>Auto-ignition temperature</b>              | : Not available.                                    |
| <b>Decomposition temperature</b>              | : Not available.                                    |
| <b>Viscosity</b>                              | : Kinematic (40°C (104°F)): <20.5 mm²/s (<20.5 cSt) |
| <b>Molecular weight</b>                       | : Not applicable.                                   |
| <b><u>Aerosol product</u></b>                 |   |
| <b>Type of aerosol</b>                        | : Spray   |
| <b>Heat of combustion</b>                     | : 16.949 kJ/g                                       |

## Section 10. Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.           |
| <b>Chemical stability</b>                 | : The product is stable.   |
| <b>Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| <b>Conditions to avoid</b>                | : Avoid all possible sources of ignition (spark or flame).   |
| <b>Incompatible materials</b>             | : No specific data.  |
| <b>Hazardous decomposition products</b>   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

## Section 11. Toxicological information

| Product/ingredient name | Result                | Species | Dose                     | Exposure |
|-------------------------|-----------------------|---------|--------------------------|----------|
| Tetrachloroethylene     | LD50 Oral             | Rat     | 2629 mg/kg               | -        |
| Butane                  | LC50 Inhalation Vapor | Rat     | 658000 mg/m <sup>3</sup> | 4 hours  |
| Acetone                 | LD50 Oral             | Rat     | 5800 mg/kg               | -        |
| Xylene, mixed isomers   | LC50 Inhalation Gas.  | Rat     | 6700 ppm                 | 4 hours  |
|                         | LD50 Oral             | Rat     | 4300 mg/kg               | -        |

### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure          | Observation |
|-------------------------|--------------------------|---------|-------|-------------------|-------------|
| Tetrachloroethylene     | Eyes - Mild irritant     | Rabbit  | -     | 162 mg            | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 24 hours 500 mg   | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 500 mg   | -           |
|                         | Skin - Severe irritant   | Rabbit  | -     | 24 hours 810 mg   | -           |
| Acetone                 | Eyes - Mild irritant     | Human   | -     | 186300 ppm        | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 10 uL             | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 20 mg    | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 20 mg             | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 395 mg            | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 500 mg   | -           |
| Talc                    | Skin - Mild irritant     | Human   | -     | 72 hours 300 ug l | -           |
| Xylene, mixed isomers   | Eyes - Mild irritant     | Rabbit  | -     | 87 mg             | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 5 mg     | -           |
|                         | Skin - Mild irritant     | Rat     | -     | 8 hours 60 uL     | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 100 %             | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg   | -           |

### Sensitization

Not available.

### Mutagenicity

Not available.

### Carcinogenicity

Not available.

### Classification

| Product/ingredient name | OSHA | IARC | NTP  |
|-------------------------|------|------|--|
| Tetrachloroethylene     | -    | 2A   | Reasonably anticipated to be a human carcinogen. |
| Talc                    | -    | 3    | -  |
| Xylene, mixed isomers   | -    | 3    | -  |

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

## Section 11. Toxicological information

| Name                  | Category   | Route of exposure | Target organs                |
|-----------------------|------------|-------------------|------------------------------|
| Tetrachloroethylene   | Category 3 | -                 | Narcotic effects             |
| Acetone               | Category 3 | -                 | Respiratory tract irritation |
| Xylene, mixed isomers | Category 3 | -                 | Narcotic effects             |
|                       | Category 3 | -                 | Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

| Name                  | Category   | Route of exposure | Target organs |
|-----------------------|------------|-------------------|---------------|
| Tetrachloroethylene   | Category 2 | -                 | -             |
| Acetone               | Category 2 | -                 | -             |
| Talc                  | Category 1 | inhalation        | lungs         |
| Xylene, mixed isomers | Category 2 | -                 | -             |

### Aspiration hazard

| Name                  | Result                         |
|-----------------------|--------------------------------|
| Xylene, mixed isomers | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

**Skin contact** : Causes skin irritation.

**Ingestion** : Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness

**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

## Section 11. Toxicological information

**Potential delayed effects** : Not available.

### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**General** : Causes damage to organs through prolonged or repeated exposure.  
**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Teratogenicity** : No known significant effects or critical hazards.  
**Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

| Route               | ATE value     |
|---------------------|---------------|
| Oral                | 4092.04 mg/kg |
| Inhalation (vapors) | 17.12 mg/l    |

## Section 12. Ecological information

### Toxicity

| Product/ingredient name | Result                               | Species   | Exposure |
|-------------------------|--------------------------------------|---|----------|
| Tetrachloroethylene     | Acute EC50 3.64 mg/l                 | Algae - <i>Chlamydomonas reinhardtii</i> - Exponential growth phase           | 72 hours |
|                         | Acute EC50 504 ppm Marine water      | Algae - <i>Skeletonema costatum</i>   | 96 hours |
|                         | Acute LC50 3.5 mg/l Marine water     | Crustaceans - <i>Elminius modestus</i> - Nauplii                              | 48 hours |
|                         | Acute LC50 3.40071 mg/l Fresh water  | Daphnia - <i>Daphnia magna</i>  | 48 hours |
|                         | Acute LC50 4000 µg/l Fresh water     | Fish - <i>Jordanella floridae</i> - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
|                         | Chronic EC10 1.77 mg/l               | Algae - <i>Chlamydomonas reinhardtii</i> - Exponential growth phase           | 72 hours |
| Acetone                 | Chronic NOEC 0.4 mg/l Fresh water    | Daphnia - <i>Daphnia magna</i>  | 21 days  |
|                         | Chronic NOEC 500 µg/l Fresh water    | Fish - <i>Pimephales promelas</i> - Larvae                                    | 32 days  |
|                         | Acute EC50 7200000 µg/l Fresh water  | Algae - <i>Selenastrum sp.</i>  | 96 hours |
|                         | Acute EC50 23.5 mg/l Fresh water     | Daphnia - <i>Daphnia magna</i>  | 48 hours |
|                         | Acute LC50 4.42589 ml/L Marine water | Crustaceans - <i>Acartia tonsa</i> - Copepodid                                | 48 hours |
|                         | Acute LC50 5600 ppm Fresh water      | Fish - <i>Poecilia reticulata</i>   | 96 hours |
|                         | Chronic NOEC 4.95 mg/l Marine water  | Algae - <i>Ulva pertusa</i>   | 96 hours |
|                         | Chronic NOEC 0.016 ml/L Fresh water  | Crustaceans - <i>Daphniidae</i>   | 21 days  |
|                         | Chronic NOEC 0.1 ml/L Fresh water    | Daphnia - <i>Daphnia magna</i> - Neonate                                      | 21 days  |
|                         | Chronic NOEC 5 µg/l Marine water     | Fish - <i>Gasterosteus aculeatus</i> -  | 42 days  |

## Section 12. Ecological information

|                       |                                   |   |          |
|-----------------------|-----------------------------------|---|----------|
| Xylene, mixed isomers | Acute LC50 8500 µg/l Marine water | Larvae<br>Crustaceans - <i>Palaemonetes pugio</i> | 48 hours |
|                       | Acute LC50 13400 µg/l Fresh water | Fish - <i>Pimephales promelas</i>                 | 96 hours |

### Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Acetone                 | -                 | -          | Readily          |
| Xylene, mixed isomers   | -                 | -          | Readily          |

### Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| Tetrachloroethylene     | -                  | 49          | Low       |
| Xylene, mixed isomers   | -                  | 8.1 to 25.9 | Low       |

### Mobility in soil






Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## Section 14. Transport information

|                            | DOT<br>Classification  | TDG<br>Classification  | Mexico<br>Classification   | IATA   | IMDG   |
|----------------------------|--|--|--|--|--|
| UN number                  | UN1950   | UN1950   | UN1950   | UN1950   | UN1950   |
| UN proper shipping name    | AEROSOLS   | AEROSOLS   | AEROSOLS   | AEROSOLS, flammable  | AEROSOLS   |
| Transport hazard class(es) | 2.1<br> | 2.1<br> | 2.1<br> | 2.1<br> | 2.1<br> |
| Packing group              | -  | -  | -  | -  | -  |
| Environmental hazards      | No.  | No.  | No.  | No.  | No.  |



## Section 14. Transport information

|                               |  |  |  |   |   |
|-------------------------------|--|--|--|---|---|
| <b>Additional information</b> | <p>-</p> <p><b>ERG No.</b></p> <p>126</p> <p>Dependent upon container size, this product may ship under the Limited Quantity shipping exception.</p> | <p>Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).</p> <p><b>ERG No.</b></p> <p>126</p> <p>Dependent upon container size, this product may ship under the Limited Quantity shipping exception.</p> | <p>-</p> <p><b>ERG No.</b></p> <p>126</p> <p>Dependent upon container size, this product may ship under the Limited Quantity shipping exception.</p> | <p>-</p> <p>Dependent upon container size, this product may ship under the Limited Quantity shipping exception.</p> | <p><b>Emergency schedules</b> F-D, S-U</p> <p>Dependent upon container size, this product may ship under the Limited Quantity shipping exception.</p> |
|-------------------------------|--|--|--|---|---|

**Special precautions for user** : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

**Transport in bulk according to IMO instruments** : Not available.

**Proper shipping name** : Not available.

## Section 15. Regulatory information

### International regulations

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### **International lists**

: **Australia inventory (AIIIC)**: Not determined.  
**China inventory (IECSC)**: Not determined.  
**Japan inventory (CSCL)**: Not determined.  
**Japan inventory (ISHL)**: Not determined.  
**Korea inventory (KECI)**: Not determined.  
**New Zealand Inventory of Chemicals (NZIoC)**: Not determined.  
**Philippines inventory (PICCS)**: Not determined.  
**Taiwan Chemical Substances Inventory (TCSI)**: Not determined.  
**Thailand inventory**: Not determined.  
**Turkey inventory**: Not determined.  
**Vietnam inventory**: Not determined.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

|                  |   |   |
|------------------|---|---|
| Health           | * | 3 |
| Flammability     |   | 2 |
| Physical hazards |   | 3 |
|                  |   |   |

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**Caution:** HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

### Procedure used to derive the classification

| Classification   | Justification         |
|--|-----------------------|
| FLAMMABLE AEROSOLS - Category 1  | On basis of test data |
| GASES UNDER PRESSURE - Compressed gas  | On basis of test data |
| ACUTE TOXICITY (inhalation) - Category 4   | Calculation method    |
| SKIN CORROSION/IRRITATION - Category 2   | Calculation method    |
| SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A                                 | Calculation method    |
| CARCINOGENICITY - Category 1B  | Calculation method    |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 | Calculation method    |
| SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1                  | Calculation method    |

### History

**Date of printing** : 2/5/2024

**Date of issue/Date of revision** : 2/5/2024

**Date of previous issue** : 1/23/2024

**Version** : 16.01

**Key to abbreviations** : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

Indicates information that has changed from previously issued version.

### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements

|  |  |                        |       |
|--|--|------------------------|-------|
| <b>Date of issue/Date of revision</b> : 2/5/2024 | <b>Date of previous issue</b> : 1/23/2024  | <b>Version</b> : 16.01 | 17/18 |
| SC0941000  | WL™941 Dry Weld Spatter Protectant Aerosol | SHW-85-NA-GHS-CA       |       |

Section 16. Other information

are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.