HHF2-C0004

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

Product code : HHF2-C0004

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Paint or paint related material.

: Industrial use only.

1.3 Details of the supplier of the safety data sheet

Mfg. in U.S.A and exported by: The Sherwin-Williams Company 101 Prospect Avenue N.W. Cleveland, OH 44115

EU Only Representative: Valspar B.V.

Zuiveringweg 89 8243 PE Lelystad P.O. Box 2139 The Netherlands

Phone: +31 (0)320 29 22 00

e-mail address of person : sds@sherwin.com

responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : +431 406 43 43

<u>Supplier</u>

Telephone number : +1 703-741-5970

Hours of operation : Emergency contact available 24 hours a day

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements: No known significant effects or critical hazards.

Precautionary statements

Prevention: Not applicable.Response: Not applicable.

Date of issue/Date of revision: 18, Apr, 2024Date of previous issue: 13, Sep, 2023Version: 31/13

POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

HHF2-C0004

SECTION 2: Hazards identification

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label

: Safety data sheet available on request.

elements

Warning! Hazardous respirable dust may be formed when used. Do not breathe

dust. FOR INDUSTRIAL USE ONLY

Special packaging requirements

Not applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of

0.1% or higher.

Other hazards which do not result in classification

: May form combustible dust concentrations in air.

SECTION 3: Composition/information on ingredients

3.2 Mixture

:

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Titanium Dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤5	Not classified.	-	[2]
Phenylimidazoline Carboxylate	REACH #: 01-2119453802-40 EC: 259-224-4 CAS: 54553-90-1	≤5	Aquatic Chronic 3, H412	-	[1]
Aluminum	REACH #: 01-2119529243-45 EC: 231-072-3 CAS: 7429-90-5 Index: 013-002-00-1	≤5	Flam. Sol. 1, H228 Water-react. 2, H261	-	[2]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 18, Apr., 2024 Date of previous issue : 13, Sep., 2023 Version : 3 2/13

POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

HHF2-C0004

SECTION 4: First aid measures

4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give

anything by mouth to an unconscious person. If unconscious, place in recovery

position and seek medical advice.

Remove contact lenses, irrigate copiously with clean, fresh water, holding the Eye contact

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

If swallowed, seek medical advice immediately and show this container or label. Ingestion

Keep person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localized skin irritation in folds of the skin or under tight clothing.

4.3 Indication of any immediate medical attention and special treatment needed

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. Notes to physician

The exposed person may need to be kept under medical surveillance for 48 hours.

: No specific treatment. Specific treatments

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Recommended: alcohol-resistant foam, CO₂ blanket, water spray or mist.

Unsuitable extinguishing

media

: Do not use water jet.

Do not use inert gas under high pressure (e.g. CO2).

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion

products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective

equipment for fire-fighters

: Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Version : 3 Date of issue/Date of revision : 18, Apr, 2024 Date of previous issue : 13, Sep, 2023 3/13

POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

HHF2-C0004

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing dust. Refer to protective measures listed in sections 7 and 8.

Keep unnecessary and unprotected personnel from entering.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes. rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Do not use a dry brush as dust clouds or static can be created.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Advice should be taken from a competent occupational health practitioner on the assessment of employees with skin or respiratory complaints before the individual is exposed to the uncured product.

7.1 Precautions for safe handling

: Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits.

Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Contaminated absorbent material may pose the same hazard as the spilled product.

7.3 Specific end use(s)

Date of issue/Date of revision : 18, Apr, 2024 Date of previous issue : 13, Sep. 2023 Version : 3 4/13

POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

HHF2-C0004

SECTION 7: Handling and storage

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Titanium Dioxide	Regulation on Limit Values - MAC (Austria, 4/2021).
	TWA: 5 mg/m³ 8 hours. Form: respirable dust
	PEAK: 10 mg/m³, 2 times per shift, 60 minutes. Form: respirable
	dust
Aluminum	Regulation on Limit Values - MAC (Austria, 4/2021).
	TWA: 10 mg/m ³ 8 hours. Form: inhalable fraction
	PEAK: 20 mg/m³, 2 times per shift, 60 minutes. Form: inhalable
	fraction
	PEAK: 10 mg/m³, 2 times per shift, 60 minutes. Form: respirable
	fraction
	TWA: 5 mg/m³ 8 hours. Form: respirable fraction

Biological exposure indices

Product/ingredient name	Exposure indices
aluminium powder (stabilised)	VGU BEI (Austria, 9/2020)
	BEI Fitness: 60 μg/g Kreatinin, aluminium [in urine]. Sampling
	time: one year.

Recommended monitoring procedures

- : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- : Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

: Avoid breathing dust. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn.

Date of issue/Date of revision: 18, Apr, 2024Date of previous issue: 13, Sep, 2023Version: 35/13

POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

HHF2-C0004

SECTION 8: Exposure controls/personal protection

: Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection
Skin protection

: Safety eyewear should be used when there is a likelihood of exposure.

Hand protection

: Wear suitable gloves tested to EN374.

Gloves

: Gloves for short term exposure or repeated or prolonged exposure (480 min): Wear any rubber glove such as Nitrile or Neoprene gloves.

Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing.

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection

- : Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.
- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Recommended: particulate filter, P2-P3 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls

: Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

Date of issue/Date of revision : 18, Apr, 2024 Date of previous issue : 13, Sep, 2023 Version : 3 6/13

POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

HHF2-C0004

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Solid. Color : Beige. Odor : None

Odor threshold : Not applicable.

pН Not relevant/applicable due to nature of the product.

insoluble in water.

Melting point/freezing point

Initial boiling point and

boiling range

: Not relevant/applicable due to nature of the product. : Not relevant/applicable due to nature of the product.

Flash point : Closed cup: Not applicable.

Evaporation rate : Not relevant/applicable due to nature of the product. **Flammability** : Not relevant/applicable due to nature of the product. : Not relevant/applicable due to nature of the product. Lower and upper explosion

limit

: Not relevant/applicable due to nature of the product. Vapor pressure

Relative vapor density : Not applicable.

Relative density : 1.47

Solubility(ies)

Media	Result
cold water	Not soluble

water

Partition coefficient: n-octanol/: Not relevant/applicable due to nature of the product.

Auto-ignition temperature : Not relevant/applicable due to nature of the product. Decomposition temperature : Not relevant/applicable due to nature of the product.

Viscosity : Kinematic (40°C): >20.5 mm²/s

Explosive properties Under normal conditions of storage and use, hazardous reactions will not occur. Oxidizing properties : Under normal conditions of storage and use, hazardous reactions will not occur.

Particle characteristics

Median particle size : Not relevant/applicable due to nature of the product.

9.2 Other information

Heat of combustion : 0.244 kJ/g

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

10.5 Incompatible materials : Not applicable.

Date of issue/Date of revision : 18, Apr, 2024 Date of previous issue : 13, Sep, 2023 Version : 3 7/13

POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

HHF2-C0004

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localized skin irritation in folds of the skin or under tight clothing.

Acute toxicity

No data available

Acute toxicity estimates

No data available

Irritation/Corrosion

No data available

Conclusion/Summary : Not available.

Sensitization

No data available

Conclusion/Summary: Not available.

<u>Mutagenicity</u>

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

No data available

Specific target organ toxicity (repeated exposure)

No data available

Aspiration hazard

No data available

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

Date of issue/Date of revision: 18, Apr, 2024Date of previous issue: 13, Sep, 2023Version: 38/13

POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

HHF2-C0004

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
No data available				

Conclusion/Summary: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
No data available			

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
No data available			

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

: No.

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

European waste catalogue (EWC)

: 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

Date of issue/Date of revision: 18, Apr, 2024Date of previous issue: 13, Sep, 2023Version: 39/13

POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

HHF2-C0004

SECTION 13: Disposal considerations

Disposal considerations

: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

European waste catalogue (EWC) Special precautions

: Plastic articles 15 01 02 - metallic packaging 15 01 04 - mixed packaging 15 01

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and

runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not applicable.

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Date of issue/Date of revision : 18, Apr, 2024 Date of previous issue : 13, Sep. 2023 Version :3 10/13

POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

HHF2-C0004

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name		Designation [Usage]
dibutyltin oxide	<0.1	20

Labeling : Not applicable.

Other EU regulations

VOC content (2010/75/EU) 0 w/w

g/l

: Listed

Industrial emissions

(integrated pollution prevention and control) -

Air

Industrial emissions

: Listed

(integrated pollution prevention and control) -

Water

Explosive precursors : Not applicable.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

15.2 Chemical Safety

: No Chemical Safety Assessment has been carried out.

Assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. acronyms

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent. Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

N/A = Not available

Key literature references and sources for data

: Regulation (EC) No. 1272/2008 [CLP]

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by

Commission Regulation (EU) 2020/878

Directive 2012/18/EU, and relative amendments & additions Directive 2008/98/EC, and relative amendments & additions Directive 2009/161/EU, and relative amendments & additions

CEPE Guidelines

Date of issue/Date of revision 11/13 : 18, Apr, 2024 Date of previous issue : 13, Sep. 2023 Version : 3

POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC

HHF2-C0004

SECTION 16: Other information

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classi	fication	Justification
Not classified.		
Full text of abbreviated H statements	H261 In	ammable solid. contact with water releases flammable gas. armful to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS]	: Aquatic Chronic 3 Flam. Sol. 1 Water-react. 2	AQUATIC HAZARD (LONG-TERM) - Category 3 FLAMMABLE SOLIDS - Category 1 SUBSTANCES AND MIXTURES, WHICH IN CONTACT WITH WATER, EMIT FLAMMABLE GASES - Category 2
Date of printing	: 18, Apr, 2024.	
Date of issue/ Date of revision	: 18, Apr, 2024	
Date of previous issue	: 13, Sep, 2023	
	: If there is no previou information.	s validation date please contact your supplier for more
Version	: 3	

Notice to reader

In accordance with Regulation (EC) 1907/2006, REACH Regulation, Articles 31, 37, any required hazard-related information on the use of substances received as downstream user will be sent forward. Consequently, the safety data sheets for some products will contain a SUMI - Safe Use of Mixture Information - attached to the safety data sheet.

SUMI(s) will be added to the SDS for products if both the following conditions are met:

- The product is classified as hazardous for health
- The product contains one or more REACH-registered substances for which extended safety data sheets (exposure scenarios) have been provided

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision: 18, Apr, 2024Date of previous issue: 13, Sep, 2023Version: 312/13

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II POWDURA® Hybrid Powder Coating - CHAMPAGNE METALLIC HHF2-C0004

Date of issue/Date of revision: 18, Apr, 2024Date of previous issue: 13, Sep, 2023Version: 3