POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

## SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : POWDURA® TGIC Polyester Powder Coating - Fence Green

**Product code** : PGS8-C0651

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Material uses** : Paint or paint related material.

: Industrial use only.

# 1.3 Details of the supplier of the safety data sheet

Mfg. in U.S.A and exported by: The Sherwin-Williams Company 101 Prospect Avenue N.W. Cleveland, OH 44115

EU Only Representative: Valspar B.V.

Zuiveringweg 89 8243 PE Lelystad P.O. Box 2139 The Netherlands

Phone: +31 (0)320 29 22 00

e-mail address of person : sds@sherwin.com

responsible for this SDS

#### 1.4 Emergency telephone number

## National advisory body/Poison Center

**Telephone number** : +431 406 43 43

**Supplier** 

**Telephone number** : +1 703-741-5970

Hours of operation : Emergency contact available 24 hours a day

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 1B, H340

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Date of issue/Date of revision : 18, Apr, 2024 Date of previous issue : 15, Oct, 2023 Version : 3 1/14

POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

#### **SECTION 2: Hazards identification**

Hazard pictograms







Signal word : Danger

**Hazard statements**: May cause an allergic skin reaction.

Causes serious eye damage.

Harmful if inhaled.

May cause genetic defects.

**Precautionary statements** 

Prevention : Obtain special instructions before use. Wear protective gloves, protective clothing,

eye protection, face protection, or hearing protection. Avoid breathing dust or mist.

**Response**: IF exposed or concerned: Get medical advice or attention. IF IN EYES: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage: Not applicable.Disposal: Not applicable.

Hazardous ingredients : Triglycidyl Isocyanurate

Supplemental label : Warning! Hazardous respirable dust may be formed when used. Do not breathe

elements dust. FOR INDUSTRIAL USE ONLY

#### **Special packaging requirements**

Not applicable.

#### 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of

0.1% or higher.

Other hazards which do not result in classification

: May form combustible dust concentrations in air.

## **SECTION 3: Composition/information on ingredients**

3.2 Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Triglycidyl Isocyanurate	EC: 219-514-3 CAS: 2451-62-9 Index: 615-021-00-6	≤5	Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 1B, H340 STOT RE 2, H373 Aquatic Chronic 3, H412	ATE [Oral] = 138 mg/kg ATE [Inhalation (vapours)] = 0.65 mg/l	[1]
Titanium Dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤3	Not classified.	-	[2]
Phthalocyanine Green	REACH #: 01-2119459333-39 EC: 215-524-7 CAS: 1328-53-6	≤3	Not classified.	-	[2]

Date of issue/Date of revision : 18, Apr., 2024 Date of previous issue : 15, Oct, 2023 Version : 3 2/14

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II
POWDURA® TGIC Polyester Powder Coating - Fence Green
PGS8-C0651

## **SECTION 3: Composition/information on ingredients**

Iron Oxide	REACH #: 01-2119457554-33 EC: 257-098-5 CAS: 51274-00-1	≤3	Not classified.	-	[2]	
	OAO. 31214-00-1		See Section 16 for the full text of the H statements declared above.			

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

## **Type**

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery

position and seek medical advice.

**Eye contact**: Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

*Inhalation* : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localized skin irritation in folds of the skin or under tight clothing.

Contains 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione. May produce an allergic reaction.

## 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

See toxicological information (Section 11)

Date of issue/Date of revision : 18, Apr, 2024 Date of previous issue : 15, Oct, 2023 Version : 3 3/14

POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

## SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Recommended: alcohol-resistant foam, CO<sub>2</sub> blanket, water spray or mist.

Unsuitable extinguishing

media

Do not use water jet.

Do not use inert gas under high pressure (e.g. CO2).

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may

cause a health hazard.

Hazardous combustion

products

: Decomposition products may include the following materials: carbon monoxide,

carbon dioxide, smoke, oxides of nitrogen.

## 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to

drains or watercourses.

Special protective equipment for fire-fighters

: Fire-fighters should wear positive pressure self-contained breathing apparatus

(SCBA) and full turnout gear.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing dust. Refer to protective measures listed in sections 7 and 8.

Keep unnecessary and unprotected personnel from entering.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any

information in Section 8 on suitable and unsuitable materials. See also the

information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local

regulations.

6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Do not use a dry brush as dust clouds or static can be created.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Advice should be taken from a competent occupational health practitioner on the assessment of employees with skin or respiratory complaints before the individual is exposed to the uncured product.

7.1 Precautions for safe handling

: Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits.

Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the

conducting type.

Keep away from heat, sparks and flame.

Date of issue/Date of revision : 18, Apr, 2024 Date of previous issue : 15, Oct, 2023 Version : 3 4/14

POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

## **SECTION 7: Handling and storage**

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

# 7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations.

## Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Contaminated absorbent material may pose the same hazard as the spilled product.

## 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

#### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
Titanium Dioxide	Regulation on Limit Values - MAC (Austria, 4/2021). TWA: 5 mg/m³ 8 hours. Form: respirable dust PEAK: 10 mg/m³, 2 times per shift, 60 minutes. Form: respirable dust
Phthalocyanine Green	Regulation on Limit Values - MAC (Austria, 4/2021). [Copper and its compounds]  TWA: 1 mg/m³, (measured as Cu) 8 hours. Form: inhalable fraction  PEAK: 4 mg/m³, (measured as Cu), 4 times per shift, 15 minutes. Form: inhalable fraction  Regulation on Limit Values - MAC (Austria, 4/2021). [Copper and its compounds (Fume)]  TWA: 0.1 mg/m³, (measured as Cu) 8 hours. Form: respirable fume  PEAK: 0.4 mg/m³, (measured as Cu), 4 times per shift, 15 minutes. Form: respirable fume
Iron Oxide	Regulation on Limit Values - MAC (Austria, 4/2021). [Iron oxide] PEAK: 20 mg/m³, 2 times per shift, 60 minutes. Form: inhalable dust

Date of issue/Date of revision: 18, Apr, 2024Date of previous issue: 15, Oct, 2023Version: 35/14SHW-A4-EU-CLP44-AT

POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

## SECTION 8: Exposure controls/personal protection

TWA: 10 mg/m<sup>3</sup> 8 hours. Form: inhalable dust TWA: 5 mg/m<sup>3</sup> 8 hours. Form: respirable dust

PEAK: 10 mg/m³, 2 times per shift, 60 minutes. Form: respirable

#### **Biological exposure indices**

No exposure indices known.

#### Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

No PNECs available.

#### 8.2 Exposure controls

### Appropriate engineering controls

- : Avoid breathing dust. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn.
- : Users are advised to consider national Occupational Exposure Limits or other equivalent values.

#### **Individual protection measures**

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## Eye/face protection Skin protection

: Safety eyewear should be used when there is a likelihood of exposure.

Hand protection

: Wear suitable gloves tested to EN374.

**Gloves** 

: Gloves for short term exposure or repeated or prolonged exposure (480 min): Wear any rubber glove such as Nitrile or Neoprene gloves. Due to many conditions (e.g. temperature, abrasion) the practical usage of a

chemical protective glove in practice may be much shorter than the permeation time determined through testing.

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove

Always ensure that gloves are free from defects and that they are stored and used

correctly.

Date of issue/Date of revision : 18, Apr, 2024 Date of previous issue : 15, Oct, 2023 Version : 3 6/14

POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

## **SECTION 8: Exposure controls/personal protection**

The performance or effectiveness of the glove may be reduced by physical/chemical

damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** 

: Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Application methods:

Brush or roller. Approved/certified respirator with organic vapor cartridge. Filter type:

A2 P2 (EN14387).

Manual spraying. Use a properly fitted, air-purifying or air-fed respirator complying

with an approved standard if a risk assessment indicates this is necessary.

Environmental exposure controls

: Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

## 9.1 Information on basic physical and chemical properties

#### **Appearance**

Physical state: Solid.Color: Clear.Odor: None

Odor threshold : Not applicable.

pH : Not relevant/applicable due to nature of the product.

insoluble in water.

Melting point/freezing point

Initial boiling point and

boiling range

: Not relevant/applicable due to nature of the product.

: Not relevant/applicable due to nature of the product.

Flash point : Closed cup: Not applicable.

Evaporation rate
 Not relevant/applicable due to nature of the product.
 Hot relevant/applicable due to nature of the product.
 Lower and upper explosion
 Not relevant/applicable due to nature of the product.

limit

Vapor pressure : Not relevant/applicable due to nature of the product.

**Relative vapor density** : Not applicable.

Relative density : 1.62

Solubility(ies) :

Date of issue/Date of revision : 18, Apr, 2024 Date of previous issue : 15, Oct, 2023 Version : 3 7/14

POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

## **SECTION 9: Physical and chemical properties**

Media	Result
cold water	Not soluble

water

**Partition coefficient:** n-octanol/: Not relevant/applicable due to nature of the product.

Auto-ignition temperature Decomposition temperature : Not relevant/applicable due to nature of the product. : Not relevant/applicable due to nature of the product.

**Viscosity** 

: Kinematic (40°C): >20.5 mm<sup>2</sup>/s

Explosive properties Oxidizing properties

: Under normal conditions of storage and use, hazardous reactions will not occur. : Under normal conditions of storage and use, hazardous reactions will not occur.

Particle characteristics

Median particle size

: Not relevant/applicable due to nature of the product.

9.2 Other information

Heat of combustion : 0.09 kJ/g

## SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

: When exposed to high temperatures may produce hazardous decomposition

products.

10.5 Incompatible materials

: Not applicable.

10.6 Hazardous decomposition products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localized skin irritation in folds of the skin or under tight clothing.

Contains 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione. May produce an allergic reaction.

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Triglycidyl Isocyanurate	LC50 Inhalation Vapor	Rat	650 mg/m³	4 hours
	LD50 Oral	Rat	138 mg/kg	-

## Acute toxicity estimates

Date of issue/Date of revision : 18, Apr, 2024 Date of previous issue : 15, Oct, 2023 Version :3 8/14

POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

## **SECTION 11: Toxicological information**

Route	ATE value	
Oral	3071.73 mg/kg	
Inhalation (vapors)	14.47 mg/l	

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Triglycidyl Isocyanurate	Eyes - Severe irritant	Rabbit	-	100 mg	-

Conclusion/Summary

: Not available.

**Sensitization** 

No data available

Conclusion/Summary

: Not available.

Mutagenicity

No data available

**Carcinogenicity** 

No data available

Reproductive toxicity

No data available

**Teratogenicity** 

No data available

## Specific target organ toxicity (single exposure)

No data available

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Triglycidyl Isocyanurate	Category 2	-	-

## **Aspiration hazard**

No data available

#### 11.2 Information on other hazards

## 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

#### 12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

#### 12.2 Persistence and degradability

Date of issue/Date of revision: 18, Apr, 2024Date of previous issue: 15, Oct, 2023Version: 39/14

POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

## **SECTION 12: Ecological information**

Product/ingredient name	Test	Result	Dose	Inoculum
No data available				

**Conclusion/Summary**: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
No data available			

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
No data available			

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

**Mobility** : Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities

with jurisdiction.

Hazardous waste

European waste catalogue (EWC)

waste paint and varnish containing organic solvents or other hazardous substances

08 01 11\*

**Disposal considerations** : Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

**Packaging** 

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered

when recycling is not feasible.

Date of issue/Date of revision : 18, Apr., 2024 Date of previous issue : 15, Oct, 2023 Version : 3 10/14

POWDURA® TGIC Polvester Powder Coating - Fence Green

PGS8-C0651

## **SECTION 13: Disposal considerations**

Disposal considerations

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

European waste catalogue (EWC) : packaging containing residues of or contaminated by hazardous substances 15 01

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not applicable.

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Date of issue/Date of revision Version : 3 : 18, Apr, 2024 Date of previous issue : 15, Oct, 2023 11/14

POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

## Annex XIV - List of substances subject to authorization

#### **Annex XIV**

None of the components are listed.

## Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
Triglycidyl Isocyanurate	Mutagen	Candidate	ED/87/2012	6/18/2012

# <u>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</u>

Product/ingredient name	%	Designation [Usage]
POWDURA® TGIC Polyester Powder Coating	≥90	29
1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	≤5	29

**Labeling**: Restricted to professional users.

**Other EU regulations** 

VOC content (2010/75/EU) : 0 w/w

0 **g/l** 

**Explosive precursors**: Not applicable.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

**National regulations** 

15.2 Chemical Safety

Assessment

: No Chemical Safety Assessment has been carried out.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

N/A = Not available

Key literature references and sources for data

: Regulation (EC) No. 1272/2008 [CLP]

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by

Commission Regulation (EU) 2020/878

Directive 2012/18/EU, and relative amendments & additions Directive 2008/98/EC, and relative amendments & additions Directive 2009/161/EU, and relative amendments & additions

**CEPE** Guidelines

## Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Date of issue/Date of revision: 18, Apr, 2024Date of previous issue: 15, Oct, 2023Version: 312/14

POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

#### **SECTION 16: Other information**

Classification	Justification
Eye Dam. 1, H318 Skin Sens. 1, H317	Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H

statements

: H301 Toxic if swallowed.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled. H332 Harmful if inhaled.

H340 May cause genetic defects.

H373 May cause damage to organs through prolonged or repeated

exposure.

H412 Harmful to aquatic life with long lasting effects.

Full text of classifications

[CLP/GHS]

: Acute Tox. 2 ACUTE TOXICITY - Category 2
Acute Tox. 3 ACUTE TOXICITY - Category 3
Acute Tox. 4 ACUTE TOXICITY - Category 4

Aquatic Chronic 3 AQUATIC HAZARD (LONG-TERM) - Category 3

Eye Dam. 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

Muta. 1B GERM CELL MUTAGENICITY - Category 1B

Skin Sens. 1 SKIN SENSITIZATION - Category 1

STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED

EXPOSURE) - Category 2

Date of printing : 18, Apr, 2024.

Date of issue/ Date of

revision

: 18, Apr, 2024

Date of previous issue : 15, Oct, 2023

: If there is no previous validation date please contact your supplier for more

information.

Version : 3

## Notice to reader

In accordance with Regulation (EC) 1907/2006, REACH Regulation, Articles 31, 37, any required hazard-related information on the use of substances received as downstream user will be sent forward. Consequently, the safety data sheets for some products will contain a SUMI - Safe Use of Mixture Information - attached to the safety data sheet.

SUMI(s) will be added to the SDS for products if both the following conditions are met:

- The product is classified as hazardous for health
- The product contains one or more REACH-registered substances for which extended safety data sheets (exposure scenarios) have been provided

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose

Date of issue/Date of revision: 18, Apr, 2024Date of previous issue: 15, Oct, 2023Version: 313/14

POWDURA® TGIC Polyester Powder Coating - Fence Green

PGS8-C0651

## **SECTION 16: Other information**

shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision: 18, Apr, 2024Date of previous issue: 15, Oct, 2023Version: 314/14