# **SAFETY DATA SHEET**

RLS8-20006

# Section 1. Identification

Product name	: POWDURA® RAL Series Superdurable TGIC Free Polyester Powder Coating RAL 5001 GL
Product code	: RLS8-20006
Other means of identification	: Not available.
Product type	: Powder.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: 866-722-9710 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

# Section 2. Hazards identification

Classification of the substance or mixture	: COMBUSTIBLE DUSTS CARCINOGENICITY - Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Suspected of causing cancer. May form combustible dust concentrations in air.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.
Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.

Date of issue/Dat	e of revision	: 4/9/2024	Date of previous issue	: 9/14/2023	Version : 16	1/12
RLS8-20006	POWDURA® RAL Serie RAL 5001 GL	s Superdurable TGIC	Free Polyester Powder Coating		SHW-85-NA-G	HS-CA

## Section 2. Hazards identification

Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> </ul>
Supplemental label elements	Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevent dust accumulation. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

## Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
	22.13 5.16	7727-43-7
	0.33	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necessa	r <u>y first aid measures</u>
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Date of issue/Date	of revision	: 4/9/2024	Date of previous issue	: 9/14/2023	Version	:16	2/12
RLS8-20006	POWDURA® RAL Series Su RAL 5001 GL	uperdurable TGIC Fr	ee Polyester Powder Coating		SHW-85-	NA-GHS-CA	

# Section 4. First aid measures

posure to airborne concentrations above statutory or recommended exposure limits ay cause irritation of the eyes.
posure to airborne concentrations above statutory or recommended exposure limits ay cause irritation of the nose, throat and lungs.
o known significant effects or critical hazards.
o known significant effects or critical hazards.
lverse symptoms may include the following: itation dness
lverse symptoms may include the following: spiratory tract irritation ughing
o specific data.
o specific data.
tention and special treatment needed, if necessary
case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
o specific treatment.
e action shall be taken involving any personal risk or without suitable training. It may a dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Date of issue/Date	of revision	: 4/9/2024	Date of previous issue	: 9/14/2023	Version	:16	3/12
RLS8-20006	POWDURA® RAL Series Su RAL 5001 GL	perdurable TGIC Fr	ee Polyester Powder Coating		SHW-85-I	NA-GHS-CA	

# Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

<b>Precautions</b>	for	safe	handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene

measures.

:9/14/2023

# Section 7. Handling and storage

Conditions for safe storage,	1	Store in accordance with local regulations. Store in a segregated and approved area.
including any		Store in original container protected from direct sunlight in a dry, cool and well-ventilated
incompatibilities		area, away from incompatible materials (see Section 10) and food and drink. Store
-		locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep
		container tightly closed and sealed until ready for use. Containers that have been
		opened must be carefully resealed and kept upright to prevent leakage. Do not store in
		unlabeled containers. Use appropriate containment to avoid environmental
		contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Barium Sulfate	7727-43-7ACGIH TLV (United States, 1/2023). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). TWA: 5 mg/m³ 10 hours. Form: Respirab fraction TWA: 10 mg/m³ 10 hours. Form: Total OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 15 mg/m³ 8 hours. Form: Total dust	
Titanium Dioxide	13463-67-7	OSHA PEL (United States, 5/2018). TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirable fraction, finescale particles
Carbon Black	1333-86-4	NIOSH REL (United States, 10/2020). TWA: 3.5 mg/m <sup>3</sup> 10 hours. OSHA PEL (United States, 5/2018). TWA: 3.5 mg/m <sup>3</sup> 8 hours. ACGIH TLV (United States, 1/2023). TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction

#### **Occupational exposure limits (Canada)**

Ingredient name	CAS #	Exposure limits		
Carbon black	1333-86-4	<ul> <li>CA British Columbia Provincial (Canada, 6/2022).</li> <li>TWA: 3 mg/m<sup>3</sup> 8 hours. Form: Inhalable</li> <li>CA Ontario Provincial (Canada, 6/2019).</li> <li>TWA: 3 mg/m<sup>3</sup> 8 hours. Form: Inhalable particulate matter.</li> <li>CA Quebec Provincial (Canada, 6/2022).</li> <li>TWAEV: 3 mg/m<sup>3</sup> 8 hours. Form: inhalable dust</li> <li>CA Alberta Provincial (Canada, 6/2018).</li> <li>8 hrs OEL: 3.5 mg/m<sup>3</sup> 8 hours.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 7 mg/m<sup>3</sup> 15 minutes.</li> <li>TWA: 3.5 mg/m<sup>3</sup> 8 hours.</li> </ul>		

Date of issue/Date	of revision	: 4/9/2024	Date of previous issue	: 9/14/2023	Version	:16	5/12
RLS8-20006	POWDURA® RAL Series Sup RAL 5001 GL	erdurable TGIC Fre	ee Polyester Powder Coating		SHW-85-N	NA-GHS-CA	

## Section 8. Exposure controls/personal protection

Occupational exposure lim	its (	<u>NIEXICO)</u>	I	
Ingredient name			CAS #	Exposure limits
None.				
Biological exposure indice	<u>s (U</u>	<u>nited States)</u>		·
No exposure indices known.				
Biological exposure indice	<u>s (C</u>	anada)		
No exposure indices known.				
Biological exposure indice	<u>s (M</u>	lexico)		
No exposure indices known.				
Appropriate engineering controls Environmental exposure	:	or mist, use process e to keep worker exposi limits. The engineerin below any lower explo	nclosures, local e ure to airborne co g controls also ne sive limits. Use e	ser operations generate dust, fumes, gas, vapor exhaust ventilation or other engineering controls ntaminants below any recommended or statutory eed to keep gas, vapor or dust concentrations explosion-proof ventilation equipment. ress equipment should be checked to ensure
controls		they comply with the re	equirements of er s, filters or engine	nvironmental protection legislation. In some pering modifications to the process equipment
Individual protection measu	<u>ires</u>			
Hygiene measures	:	eating, smoking and u Appropriate technique	sing the lavatory s should be used lothing before reu	ghly after handling chemical products, before and at the end of the working period. to remove potentially contaminated clothing. sing. Ensure that eyewash stations and safety cation.
Eye/face protection	:	assessment indicates gases or dusts. If con the assessment indica	this is necessary tact is possible, th ates a higher degr	oved standard should be used when a risk to avoid exposure to liquid splashes, mists, ne following protection should be worn, unless ee of protection: safety glasses with side- igh dust concentrations to be produced, use
Skin protection				
Hand protection	:	worn at all times when necessary. Considerin during use that the glo noted that the time to	handling chemic ng the parameters oves are still retair breakthrough for In the case of mize	complying with an approved standard should be al products if a risk assessment indicates this is s specified by the glove manufacturer, check ning their protective properties. It should be any glove material may be different for different xtures, consisting of several substances, the accurately estimated.
Body protection	:			ody should be selected based on the task being nould be approved by a specialist before
Other skin protection	:		ng performed and	I skin protection measures should be selected the risks involved and should be approved by a
Respiratory protection	:	appropriate standard of	or certification. Re	xposure, select a respirator that meets the espirators must be used according to a e proper fitting, training, and other important

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

: Solid.	
: Blue.	
: Not available.	
: Not available.	
: Not applicable.	
: Not available.	
: Not available.	
: Closed cup: Not applicable.	
: Not available.	
: Not available.	
: Not applicable.	
: Not available.	
: Not applicable.	
: 1.51	
:	
	<ul> <li>Blue.</li> <li>Not available.</li> <li>Not available.</li> <li>Not applicable.</li> <li>Not available.</li> <li>Not available.</li> <li>Closed cup: Not applicable.</li> <li>Not available.</li> <li>Not available.</li> <li>Not available.</li> <li>Not available.</li> <li>Not applicable.</li> <li>Not applicable.</li> <li>Not applicable.</li> <li>1.51</li> </ul>

Media		Result		
cold water	Not soluble			
Partition coefficient: n- octanol/water	: Not	applicable.		
Auto-ignition temperature	: Not applicable.			
Decomposition temperature	: Not available.			
Viscosity	: Kin	ematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)		
Molecular weight	: Not	t applicable.		
Heat of combustion	: 0.14	12 kJ/g		

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Date of issue/Date of revision	• 4/9/2024 Date of previous issue • 9/14/2023 Version • 16 7/1

Date of issue/Date	of revision	: 4/9/2024	Date of previous issue	: 9/14/2023	Version	:16	7/12
RLS8-20006	POWDURA® RAL Series St RAL 5001 GL	uperdurable TGIC F	Free Polyester Powder Coating		SHW-85-I	NA-GHS-CA	

### Section 10. Stability and reactivity

# Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Carbon Black	LD50 Oral	Rat	>15400 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide Carbon Black	-	2B 2B	

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

Not available.

### Information on the likely : Not available. routes of exposure

#### Potential acute health effects

Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Date of issue/Dat	e of revision	: 4/9/2024	Date of previous issue	: 9/14/2023	Version : 16	8/12
RLS8-20006	POWDURA® RAL Serie RAL 5001 GL	s Superdurable TGIC	Free Polyester Powder Coating		SHW-85-NA-GHS-CA	

# Section 11. Toxicological information

	bysical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate eff	fects and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	<u>fects</u>
Not available.	
General	: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

#### Numerical measures of toxicity Acute toxicity estimates Not available.

# Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
Barium Sulfate Titanium Dioxide	Acute EC50 634 mg/l Fresh water Acute EC50 32 mg/l Fresh water Acute LC50 >1000000 µg/l Marine water	Crustaceans - Cypris subglobosa Daphnia - Daphnia magna Fish - Fundulus heteroclitus	48 hours 48 hours 96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

I	Date of issue/Date	of revision	: 4/9/2024	Date of previous issue	: 9/14/2023	Version	:16	9/12
	RLS8-20006	POWDURA® RAL Series Su RAL 5001 GL	perdurable TGIC F	ree Polyester Powder Coating		SHW-85-	NA-GHS-CA	

## Section 12. Ecological information

#### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	_	-
pecial precautions	conside mode o suitably to shipr of the p dangero	odal shipping descripter odal shipping descripter of container sizes. The of transport (sea, air, of or that mode of transformed of transformed nent, and compliance the son offering the propus goods must be the all actions in case of	ne presence of a shi etc.), does not indic nsport. All packaging e with the applicable oduct for transport. rained on all of the r	pping description for ate that the product g must be reviewed regulations is the s People loading and isks deriving from th	a particular is packaged for suitability prior ole responsibility unloading
	rision : 4/9/202 DURA® RAL Series Superdurable T 001 GL	•			ion :16 10/ <sup>-</sup> I-85-NA-GHS-CA

### Section 14. Transport information

Transport in bulk according : Not available. to IMO instruments

Proper shipping name

: Not available.

## Section 15. Regulatory information

International regulations **Montreal Protocol** Not listed. Stockholm Convention on Persistent Organic Pollutants Not listed. : Australia inventory (AIIC): Not determined. **International lists** China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
COMBUSTIBLE DUSTS CARCINOGENICITY - Category 2	On basis of test data

<u>History</u>	
Date of printing	: 4/9/2024
Date of issue/Date of revision	: 4/9/2024
Date of previous issue	: 9/14/2023
Version	: 16

Date of issue/Date	e of revision	: 4/9/2024	Date of previous issue	: 9/14/2023	Version : 16	11/12
RLS8-20006	POWDURA® RAL Series S RAL 5001 GL	uperdurable TGIC I	Free Polyester Powder Coating		SHW-85-NA-GHS-CA	

### Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
-	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
	as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations
<b>—</b> • • • • • • •	

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.