



SUPERDECK® Stain & Sealer Remover

DESCRIPTION

SuperDeck® Stain & Sealer Remover is specifically designed to help remove semi-transparent and weathered solid latex and oil-based stains from decks and other exterior wood. **SuperDeck Stain & Sealer Remover** allows you to change the color of your deck or siding by restoring the natural beauty of the wood.

Where to use:

SuperDeck Stain & Sealer Remover can be used on many exterior wood surfaces such as decks, siding and fences and will remove the following stains and finishes:

- Polyurethane and some weathered latex paint
- Oil-based toners, transparent, semi-transparent, and weathered solid stains
- Water-based toners, transparent, semi-transparent, and weathered stains
- Water-reducible toners, transparent, semi-transparent and weathered solid stains
- Old, weathered, clear protective finishes

SuperDeck Stain & Sealer Remover will help restore color to severely weathered and discolored wood. Test product on an inconspicuous area before applying to your entire deck. Do not use on new, untreated wood or new wood treated with a clear protective finish. **SuperDeck Stain & Sealer Remover** may darken the appearance of new wood.

CHARACTERISTICS

Coverage:..... Approximately 150 sq. ft/gal.
 Depending upon the condition and porosity of the wood
 Appearance:..... Clear, amber liquid
 pH:..... 13.5
 Solvent:..... Water
 Weight per Gallon:.....9.3 lb

SURFACE PREPARATION

WARNING! Removal of old coatings by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (**NIOSH** approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US)

SURFACE PREPARATION

Be sure the surface is free of any loose dirt and debris. If the surface is extremely dry or in direct, hot sunlight, dampen with water. Thoroughly wet plants and shrubs and cover to protect them from overspray. Uncover promptly after cleaning. Remove all deck furniture and decorative items. Do not allow **SuperDeck Stain & Sealer Remover** to come into contact with finished or aluminum surfaces. Rinse immediately after use on metal to avoid pitting or discoloration. Do not allow **SuperDeck Stain & Sealer Remover** to come into prolonged contact with clothing, carpet, or fabric, as damage may occur.

Plan the application; for horizontal surfaces, work backwards so that you do not walk on the surface being treated. For vertical surfaces, work from the top down. Treat small areas one at a time.

APPLICATION

Add contents of container to plastic bucket. **DO NOT MIX WITH ANY OTHER PRODUCT.** Do not use metal containers. Apply **SuperDeck Stain & Sealer Remover** liberally with brush or roller. Clean small areas one at a time allowing product to sit for 10-15 minutes. Scrub the surface with a synthetic stiff bristle brush (do not use a wire or natural bristle brush) to remove those finishes that do not come up immediately. Do not allow **SuperDeck Stain & Sealer Remover** to dry during application. If stubborn areas remain, repeat the application in those areas.

Be cautious with wet surfaces as they may be slippery.

Thoroughly rinse the surface with fresh water from a hose, removing all residue. Any residue left on the surface may interfere with the drying or adhesion of topcoats.

Rinse surrounding area and vegetation with water.

SuperDeck Stain & Sealer Remover may darken Western Red Cedar and Redwood.

SuperDeck Revive™ must be used after **SuperDeck Stain & Sealer Remover** to neutralize the surface and as a second step to bring back the natural color of the wood.

Note: If the grain of your wood raises after application, sand the surface lightly.



114.01

SUPERDECK® Stain & Sealer Remover

CLEANUP INFORMATION

Rinse equipment and brushes with soap and water.

Storage: Protect from freezing. Do not store below 30°F.

SURFACE PREPARATION

Using the right cleaner often makes the cleaning easier. Clean all surfaces completely with the appropriate cleaner based on the conditions. Rinse the surface completely and allow the surface to dry thoroughly.

SuperDeck Deck Wash

- Mildew stain
- Algae stain
- Weathered wood (bleaches wood)
- Gray wood (bleaches wood)

SuperDeck Revive®

- Tannin Bleed
- Nail stain
- Weathered wood (restores color)
- Gray wood (restores color)
- Mill Glaze

Sales No.
640359949

Size
1 gal.

DANGER! CAUSES EYE, SKIN AND RESPIRATORY TRACT BURNS. Before using, carefully read CAUTIONS.

CAUTIONS

CONTAINS Sodium Hydroxide. Avoid contact with eyes and skin. Causes severe burns to eyes and mucous membranes on contact. Wear protective gloves. Wear eye protection. Wash hands immediately after use. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, immediately flush eyes with water for 15 minutes. Get immediate medical attention! For skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, do NOT induce vomiting. Call Poison Control Center, hospital emergency room or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW
FRC, SP

01/22/2015

640359949

03 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit www.paintdocs.com to obtain the most current version of the PDS and/or an SDS.