# **SAFETY DATA SHEET**

W12AF0005

## Section 1. Identification

Product name	: WHITE LIGHTNING® 3006™ Advanced Formula White
Product code	: W12AF0005
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Paint or paint related material	
Manufacturer	: White Lightning Products 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	: (216) 566-2917
Product Information Telephone Number	: (800) 241-5295

# Transportation Emergency: (800) 424-9300Telephone Number

## Section 2. Hazards identification

OSHA/HCS state	us :	This material is considered hazardous by the OSHA Hazard C (29 CFR 1910.1200).	ommunication Standard
<b>Classification o</b>	f the :	SKIN CORROSION/IRRITATION - Category 2	
substance or m	ixture	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	
		CARCINOGENICITY - Category 1A	
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSUR irritation) - Category 3	E) (Respiratory tract
		SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOS	SURE) - Category 2
		Percentage of the mixture consisting of ingredient(s) of unkno	
		(oral), 1.3% (dermal), 1.3% (inhalation)	wir doute toxioity. 1.070
GHS label eleme	<u>ents</u>		
Hazard pictog			
Signal word		Danger	
Hazard statem	ents :	Causes skin irritation.	
		Causes serious eye irritation. May cause respiratory irritation.	
		May cause cancer.	
		May cause damage to organs through prolonged or repeated	exposure.
Precautionary s	<u>tatements</u>		
General	:	Read label before use. Keep out of reach of children. If medi product container or label at hand.	cal advice is needed, have
Date of issue/Date of	of revision	: 2/5/2024 Date of previous issue : 9/19/2023	Version : 23 1/14
	WHITE LIGHTNING® White	3006™ Advanced Formula	SHW-85-NA-GHS-US

## Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash thoroughly after handling.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

## Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Calcium Carbonate	≥50 - ≤75	1317-65-3
Light Aliphatic Hydrocarbon	≤3	64742-47-8
Titanium Dioxide	≤3	13463-67-7
Crystalline Silica, non-respirable	≤1	14808-60-7
Crystalline Silica, respirable powder	<1	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

## Section 4. First aid measures

Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health effe	<u>ets</u>	
Eye contact	: Causes serious eye irritation.	
Inhalation	May cause respiratory irritation.	
Skin contact	Causes skin irritation.	
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs/sym	<u>ptoms</u>	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing	
Skin contact	: Adverse symptoms may include the following: irritation redness	
Ingestion	: No specific data.	
Indication of immediate me	dical attention and special treatment needed, if necessary	
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

#### See toxicological information (Section 11)

Date of issue/Date	of revision	: 2/5/2024	Date of previous issue	: 9/19/2023	Version : 23	3/14
W12AF0005	WHITE LIGHTNING®	9 3006™ Advan	ced Formula		SHW-85-NA-GHS-US	

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".	n
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Methods and materials for co	inment and cleaning up	
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material an place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Was spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.	h

## Section 7. Handling and storage

Precautions for safe handling	L	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits (OSHA United States)** 

Ingredient name	CAS #	Exposure limits
Calcium Carbonate	1317-65-3	OSHA PEL (United States, 5/2018). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust NIOSH REL (United States, 10/2020). [calcium carbonate] TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Respirable fraction TWA: 10 mg/m <sup>3</sup> 10 hours. Form: Total
Light Aliphatic Hydrocarbon	64742-47-8	ACGIH TLV (United States, 1/2023). [Kerosene as total hydrocarbon vapor] Absorbed through skin. TWA: 200 mg/m <sup>3</sup> , (as total hydrocarbon
Titanium Dioxide	13463-67-7	<ul> <li>vapor) 8 hours.</li> <li>OSHA PEL (United States, 5/2018).</li> <li>TWA: 15 mg/m<sup>3</sup> 8 hours. Form: Total dust</li> <li>ACGIH TLV (United States, 1/2023).</li> <li>TWA: 2.5 mg/m<sup>3</sup> 8 hours. Form: respirable fraction, finescale particles</li> </ul>
Crystalline Silica, non-respirable	14808-60-7	<ul> <li>OSHA PEL (United States, 5/2018). [Silica, crystalline]</li> <li>TWA: 50 μg/m<sup>3</sup> 8 hours. Form: Respirable dust</li> <li>OSHA PEL Z3 (United States, 6/2016).</li> <li>TWA: 30 mg/m<sup>3</sup> / (%SiO2+2) 8 hours. Form Total dust</li> </ul>
Crystalline Silica, respirable powder	14808-60-7	OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / (%SiO2+5) 8 hours. Form
ate of issue/Date of revision : 2/5/2024 Date /12AF0005 WHITE LIGHTNING® 3006™ Advanced For White	e <b>of previous issue</b> mula	: 9/19/2023 Version : 23 5/1 SHW-85-NA-GHS-US

## Section 8. Exposure controls/personal protection

 -
Respirable
TWA: 10 mg/m <sup>3</sup> / (%SiO2+2) 8 hours. Form:
Respirable
OSHA PEL (United States, 5/2018). [Silica,
crystalline]
TWA: 50 µg/m <sup>3</sup> 8 hours. Form: Respirable
dust
ACGIH TLV (United States, 1/2023). [Silica,
crystalline]
TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form:
Respirable fraction
NIOSH REL (United States, 10/2020).
[SILICA, CRYSTALLINE (AS RESPIRABLE
TWA: 0.05 mg/m <sup>3</sup> 10 hours. Form: respirable
dust

#### Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits		
Petroleum refining, hydrotreated light distillate	64742-47-8	<ul> <li>CA British Columbia Provincial (Canada, 6/2022). [Kerosene/Jet fuels as total hydrocarbon vapour] Absorbed through skin. Notes: Application restricted to conditions in which there are negligible aerosol exposures.</li> <li>TWA: 200 mg/m<sup>3</sup>, (as total hydrocarbon vapour) 8 hours.</li> <li>CA Alberta Provincial (Canada, 6/2018). [Kerosene/Jet fuels as total hydrocarbor vapour] Absorbed through skin.</li> <li>8 hrs OEL: 200 mg/m<sup>3</sup>, (as total hydrocarbor vapour) 8 hours.</li> <li>CA Ontario Provincial (Canada, 6/2019).</li> <li>Absorbed through skin.</li> <li>TWA: 200 mg/m<sup>3</sup>, (as total hydrocarbor vapour) 8 hours.</li> </ul>		
Quartz	14808-60-7	CA Quebec Provincial (Canada, 6/2022). [Silica Crystalline -Quartz] TWAEV: 0.1 mg/m <sup>3</sup> 8 hours. Form: Respirable dust.		
Quartz	14808-60-7	<ul> <li>CA British Columbia Provincial (Canada, 6/2022). [Silica, Crystalline - alpha quartz and Cristobalite Respirable]</li> <li>TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form:</li> <li>Respirable</li> <li>CA Quebec Provincial (Canada, 6/2022).</li> <li>[Silica Crystalline -Quartz]</li> <li>TWAEV: 0.1 mg/m<sup>3</sup> 8 hours. Form:</li> <li>Respirable dust.</li> <li>CA Alberta Provincial (Canada, 6/2018).</li> <li>8 hrs OEL: 0.025 mg/m<sup>3</sup> 8 hours. Form:</li> <li>Respirable particulate</li> <li>CA Ontario Provincial (Canada, 6/2019).</li> <li>[Silica, Crystalline (Quartz/Tripoli)]</li> <li>TWA: 0.1 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate</li> </ul>		
ate of issue/Date of revision : 2/5/2024 Date of 12AF0005 WHITE LIGHTNING® 3006™ Advanced Form	of previous issue	: 9/19/2023 Version : 23 6 SHW-85-NA-GHS-US		

## Section 8. Exposure controls/personal protection

|--|

#### Occupational exposure limits (Mexico)

	CAS # Exposure limits			
Light Aliphatic Hydrocarbon	64742-47-8	ACGIH TLV (United States, 1/2023). [Kerosene as total hydrocarbon vapor] Absorbed through skin. TWA: 200 mg/m <sup>3</sup> , (as total hydrocarbon vapor) 8 hours.		

#### **Biological exposure indices (United States)**

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

W12AF0005

White

WHITE LIGHTNING® 3006™ Advanced Formula

Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	ures de la constante de la const
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Date of issue/Date of revision	: 2/5/2024 Date of previous issue : 9/19/2023 Version : 23 7/14

SHW-85-NA-GHS-US

### Section 8. Exposure controls/personal protection

#### Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance					
Physical state	:	iquid.			
Color	:	/hite.			
Odor	:	ot available.			
Odor threshold	:	ot available.			
рН	:	3			
Melting point/freezing point	:	: Not available.			
Boiling point, initial boiling point, and boiling range	:	00°C (212°F)			
Flash point	:	losed cup: Not applicable.			
Evaporation rate	:	.13 (butyl acetate = 1)			
Flammability	:	ot available.			
Lower and upper explosion limit/flammability limit	:	: Lower: 1% Upper: 6%			
Vapor pressure	:	: 2.3 kPa (17.5 mm Hg)			
Relative vapor density	:	[Air = 1]			
Relative density	:	62			
Solubility(ies)	:				
Media		Result			
cold water		Partially soluble			
Partition coefficient: n- octanol/water	:	ot applicable.			
Auto-ignition temperature	:	: Not available.			
Decomposition temperature	:	: Not available.			
Viscosity	:	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)			
Molecular weight	:	lot applicable.			
Heat of combustion	:	.384 kJ/g			
Castion 10 Stabili	4				

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.

Date of issue/Date	of revision	: 2/5/2024	Date of previous issue	: 9/19/2023	Version	: 23	8/14
W12AF0005	WHITE LIGHTNING® 3	3006™ Advance	ed Formula		SHW-85-	NA-GHS-US	

## Section 10. Stability and reactivity

**Incompatible materials** 

: No specific data.

## Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity

Not available.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
				ug l	

#### Sensitization

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide Crystalline Silica, non- respirable	- +	2B 1	- Known to be a human carcinogen.
Crystalline Silica, respirable powder	+	1	Known to be a human carcinogen.

#### Reproductive toxicity

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Calcium Carbonate	Category 3	-	Respiratory tract irritation
Light Aliphatic Hydrocarbon	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Light Aliphatic Hydrocarbon	Category 2	-	-
Crystalline Silica, respirable powder	Category 1	inhalation	

#### **Aspiration hazard**

Date of issue/Date	of revision	: 2/5/2024	Date of previous issue	: 9/19/2023	Version	:23	9/14
W12AF0005	WHITE LIGHTNING® White	3006™ Advano	ced Formula		SHW-85-	NA-GHS-US	

## Section 11. Toxicological information

Name	Result
Light Aliphatic Hydrocarbon	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	: Not available.
Potential acute health effect	<u>cts</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: May cause respiratory irritation.
Skin contact	: Causes skin irritation.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the pl	hysical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delayed and immediate effo	ects and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	• Not available

enects	
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	iects
Not available.	
General	: May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Mutagenicity Teratogenicity	<ul><li>No known significant effects or critical hazards.</li><li>No known significant effects or critical hazards.</li></ul>
	5
Teratogenicity	: No known significant effects or critical hazards.

#### Numerical measures of toxicity Acute toxicity estimates Not available.

## Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure	
0 1 3	10		4 days 🥄 96 hours	

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Date of issue/Date of rev V12AF0005 WHI White	TE LIGHTNING® 3006™ Ad	•	issue : 9/19/202		on : 23 11/1 -85-NA-GHS-US

Section 14. Transp	oort information			
Special precautions for user	: Multi-modal shipping de consider container sizes			
	mode of transport (sea, suitably for that mode of to shipment, and compli of the person offering th	air, etc.), does not indica transport. All packaging ance with the applicable e product for transport. F	te that the product must be reviewed f regulations is the so People loading and u	is packaged for suitability prior ble responsibility unloading
	dangerous goods must and on all actions in cas			e substances
Transport in bulk according to IMO instruments	: Not available.			
	Proper shipping name	: Not available.		

## Section 15. Regulatory information

#### SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

#### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

#### **International regulations**

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of issue/Date of revision		: 2/5/2024	Date of previous issue	: 9/19/2023	Version : 23	12/14
W12AF0005			ced Formula		SHW-85-NA-GHS-US	6
	White					

## Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

#### Procedure used to derive the classification

	Classification	Justification		
SKIN CORROSION/IRRIT SERIOUS EYE DAMAGE/ CARCINOGENICITY - Ca SPECIFIC TARGET ORG irritation) - Category 3 SPECIFIC TARGET ORG	Calculation method Calculation method Calculation method Calculation method Calculation method			
History				
Date of printing	: 2/5/2024			
Date of issue/Date of revision	: 2/5/2024			
Date of previous issue	: 9/19/2023			
Version	: 23			
Key to abbreviations	IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition co MARPOL = International Convention for the Preven	<ul> <li>TE = Acute Toxicity Estimate</li> <li>CF = Bioconcentration Factor</li> <li>HS = Globally Harmonized System of Classification and Labelling of Chemicals</li> <li>TA = International Air Transport Association</li> <li>C = Intermediate Bulk Container</li> <li>DG = International Maritime Dangerous Goods</li> <li>gPow = logarithm of the octanol/water partition coefficient</li> <li>ARPOL = International Convention for the Prevention of Pollution From Ships, 1973</li> <li>modified by the Protocol of 1978. ("Marpol" = marine pollution)</li> <li>A = Not available</li> <li>GG = Segregation Group</li> </ul>		

✓ Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buver/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

:9/19/2023

: 9/19/2023