



SPECIALTY

MEGALASTIC®

**Siliconized Acrylic Latex
Elastomeric Sealant**



White Lightning® Megalastic® Super Elastic Sealant is a premium sealant which provides “stretchability” of over 700% and has outstanding flexibility and adhesion to most surfaces. Ideal for any caulking project, it is commonly applied to doors, windows, trim, crown molding and any joints where extreme movement can be expected. For use on: drywall, wood, glass, masonry, concrete, metal, porcelain and plastic.

- Superior “stretchability” of over 700%
- Superior Adhesion
- No cracking



PAINTABLE



INTERIOR/
EXTERIOR



WATER
CLEANUP

PART #	UPC	Color	SIZE
--------	-----	-------	------

W13300010	0-23275-04506-4	White	10 fl oz
-----------	-----------------	-------	----------



Product Description:

White Lightning® Megalastic® Super Elastic Sealant is a premium sealant which provides "stretchability" of over 700% and has outstanding flexibility and adhesion to most surfaces. Ideal for any caulking project, it is commonly applied to doors, windows, trim, crown molding and any joints where extreme movement can be expected. For use on: drywall, wood, glass, masonry, concrete, metal, porcelain and plastic.

Physical Properties:

Type: Styrene Acrylic

Colors: White

Shelf Life: 24 Months

Flash Point: N/A (water based)

Flammability: N/A (water based)

Full Cure Time: 48 hours

Tack Free Time: 2 hours

Application Temperature: 40° F to 140° F

Service Temperature: -30° F to 180°

Vehicle: Styrene Acrylic

Solids by Weight: 69.49

Weight/Gallon: 10.90

Painting: Paintable

Primers: Not required

Mildew Resistance: Excellent

Water resistance: Excellent

Odor: Low

Shrinkage: Low

Performance Data:

Joint Size: 1/8" x 1/8" to 1/2" x 1/2"

Freeze-Thaw Stability: Passes Through 5 Cycles

Shelf Life: 24 Months

Clean Up: Water; promptly clean tools and excess caulk with water or a damp cloth.

Flexibility: Superior

Linear Coverage: 10 oz cartridge 24 ft at 1/4" wide by 1/4" deep bead

Painting: A minimum of 4 hours dry time is required before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

Application:

1. Remove all existing caulk from surface.
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

• 10 FL oz cartridge

- Cut cartridge tip 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

Clean Up:

Water; promptly clean tools and excess caulk with water or a damp cloth.

Cautions:

See SDS

Limitations:

For best results, apply at temperatures above 40° F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line.

LIMITED WARRANTY:

LIMITED WARRANTY: If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

For more information please call or write:

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com