



SPECIALTY

PAINTABLE SILICONE

Premium Hybrid Sealant



White Lightning® Paintable Silicone is a high performance hybrid sealant with EMR™ technology that resists rain and water washout after three hours of application. It is also paintable in 30 minutes. White Lightning® Paintable Silicone features excellent adhesion and silicone-like performance with paintability of an acrylic latex sealant. For use on: aluminum, glass, marble, wood, steel, trim, vinyl siding & various types of plastic.

- Premium Hybrid Technology
- Excellent Adhesion and Flexibility
- Weather and UV Resistant
- Provides a Water Tight Seal



WATER
PROOF



PAINTABLE



INTERIOR/
EXTERIOR

PART #	UPC	Color	SIZE
W31202210	0-23275-99017-3	White	9 fl oz



WHITE



Paintable Silicone

**PREMIUM
HYBRID
TECHNOLOGY**

- Excellent Adhesion & Flexibility
- Weather & UV Resistant
- Provides a Watertight Seal

**HYBRID
SEALANT**



WATERPROOF



PAINTABLE



INTERIOR/
EXTERIOR



Exceeds ASTM C-920,
Class 25

9 FL OZ (266 mL)

Product Description:

White Lightning® Paintable Silicone is a high performance hybrid sealant with EMR™ technology that resists rain and water washout after three hours of application. It is also paintable in 30 minutes. White Lightning® Paintable Silicone features excellent adhesion and silicone-like performance with paintability of an acrylic latex sealant. For use on: aluminum, glass, marble, wood, steel, trim, vinyl siding & various types of plastic.

Physical Properties:

Type: Silane Terminated Polyether

Colors: White

Shelf Life: 18 Months

Flash Point: N/A

Flammability: N/A

Full Cure Time: 24 Hours

Tack Free Time: <1 Hour

Application Temperature: 40° F to 140° F

Service Temperature: Up to 400° F for short periods

Vehicle: Silane Terminated Polymer

Solids by Weight: 12.06

Weight/Gallon: 12.6 lbs/gal

Paintable: Paintable

Primers: Not required

Mildew Resistance: Excellent

Water resistance: Excellent

Odor: Low

Shrinkage: Low

Performance Data:

Joint Size: 1/8" x 1/8" to 1/2" x 1/2"

Freeze-Thaw Stability: N/A

Shelf Life: 18 Months

Clean Up: Mineral spirits, promptly clean tools and excess caulk; wash hands with soap and water.

Flexibility: Excellent

Durability: Excellent

Linear Coverage: 9 oz cartridge 21.6 ft at 1/4" wide by 1/4" deep bead.

Paintable: Can be painted after 30 minutes (65°F and 50% humidity). Allow extra dry time during periods of high humidity and/or cool temperatures.

ASTM: Single component, Non-Sag, Exceeds C-920, class 35

Application:

1. Remove all existing caulk
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

9oz cartridge

- Cut cartridge tip 45° angle.
- Puncture inner seal.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

Clean Up:

Mineral spirits, promptly clean tools and excess caulk; wash hands with soap and water.

Cautions:

See SDS

LIMITATIONS:

For best results, apply at temperatures above 40° F and allow 3 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line.

LIMITED WARRANTY:

LIMITED WARRANTY: For the life of the single family house to which this product is applied, if when applied according to label directions within one year from date of purchase, if this product fails to perform in accordance with the specifications set forth on this label, as your sole remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. Applies to single family house only. This warranty is made to the original residential consumer purchaser and is not transferable. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

For more information please call or write:

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com