



**SPECIALTY**

# SEASONSeal™

Synthetic Polymer



White Lightning® SEASONSeal™ Removable Weather Stripping Sealant is a temporary sealant that provides a clear, weathertight seal around interior/ exterior areas where drafts are a problem. It is easily removable and will not harm painted surfaces. Commonly used on: windows, doors or other exterior openings.

- Removable after use
- Insulates against drafts & leaks
- Won't harm painted surfaces



WATER  
PROOF



INTERIOR/  
EXTERIOR

PART #	UPC	Color	SIZE
W41501010	0-23275-09595-3	Clear	10 fl oz

CLEAR



SEASONSeal™

**REMOVABLE  
WEATHER  
STRIPPING**

- Removable After Use
- Insulates Against Drafts and Leaks
- Won't Harm Painted Surfaces

**SYNTHETIC  
POLYMER**



WATERPROOF



INTERIOR/  
EXTERIOR

**DANGER!**  
HARMFUL OR FATAL  
IF SWALLOWED.  
COMBUSTIBLE! VAPOR  
HARMFUL. IRRITATES  
EYES, SKIN AND  
RESPIRATORY TRACT.

Before using,  
carefully read  
CAUTIONS on  
back panel

10 FL OZ (295 mL)

### Product Description:

White Lightning® SEASONSeal™ Removable Weather Stripping Sealant is a temporary sealant that provides a clear, weathertight seal around interior/exterior areas where drafts are a problem. It is easily removable and will not harm painted surfaces. Commonly used on: windows, doors, or other exterior openings.

### Physical Properties:

**Type:** Synthetic Polymer

**Colors:** Clear

**Shelf Life:** 12 Months

**Flash Point:** 109° F

**Flammability:** Combustible

**Full Cure Time:** 24 hours/removable after five days

**Tack Free Time:** 5 Minutes at 75° F

**Application Temperature:** 40° F to 120° F

For ease of application, bring product to room temperature prior to application.

**Service Temperature:** -20° F to 140° F

**Vehicle:** Solvent based

**Solids by Weight:** 38 +/- 2%

**Weight/Gallon:** 7.03 +/- 2 %

**Paintable:** No

**Primers:** Not required

**Mildew Resistance:** Excellent

**Water resistance:** Excellent

**Odor:** Low

**Shrinkage:** Low

---

### Performance Data:

**Joint Size:** 1/4" x 1/4" to 3/8" x 3/8"

**Freeze-Thaw Stability:** Freeze-Thaw Stable

**Shelf Life:** 12 Months

**Clean Up:** Mineral Spirits; promptly clean tools and excess sealant, wash hands with soap and water.

**Flexibility:** Excellent

**Linear Coverage:** 10 oz cartridge 24ft at 1/4" wide by 1/4" deep bead

**Paintable:** No

### Application:

1. Clean surfaces thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
2. Cut cartridge tip diameter between 1/4" and 5/16" (maximum) at 45° angle.

3. **Be sure to puncture inner seal, completely**

4. Load cartridge into caulk gun

5. Squeeze trigger - tooling not required.

6. Remove sealant after use (minimum 5 days).

*For ease of application, bring product to room temperature prior to application.*

### Clean Up:

Mineral Spirits; promptly clean tools and excess sealant, wash hands with soap and water.

### Cautions:

See SDS

### Limitations:

Do not paint

### LIMITED WARRANTY:

**LIMITED WARRANTY:** If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

---

**For more information please call or write:**

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115  
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service  
[www.wlcaulk.com](http://www.wlcaulk.com)