



SPECIALTY ASPHALT ROOF SEALANT



White Lightning® Asphalt Roof Sealant is ideal for sealing leaks and openings and provides a durable, watertight seal when waterproofing, repairing or sealing roofs. Commonly applied at flashing, copings, roof decks, roof vents and repairing loose shingles. For use on: aluminum, asphalt, brick, cement, concrete, stone and vinyl.

- Excellent Adhesion and Weatherproofing
- Long-lasting Watertight Seal



PART #	UPC	Texture	SIZE
W43505010	023275002159	Black	10 FL oz





SPECIALTY Asphalt Roof Sealant

Product Description:

White Lightning® Asphalt Roof Sealant is ideal for sealing leaks and openings and provides a durable, watertight seal when waterproofing, repairing or sealing roofs. Commonly applied at flashing, copings, roof decks, roof vents and repairing loose shingles. For use on: aluminum, asphalt, brick, cement, concrete, stone and vinyl.

Physical Properties:

Type: Roof Sealant

Color: Black

Shelf Life: 36 months

Flash Point: 101°F

Flammability: Combustible

Full Cure Time: 7-14 days

Tack Free Time: Up to 12 hours depending on drying conditions

Application Temperature: Above 32° F

Service Temperature: -40°F to 180°F

Vehicle: Solvent Based

Solids by Weight: 80%

Weight: 9.35 lbs/gallon

Painting: Not Paintable

Primers: Not Required

Performance Data:

Joint Size: 1/8" x 1/8" to 1/2" x 1/4"

Freeze-Thaw Stability: Will withstand multiple freeze-thaw cycles.

Shelf Life: 36 Months

Clean Up: Clean tools and excess sealant with mineral spirits, wash hands with soap and water or a damp cloth

Flexibility: Excellent

Mildew Resistance: Good

Painting: Not Paintable

ASTM: ASTM D 4586, Type I, Class II

Application:

1. Remove all existing caulk.
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

- Cut tip at 45° angle.
- Puncture inner seal
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

Clean Up:

Clean tools and excess sealant with mineral spirits, wash hands with soap and water or a damp cloth while still wet.

Cautions:

See SDS

Limited Warrantee:

If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

For more information please call or write:

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com