



# WINDOW | DOOR

## SILICONE ULTRA

### 100% Silicone Sealant



White Lightning® Window & Door Silicone Ultra is a premium 100% silicone sealant that provides a superior weather resistant seal. It is extremely durable, UV resistant, and water ready in three hours. White Lightning® Window & Door Silicone Ultra is commonly applied at: windows, doors, vinyl siding, trim, etc. It is excellent for interior/exterior application on: wood, glass, fiberglass, metal, vinyl, masonry, stucco, plaster and many plastics.

- Superior Weather Resistant Seal
- Permanently Flexible
- Easy to Apply
- Durable / Long Lasting



INTERIOR/  
EXTERIOR



WATERPROOF

PART #	UPC	COLOR	SIZE
W31100010	0-23275-09215-0	White	10 fl oz
W31101010	0-23275-09015-6	Clear	10 fl oz
W31104510	0-23275-00991-2	Aluminum	10 fl oz
W31103510	0-23275-00981-3	Bronze	10 fl oz





## WINDOW | DOOR Silicone Ultra

### Product Description:

White Lightning® Window & Door Silicone Ultra is a premium 100% silicone sealant that provides a superior weather resistant seal. It is extremely durable, UV resistant, and water ready in three hours. White Lightning® Window & Door Silicone Ultra is commonly applied at: windows, doors, vinyl siding, trim, etc. It is excellent for interior/exterior application on: wood, glass, fiberglass, metal, vinyl, masonry, stucco, plaster and many plastics.

### Physical Properties:

**Type:** 100% Silicone

**Colors:** White, Clear, Aluminum, Bronze

**Shelf Life:** 12 months

**Flash Point:** >200°F

**Flammability:** n/a

**Full Cure Time:** 24 hours

**Tack Free Time:** 30 Minutes at 75°F

**Application Temperature:** -20°F to 122°F

**Service Temperature:** -60°F to 300°F

**Vehicle:** Solvent Based

**Solids by Weight:** 96.9%

**Weight/Gallon:** 8.69

**Painting:** Not Paintable

**Primers:** Not required

**Mildew Resistance:** Excellent

**Water Resistance:** Excellent

**Odor:** Low

**Shrinkage:** Low

### Performance Data:

**Joint Size:** 1/8" x 1/8" to 1/2" x 1/2"

**Freeze-Thaw Stability:** n/a

**Shelf Life:** 12 Months

**Clean Up:** Mineral spirits, promptly clean tools and excess caulk; wash hands with soap and water.

**Flexibility:** Excellent

**Linear Coverage** 10oz cartridge 24ft at 1/4" wide by 1/4" deep bead

**Painting:** Not paintable.

**ASTM:** Exceeds ASTM C-920, Class 25. Meets or exceeds performance requirements of Federal Specification TT-S-001543A Class A (COM-NBS) for silicone building sealants and TT-S-00230C Class A (COM-NBS) for one-component sealants.

### Application:

1. Remove all existing caulk
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

### • 10oz cartridge

- Unscrew nozzle, cut cartridge nub, screw on nozzle
- Cut nozzle tip 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

### Clean Up:

Mineral spirits, promptly clean tools and excess caulk; wash hands with soap and water.

### Cautions:

See MSDS

### Limitations:

For best results, apply at temperatures above 40°F and allow 3 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line.

### LIMITED WARRANTY:

If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

**For more information please call or write:**

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115  
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service  
[www.wlcaulk.com](http://www.wlcaulk.com)