



# WINDOW | DOOR WEATHER SEAL

## Siliconized Acrylic Latex Caulk



White Lightning® Weather Seal is a siliconized acrylic latex adhesive caulk that offers a weathertight/watertight seal for interior and exterior applications. The latex formula provides for easy application and easy water clean-up. Ideal for use on doors, windows and trim. White Lightning® Weather Seal seals cracks between aluminum, metal, plastic, vinyl, wood.

- Flexible Seal
- Good Adhesion and Durability
- Cured Caulk is Mold and Mildew Resistant



INTERIOR/  
EXTERIOR



PAINTABLE



WATER  
CLEANUP

PART #	UPC	Color	SIZE
W32000010	0-23275-30600-4	White	10 fl oz

WHITE



WINDOW | DOOR

# WEATHER SEAL

- Flexible Seal
- Good Adhesion and Durability

SILICONIZED  
ACRYLIC LATEX  
CAULK



PAINTABLE



INTERIOR/  
EXTERIOR



WATER  
CLEANUP



Exceeds ASTM C-834

### Product Description:

White Lightning® Weather Seal is a siliconized acrylic latex adhesive caulk that offers a weathertight/watertight seal for interior and exterior applications. The latex formula provides for easy application and easy water clean-up. Ideal for use on doors, windows and trim. White Lightning® Weather Seal seals cracks between aluminum, metal, plastic, vinyl, wood.

### Physical Properties:

**Type:** Acrylic

**Colors:** White

**Shelf Life:** 24 Months

**Flash Point:** n/a (water based)

**Flammability:** n/a (water based)

**Full Cure Time:** 5 to 7 days at 75° F

**Tack Free Time:** 12 Minutes at 75° F

**Application Temperature:** above 40° F

**Service Temperature:** -30° F to 180° F

**Vehicle:** Water

**Solids by Weight:** 82% +/- .2%

**Weight/Gallon:** 13.55 lbs/gal

**Painting:** Paintable

**Primers:** Not required

**Mildew Resistance:** Good

**Water Resistance:** Good

**Odor:** Low

**Shrinkage:** Low

---

### Performance Data:

**Joint Size:** 1/8" x 1/8" to 1/2" x 1/4"

**Freeze-Thaw Stability:** Passes Through 5 Cycles

**Shelf Life:** 24 Months

**Clean Up:** Water, promptly clean tools and excess caulk with water or a damp cloth.

**Flexibility:** Good

**Linear Coverage** 10oz cartridge 24ft at 1/4" wide by 1/4" deep bead

**Painting:** A minimum of 4-5 hours dry time is required before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

**ASTM:** Exceeds ASTM Specification C-834

### Application:

1. Remove all existing caulk
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

### • 10oz cartridge

- Cut cartridge tip 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

### Clean Up:

Water; promptly clean tools and excess caulk with water or a damp cloth.

### Cautions:

See MSDS

### Limitations:

For best results, apply at temperatures above 40° F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line

### LIMITED WARRANTY:

LIMITED WARRANTY: If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

**For more information please call or write:**

---

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115  
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service  
[www.wlcaulk.com](http://www.wlcaulk.com)