

# Kitchen & Bath Latex Ultra Sealant

## **Physical Properties:**      *Kitchen & Bath Latex Ultra Sealant*

<b>Type:</b>	Acrylic	Acrylic
<b>Color:</b>	White and Bisque	Clear
<b>Shelf Life:</b>	12 Months	12 Months
<b>Flash Point:</b>	n/a (water based)	n/a (water based)
<b>Flammability:</b>	n/a (water based)	n/a (water based)
<b>Full Cure Time:</b>	3 to 4 days	5 to 7 days
<b>Tack Free Time:</b>	45 Minutes at 75° F	45 Minutes at 75° F
<b>Application Temperature:</b>	40° F to 140° F	40° F to 140° F
<b>Service Temperature:</b>	-30° F to 180° F	-30° F to 180° F
<b>VOC Level:</b>	1.96%	
<b>Mildew Resistance:</b>	Excellent	Excellent
<b>Water Resistance:</b>	Excellent	Excellent
<b>Odor:</b>	Low	Low
<b>Shrinkage:</b>	Low	Low/Moderate
<b>Vehicle:</b>	Acrylic Polymer	Acrylic Polymer
<b>Solids by Weight:</b>	69+/-2%	62.02+/-1%
<b>Weight/Gallon:</b>	10.78+/-0.15	8.81+/-0.2 lb.
<b>Painting:</b>	Paintable	Paintable

## **Performance Data:**

<b>Joint Movement Capability:</b>	Excellent	Excellent
<b>Joint Size:</b>	1/8" x 1/8" to 1/2" x 1/2"	1/8" x 1/8" to 1/2" x 1/2"
<b>Freeze-Thaw Stability</b>	Passes Through 5 Cycles	Stable Through 5 Cycles
<b>Clean Up:</b>	Water	Water
<b>Flexibility:</b>	Excellent	Excellent
<b>Durability:</b>	Excellent	Excellent

### **Product Description:**

White Lightning® Kitchen and Bath Latex Ultra Sealant is an easy to use interior/exterior caulk. It is used for sealing and waterproofing areas around bathrooms, basins, sinks, showers, toilets, countertops and splashboards.

### **Surface Preparation:**

Remove old caulk. Clean thoroughly to remove grease, dirt, oil, wax, loose paint, dust and soap film. Remove mildew with bleach and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

### **Painting:**

A minimum of 4 hours dry time is required before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

### **Clean-Up:**

Promptly clean tools and excess caulk with water or a damp cloth.

### **Cautions:**

Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage.

### **Limitations:**

For best results, apply at temperatures above 40° F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line.



**For more information please call or write:**

White Lightning® Products • 101 Prospect Ave. NW • Cleveland, OH 44115  
1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service  
[www.wlcaulk.com](http://www.wlcaulk.com)