

**White Lightning®**  
**Siliconized Latex Glazing Compound**  
WL08012

**Physical Properties:**

<b>Type:</b>	Siliconized Latex glazing compound
<b>Color:</b>	White
<b>Shelf Life:</b>	12 months
<b>Flash point:</b>	N/A - Waterbased
<b>Flammability:</b>	N/A - Waterbased
<b>Cure Time:</b>	2-5 Days
<b>Tack Free Time:</b>	30 – 60 minutes
<b>Application Temperature:</b>	Above 50 F
<b>VOC Level:</b>	0.464 lbs / gal
<b>Mildew Resistance:</b>	Excellent
<b>Odor:</b>	Low
<b>Shrinkage:</b>	Low / None
<b>Vehicle:</b>	Water
<b>Weight per gallon:</b>	15.32 lbs/gal

**Performance:**

<b>Joint movement capability:</b>	Good
<b>Glazing bead sizes (recommended):</b>	1/8" x 1/8" – 3/8" – 3/8"
<b>Freeze / thaw stability:</b>	Passes 5 cycles
<b>Clean-up:</b>	Water
<b>Flexibility:</b>	Excellent
<b>Painting:</b>	Paintable within 4-6 hours
<b>Water resistance:</b>	Good

**Surface Preparation:** Apply to clean, dry surface. For best results, surface should be primed before glazing.

**Precautions:** Do not use in areas subject to water. Keep from freezing.

**Packaging:**

<b>Size</b>	<b>Order#</b>	<b>UPC</b>
10 oz cartridge	WL08012	0-23275-08012-6

For More Information please call or write:  
White Lightning Products  
101 Prospect Ave NW  
Cleveland, OH 44115  
1-800-241-5295  
3/4/08

