

White Lightning® WL2000 Drywall/ All Purpose Construction Adhesive

Physical Properties:

WL2000 All Purpose Construction Adhesive

Type:	Solvent-Based Adhesive	Storage Temperature:	Room Temperature
Color:	Tan	VOC Level:	344.3 g/l
Shelf Life:	12 Months	Shrinkage:	Low/Moderate
Flash Point:	Less Than 0°F	Vehicle:	Synthetic Rubber
Open Time:	30 Minutes	Weight Solids:	68%
Full Cure Time:	24 Hours	Weight/Gallon:	9.2 lbs/gal
Application Temperature:	20°F to 110°F	Consistency:	Medium Mastic
Service Temperature:	0°F to 175°F		

Performance Data:

Clean-Up:	Mineral Spirits
Water Resistance:	Excellent
Mildew Resistance:	Excellent
Linear Coverage:	
10 oz Cartridge	
3/8" Bead Application	11.5 ft
29 oz Cartridge	
3/8" Bead Application	33.4 ft

Product Description: White Lightning® WL2000 Drywall/All Purpose Construction Adhesive is a high performance adhesive.

Basic Uses: WL2000 simplifies the construction process by reducing nailing in repair, remodeling and other general purpose jobs. Can be used on: drywall, hardboard, particleboard, gypsumboard, fiberglass, ceramic/terracotta tile, decorative strips and trim. WL2000 can be used to bond drywall to masonry or any other structurally sound surface.

Surface Preparation: Surface should be clean, dry, free from oils, dirt, old caulking, old paint or other contaminants.

Walls: Nail at 16" intervals around perimeter of board where board contacts framing.

Ceilings: Where board contacts framing, nail at 16" intervals around perimeter. When board is installed parallel to framing, use four nails spaced 24" apart down the center of the board. When the board is installed across framing, use only one nail per framing member down the center of the board.

Cautions: Contents are EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. During use, and until all vapors are gone. Keep area ventilated. Do not smoke. Extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools and appliances, and any other sources of ignition.

CONTAINS: CRYSTALLINE SILICA, HEXANE AND TOLUENE. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. Avoid contact with eyes and skin. Wash hands after using. Do not transfer to other containers for storage.

Limitations: For best results store product at room temperature for 24 hours before using. Apply adhesive with liberal coverage. Position materials within 5-10 minutes of application. For large or heavier materials, fasten securely with nails or screws at corners and borders if needed.

Specifications: Meets and exceeds ASTM C-557, ASTM E-72 for racking and shear, conforms to Canadian Specification CAN/CG G-71.25-M88. Certified by BOCA under Research Report #82-63. Recommended by ICBO under Research #2231. Accepted by HUD. Meets FHA requirements.



For more information please call or write:

White Lightning® Products • 101 Prospect Ave. NW • Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com