

White Lightning® PAINTER'S PREFERRED™ Acrylic Latex Caulk

Physical Properties:

PAINTER'S PREFERRED™ Acrylic Latex Caulk

Type:	Acrylic Latex Caulk	Application Temperature:	40°F to 120°F
Color:	White	Service Temperature:	-30°F to 180°F
Shelf Life:	12 Months	VOC Level:	.50 lb/gal
Flash Point:	N/A	Odor:	Low/None
Flammability:	N/A	Shrinkage:	Low/Moderate
Full Cure Time:	7-14 Days	Vehicle:	Water
Tack Free Time:	5-7 Minutes	Weight Solids:	82%
		Weight/Gallon:	13.71 lbs/gal

Performance Data:

Joint Movement Capability:	Low	Water Resistance:	Good
Joint Size:	1/2" x 1/4" to 1/8" x 1/8"	Mildew Resistance:	Good
Freeze-Thaw Stability:	Stable Through 5 Cycles	Linear Coverage:	
Clean-Up:	Water	10 oz Cartridge	
Flexibility:	Good	1/8" Bead Application	96.7 ft
Painting:	Paintable	1/4" Bead Application	24.2 ft

Product Description:

White Lightning® PAINTER'S PREFERRED™ Acrylic Latex Caulk is an economical, easy to use interior/exterior caulk.

Basic Uses:

PAINTER'S PREFERRED™ is an economical general purpose product suitable for sealing openings around wood, drywall and plastics. Ideal for use on doors, windows and trim work. Not recommended for crown molding.

Surface Preparation:

Surface should be clean, dry, free from oils, dirt, old caulking, old paint or other contaminants.

Painting:

A minimum of 2 hours dry time is required before painting with latex or oil based paint. Allow extra dry time during periods of high humidity or cool temperatures.

Cautions:

Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer to other containers for storage.

Limitations:

For best results apply at temperatures above 40°F. Never use in deep joints, joints subject to heavy abrasion and wear, or those that are frequently under water. Do not apply when rain or moisture is expected.

Specifications:

Meets performance requirements of ASTM C-834-00, Grade NF for extension recovery and adhesion.



For more information please call or write:

White Lightning® Products • 101 Prospect Ave. NW • Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com