

White Lightning® Window & Door Acrylic Latex Caulk

Physical Properties:		Window & Door Acrylic Latex Caulk	
Type:	Acrylic Latex Caulk With Silicone	Application Temperature:	Above 50°F
Color:	White	Service Temperature:	-30°F to 180°F
Shelf Life:	12 Months	VOC Level:	.387 lbs/gal
Flash Point:	N/A (Waterbased)	Odor:	Low
Flammability:	N/A (Waterbased)	Vehicle:	Water
Full Cure Time:	5-7 Days	Solids by Weight:	82.6%
Tack Free Time:	12 Minutes at 75°F	Weight/Gallon:	13.55 lbs/gal
Performance Data:			
Joint Movement Capability:	Moderate	Water Resistance:	Good
Joint Size:	1/8" x 1/8" to 1/2" x 1/4"	Rust Resistance:	Good
Freeze-Thaw Stability:	Passes Through 5 Cycles	Shrinkage:	Low
Clean-Up:	Water	Linear Coverage:	
Flexibility:	Good	10 oz Cartridge	
Painting:	Paintable	1/8" Bead Application	96.7 ft
Mildew Resistance:	Good	1/4" Bead Application	24.2 ft

Product Description:

White Lightning® Window & Door Acrylic Latex Caulk is an easy-to-use interior/exterior caulk.

Basic Uses:

Window & Door Acrylic Latex Caulk is used for sealing and filling joints and openings around doors, windows and trim.

Surface Preparation:

Surface should be clean, dry, free from oils, dirt, old caulking, old paint or other contaminants.

Painting:

A minimum of 4-5 hours dry time is recommended before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

Cautions:

Use with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage.

Limitations:

For best results, apply at temperatures above 50°F. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line.

Specifications:

Exceeds ASTM Spec C-834.



For more information please call or write:

White Lightning® Products • 101 Prospect Ave. NW • Cleveland, OH 44115
 1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com