

# White Lightning<sup>®</sup> STORM BLASTER™ All Season Sealant

## Physical Properties:

---

Type:	Synthetic rubber in solvent
Color:	Clear
Shelf Life:	12 months
Flash Point:	52°F
Flammability:	Flammable
Cure Time:	1 week
Tack Free Time:	30 minutes
Application Temperature:	0° - 120°
Service Temperature:	Less than 200°F
VOC Level:	330 g/l
Water Resistance:	Excellent
Odor:	Hydrocarbon Odor
Shrinkage:	Moderate
Vehicle:	Hydrocarbon Solvents
Solids by Weight:	7.28 lbs./gal

## Performance Data:

---

Joint Size:	½" wide x ½" deep
Freeze-Thaw Stability:	Keep from freezing
Clean Up:	Clean tools with mineral spirits
Flexibility:	Excellent
Painting:	Latex paint in 24 hours or oil-based paint within 1 week

## Application:

1. Surface should be free from oils, loose mortar, release agents, old caulking, old paint, or other contaminants.
2. Cut tip to desired orifice size at a 45° angle, puncture inner seal and load cartridge into caulk gun.
3. Squeeze trigger to start flow of material, then work caulk into joint.
4. Smooth or trim caulk with a proper tool. Small amount of soapy water or mineral spirits helps smoothing.
5. Clean up with mineral spirits.
6. **FOR BEST RESULTS:** Do not use in areas of continuous submersion (i.e. aquariums or swimming pools). Do not use in areas where temperatures exceed 200°F. Do not apply to frosty or icy surfaces. STORM BLASTER may damage some plastics, such as polystyrene foam insulation.

## Ingredients:

V. M. & P. Naphtha 64742-89-8, Hydrocarbon Polymer Proprietary, Toluene 108-88-3, Styrene-Butadiene, Polymer Proprietary, Styrene-Hydrocarbon, Copolymer Proprietary

**Cautions:** FLAMMABLE. Contains toluene and other petroleum distillates. Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage. Keep away from heat and open flame. Use only in well-ventilated areas. Keep out of reach of children. **FIRST AID:** In case of eye contact, flush with large amounts of water for at least 15 minutes. Get medical attention. For skin contact, wash thoroughly with soap and water. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

**Limitations:** Product may damage polystyrene insulation. We recommend testing a small area of material before applying product to plastic or fiberglass. Do not use in areas of continuous submersion such as fish tanks or swimming pools. Do not apply to frosty or icy surfaces.

## Packaging:

Color	Order #	UPC	Size
Clear	WL7701010	0-23275-77010-2	10.0 fl oz.

For more information please call or write:  
White Lightning Products  
101 Prospect Ave. NW  
Cleveland, OH 44115  
1-800-241-5295 Customer Service  
1-800-241-5295 Technical Service



Part # WP0009510