



Dutch Boy® Dimensions® Granite

Product Data Sheet

DB2000 - Granite

Give your walls the look and feel of well-worn stone with **Dutch Boy® Dimensions® Granite Unique Decorative Interior Finish**. Layers of rich texture with light and dark highlights complement a range of design aesthetics from stately elegance to industrial chic. A stunning addition to bedrooms, dens, theater rooms, and living rooms, Dimensions Granite is the easy way to add depth and beauty to any room. For color inspiration and how-to advice, check out the Dutch Boy Faux Real brochure. Dimensions Granite Unique Decorative Interior Finish is available in the easy-to-use Dutch Boy Twist & Pour® container.

Features

- Unique decorative finish offers the distinct look and feel of stone with a lightly pebbled matte finish
- Intricate layers add texture and depth to your walls with contrasting light and dark highlights
- Instructions are easy to follow and are supported by online content
- Backed by a satisfaction guaranteed warranty

Where To Use

Use on properly prepared interior walls and ceilings of previously painted or bare drywall, plaster, masonry, wood and primed metal.

Recommended Systems

Prime all unpainted surfaces with an appropriate primer. Dimensions® Granite applies best over non-slick surfaces. A basecoat of Dutch Boy® flat or eggshell paint tinted to a similar color as Dimensions® Granite is recommended over glossy paints.

Previously Painted Surfaces:

- Over glossy paints, a basecoat of Dutch Boy® flat or eggshell paint tinted to a similar color as Dimensions® Granite is recommended
- 2 coats of Dimensions® Granite

Bare Surfaces: Drywall, Plaster, Masonry, Primed Metal, and Wood:

- 1 coat appropriate primer
- 2 coats of Dimensions® Granite

COVERAGE:



Up to 200 sq. ft./gal

DRY TIME (@77°F, 50% R.H.):



Touch: 1 hour

Recoat: 4 hours

APPLICATION:



Brush: nylon/polyester
Roller: 3/8" synthetic nap

CLEAN UP:



Warm soapy water

Application

- Apply when surface, air and product temperatures are above 50°F. Paint dries best between 65°F and 85°F.
- Stir paint thoroughly. Mix gallons together when using more than one gallon of the same product. Do not thin.
- Starting at the top corner of the wall, cut in 18" strips of Dimensions® Granite across the ceiling and down the corner with a brush.
- Using a high quality 3/8" nap synthetic roller, fill in the 18" x 18" section with just enough pressure to spread the product evenly, while rolling over the cut-in area to texture it.
- Continue down the wall by cutting in at the corner, and rolling 18" x 18" sections all the way down the wall, reloading the roller for each section.
- When the column is complete, follow with a light, continuous sweep of the roller from ceiling to floor without reloading the roller. This will smooth the finish.
- Repeat this process all the way across the wall, and allow to dry at least 4 hours.
- It is normal for the first coat to look somewhat uneven – this will be corrected with the second coat.
- Repeat the same process for the second coat.
- Two coats are required.

Brush:

Nylon/Polyester

Roller:

Synthetic, 3/8" Nap

Clean Up/Disposal

- Clean hands and tools with warm, soapy water.
- Promptly wipe up spills and spatters with a damp cloth.
- In event of a spill, absorb with inert material such as sand or kitty litter.
- Dispose of empty container or unused portion in accordance with local, state, and federal regulations.

Maintenance

Freshly painted surfaces may be washed after 30 days. Clean with mild, non-abrasive, non-oily cleanser and water. When it is time to repaint, two coats of any Dutch Boy® paint will completely cover the subtle texture of Dimensions® Granite.

Cautions

- Protect from freezing
- For interior use only

Surface Preparation

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (In US) or contact your local health authority.

All surfaces should be sound, clean, dull and dry. Remove loose paint. Wash with a mild, non-abrasive, non-oily cleanser and water. Rinse completely, let dry. Fill cracks and holes with patching/spackling paste and sand smooth. Sand glossy surfaces dull. Remove sanding dust with a damp cloth.

Drywall: Wipe with a damp cloth to remove dust. Allow to dry. Fill cracks & holes with spackling compound and sand smooth. Joint compound must be cured and sanded smooth. Remove all sanding dust.

Plaster: All new surfaces must be hard and cured according to the supplier's recommendations—usually at least 30 days. Treat textured, soft, porous, or powdery plaster with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry.

Masonry: Allow new masonry to cure at least 30 days. Surface must have a pH less than 8. Clean old masonry with a wire bristle brush to remove all loose concrete and efflorescence. Rinse thoroughly and allow to dry. Fill rough surfaces, if desired, with block filler.

Wood: Sand any exposed wood to a fresh smooth surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. Remove all sanding dust.

Aluminum and Galvanized Metal: Wash with appropriate cleaner to remove any oil, grease, or surfaces contamination using a water-based cleaner-degreaser. Remove all corrosion with sandpaper, steel wool, or other abrading methods. Wipe with a damp cloth.

Caulking: Fill gaps between walls, ceilings, crown moldings, and other trim with latex or siliconized latex caulk after priming the surface.

Mildew: Remove mildew before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the mildewed area for 10 minutes. Rinse thoroughly with water and allow surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

Technical Data

Vehicle:	Vinyl Acrylic
Finish:	Flat
Flash Point:	N/A
Weight Solids:	51% ± 2%
Volume Solids:	38% ± 2%
Dry Time(@77°F and 50% R.H.):	
To Touch:	1 hour
To Recoat:	4 hours
Weight per gallon:	10.6 lb/gal
VOC:	VOC 92 g/L - 1.37 lb./gal as per 40 CFR 59.406
Spread Rate:	Up to 200 sq. ft. per gal
Film Thickness:	@ 4 mils wet; 1.52 mils dry
Sizes:	Gallon

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.