

PRODUCT NAME: Premium Interior Acrylic Primer

PRODUCT NUMBER: #107 Series

DESCRIPTION: FLEX BON Interior Acrylic Latex Primer

USES: SPECIFY FOR priming interior drywall, plaster or concrete, masonry, and stucco. May be applied to wood. Seals drywall without raising fibers, for a smooth finish. Alkali resistant for compatibility with plaster or concrete, masonry and stucco. Allows for good adhesion of the finish to sound textured drywall surfaces. Provides good hold-out of sheen finishes.

TYPICAL FINISHES: All Flex Bon Interior Latex and Oil Finishes.

LIMITATIONS/CAUTIONS:

Plaster or concrete, masonry, and stucco surfaces should be completely dry and well cured. All surfaces to be primed should be sound, dry, clean, and free from dust or chalky powder.

SPECIFICATIONS: Apply at no greater than 450 square feet per gallon (3.6 wet mils thick) to achieve 1.1 dry mils. Apply by brush, roller or airless spray.

TECHNICAL DATA:

RESIN TYPE:	Modified Acrylic
PIGMENT TYPE:	Titanium Dioxide
FINISH:	Flat
VISCOSITY:	91 ± 3 K.U.
WEIGHT PER GALLON:	10.8 lbs.
WEIGHT OF NON-VOLATILES:	45.0%
VOLUME OF NON-VOLATILES:	29.4%
DRY TO TOUCH IN HOURS:	1/2 – 2
RECOAT TIME IN HOURS:	4 - 6
THINNER:	Water
FLASH POINT:	N/A
VOC IN GRAMS PER LITER:	75
FEDERAL SPEC. EQUIV.:	TT-P-650

Dry time and recoat time is temperature, humidity, and film thickness dependent.

This information is intended for selecting products or systems for various applications. The applicator should obtain more detailed information from the product label. Flex Bon representatives are also available for consultation.

02/07