

PRODUCT NAME: Premium Exterior Acrylic Primer

PRODUCT NUMBER: #194 Series

DESCRIPTION: FLEX BON Exterior 100% Acrylic Latex Primer

USES: SPECIFY FOR concrete, masonry, stucco, wood, steel, galvanized metal, aluminum, asbestos siding, plaster or hardcoat. Alkali resistant. Good stain blocking qualities. Flash rust resistant. See Bulletins: Coating "Staining Woods" such as Cedar and Redwood and "Preparing Galvanized Metal." Also use to seal light chalk or previously painted wood surfaces prior to repainting. Also suitable for interior use with interior top coats.

TYPICAL FINISHES: All Flex Bon Exterior Latex and Oil Finishes.

LIMITATIONS/CAUTIONS:

USE WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER USE. WASH HANDS AFTER HANDLING AND BEFORE EATING OR SMOKING. KEEP OUT OF THE REACH OF CHILDREN. KEEP FROM FREEZING.

SPECIFICATIONS: Apply at no greater than 400 square feet per gallon (4.0 wet mils thick) to achieve 1.6 dry mils. Apply by brush, roller or airless spray.

TECHNICAL DATA:

RESIN TYPE:	100% Acrylic
PIGMENT TYPE:	Titanium Dioxide
FINISH:	Flat
VISCOSITY:	88 ± 3 K.U.
WEIGHT PER GALLON:	10.2 lbs.
WEIGHT OF NON-VOLATILES:	48.7%
VOLUME OF NON-VOLATILES:	39.0%
DRY TO TOUCH IN HOURS:	2 – 4
RECOAT TIME IN HOURS:	18
THINNER:	Water
FLASH POINT:	N/A
VOC IN GRAMS PER LITER:	70
FEDERAL SPEC. EQUIV.:	N/A

Dry time and recoat time is temperature, humidity, and film thickness dependent.

This information is intended for selecting products or systems for various applications. The applicator should obtain more detailed information from the product label. Flex Bon representatives are also available for consultation.

02/07