

PRODUCT NAME: Exterior Alkyd Wood Primer Plus

PRODUCT NUMBER: #169 Series

DESCRIPTION: FLEX BON Exterior Alkyd Primer Plus

USES: SPECIFY FOR exterior wood where an alkyd primer is desired. Good stain blocking properties and enamel hold-out are features of this primer. Use for sealing moderate chalk on previously painted wood surfaces prior to repainting.

See Bulletin "Painting 'Staining Woods' (Such As Cedar and Redwood)"

TYPICAL FINISHES: All Flex Bon Interior and Exterior Latex and Oil Finishes.

LIMITATIONS/CAUTIONS:

CAUTION! COMBUSTIBLE! KEEP AWAY FROM HEAT AND OPEN FLAME. AVOID BREATHING VAPOR OR SPRAY MIST AND PROLONGED CONTACT WITH SKIN. USE WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER USE. WASH HANDS AFTER HANDLING AND BEFORE EATING OR SMOKING. KEEP OUT OF THE REACH OF CHILDREN.

SPECIFICATIONS: Apply at no greater than 450 square feet per gallon (3.6 wet mils thick) to achieve 2.1 dry mils. Apply by brush, roller or airless or conventional spray.

TECHNICAL DATA:	RESIN TYPE:	Alkyd
	PIGMENT TYPE:	Titanium Dioxide
	FINISH:	Flat
	VISCOSITY:	93 ± 3 K.U.
	WEIGHT PER GALLON:	11.6 lbs. ± .15
	WEIGHT OF NON-VOLATILES:	76.5% ± 2.0
	VOLUME OF NON-VOLATILES:	57.7% ± 2.0
	DRY TO TOUCH IN HOURS:	2 - 4
	RECOAT TIME IN HOURS:	18
	CLEAN-UP SOLVENT:	Mineral Spirits
	FLASH POINT:	105°F PMCC
	VOC IN GRAMS PER LITER:	325
	FEDERAL SPEC. EQUIV.:	TT-P-25

Dry time and recoat time is temperature, humidity, and film thickness dependent.

This information is intended for selecting products or systems for various applications. The applicator should obtain more detailed information from the product label. Flex Bon representatives are also available for consultation.

02/07