



111.34
H&C®

CLEANER DEGREASER

<u>DESCRIPTION</u>	<u>PRODUCT USE</u>	<u>TECHNICAL DATA</u>
<p>H&C® Cleaner Degreaser is a concentrated heavy-duty cleaner that will remove most automotive fluids (oil, grease, brake fluid, transmission fluid, gear fluid and antifreeze) from concrete and masonry surfaces. Its primary use is to degrease and prepare concrete, block, brick, and masonry prior to applying H&C® Concrete Sealer Solvent Based, H&C® Concrete Stain Water Based, and other coatings.</p> <p>Features:</p> <ul style="list-style-type: none"> • Removes grease and oil stains • Prepares surfaces for paints, stains, and sealers • Increases any coating's ability to bond with the surface by providing a clean substrate <p>Recommended Uses:</p> <ul style="list-style-type: none"> • Stadium Supports • Bridges and Bridge Structures • Parking Garages • Patios and Walkways • Pool Decks • Concrete Driveways • Garage Floors • Block & Stucco Walls • Athletic/Tennis/Shuffleboard Courts • Other Concrete Surfaces 	<p>Coverage: Approximately 100 sq ft/ gallon at 50/50 dilution</p> <p>Mixing Instructions: H&C® Cleaner Degreaser is highly concentrated. For best results, dilute with hot water. This will improve the product's effectiveness and reduce clean-up time. Dilute product based on the condition of the surface to be cleaned. For light to moderately soiled surfaces dilute 64 oz. (1/2 gal.) of H&C Degreaser with 64 oz. (1/2 gal.) of water. For more heavily soiled areas, use product at full strength.</p> <p>Application Method:</p> <ul style="list-style-type: none"> • Sweep away loose dirt • Scrape off excess grease and oil • Dilute solution according to surface condition • Sprinkle solution onto surface in 10'x10' sections (a standard garden sprinkling can works well) • Allow to penetrate for 5-6 minutes • Scrub the area with a stiff bristle broom while rinsing with a garden hose • After the surface has dried, check for any trouble spots (glossy, oily, etc.) by applying a few drops of water. (If the water does not penetrate quickly, repeat the application over these spots.) • Allow surface to dry completely (18-24 hours recommended) before applying any coating. 	<p>Physical and Chemical Data:</p> <p>Specific Gravity 0.91 Boiling Point 212-405°F Volatile Volume 81% Weight per gallon 7.59 lb/gal VOC 619 gr/L; 5.17 lb/gal Flash Point 141°F HMIS 320B</p> <p>ORDERING INFORMATION</p> <p>Part Numbers</p> <p>1/2 Gallon 50.070015</p> <p>SMIS</p> <p>1/2 Gallon 161-2746</p> <p>CAUTIONS</p> <p>Safety Instructions</p> <ul style="list-style-type: none"> • Harmful or fatal if swallowed • Combustible • Wear safety goggles with side shields and rubber gloves • Avoid prolonged contact with skin • Avoid prolonged breathing of vapors • Ventilate area being coated during application and drying periods <p>Not recommended for asphalt.</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of H&C concrete coatings and The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your H&C or Sherwin-Williams representative to obtain the most recent Product Data sheet.</p>