



111.15

H&C® PAVER SEALER

NATURAL LOOK WATER BASED

PRODUCT DESCRIPTION

H&C® Paver Sealer Natural Look is a premium quality sealer that penetrates and protects all types of porous decorative pavers as well as bonding joint sand. This single component, solvent free, VOC compliant penetrating sealer will enhance the appearance of pavers while providing excellent weather and water resistance. H&C® Paver Sealer Natural Look will apply milky white to ensure complete coverage, but dries to a clear transparent finish. .

Where to use:

- Patios
- Lanai
- Driveways
- Walkways
- Pool Decks
- Brick and Concrete Retaining Walls

Note: This product is intended for use on bare unsealed pavers and masonry surfaces. To determine porosity, splash water on the surface to be protected. If the water rapidly absorbs and darkens the surface, the surface is porous and can be sealed after following complete surface preparation. If the surface does not darken with water this means the surface has been treated and the H&C® Paver Sealer Natural Look may not be compatible with a previous treatment. A test area should be coated before complete application is done. Please contact 1-800-TO STAIN (867-8246) for further assistance.

CHARACTERISTICS

Color: Applies Milky White Dries Clear

Coverage **sq ft/gal**
 Standard Brick Paver 100-150

Drying Time, @ 77°F, 50% RH:
 temperature and humidity dependent
 To Touch: 1 hour
 Recoat: 2 hours
 Light traffic: 24 hours
 Heavy traffic: 48 hours

*NOTE: High humidity and /or low temperatures will affect drying time.

Finish: Low Luster

Vehicle Type: Acrylic

VOC (less exempt solvents): 134 g/L

Volume Solids: 15%

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Testing: Due to the wide variety of substrates, preparation methods, application methods and environments, the customer should test the product in an inconspicuous spot for penetration and compatibility **prior to full scale application.**

Bare Brick Pavers:

This product should be applied to a clean surface free of oil, grease and mildew. H&C® Cleaner Degreaser mixed 50% with water will remove light soil from the surface. H&C® Cleaner Degreaser should be used full strength on heavy oil and grease stains. Refer to the H&C® Cleaner Degreaser label for specific instructions. All excess joint sand should be swept off the surface prior to application of the sealer. Do not apply H&C® Paver Sealer Natural Look if rain is imminent or expect within 12 hours of application.



H&C[®] PAVER SEALER

NATURAL LOOK WATER BASED

APPLICATION

Determine if conditions are proper for application:

For best results, surface and air temperature should be above 50°F and below 95°F. Temperature should not fall below 40°F for the period following application.

The most efficient method of application, is with a low-pressure pump type sprayer but can be brushed or rolled if desired. Nozzle pressure should not exceed 20psi (pounds/square inch). Apply the sealer liberally and evenly flooding the paving stone joint to achieve maximum joint sand stabilization. Approximate coverage will be around 100-150 square feet per gallon. The coverage will vary depending on the texture and density of the concrete or clay pavers. On horizontal surfaces, remove excess material by back rolling, squeegee or wiping. The H&C[®] Paver Sealer Natural Look will go on milky white and dry clear in approximately 1 hour.

Vertical surfaces, such as retaining walls, should be coated in the same manner as described above working from the bottom of the wall to the top of the wall. Allow the sealer to run down the surface 8 to 10 inches always maintaining a wet edge to prevent "lapping". One coat is adequate for proper sealing and joint sand stabilizing. If a second coat if desired, apply within 1-2 hours of first coat application. Do not over apply this product as the surface may become slippery. Do not apply more than 2 coats of H&C[®] Paver Sealer Natural Look. Contact H&C[®] technical services at 1-800-TO STAIN (867-8246) for further assistance.

CLEANUP INFORMATION

Tools and equipment: Clean sprayer and tools with warm soapy water immediately following application.

MAINTENANCE

Clean light to medium soiled surfaces with a 50/50 solution of H&C[®] Cleaner Degreaser to water. Use H&C[®] Cleaner Degreaser at full strength for heavy soiled areas, such as oil and grease stains. If H&C[®] Cleaner Degreaser is not available use a good quality neutral based cleaner degreaser following label instructions for use.

WARNING

- Use with adequate ventilation
- Keep out of the reach of children
- Use a NOISH approved respirator, when necessary
- Do not take internally
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting

If splashed in the eyes, flush thoroughly with clean water for a minimum of 15 minutes. CALL A PHYSICIAN immediately. May cause irritation to the skin. If brought into contact with the skin, wash thoroughly with soap and water. Seek medical attention if redness or irritation occurs. Avoid breathing vapors and spray mist. Keep away from heat, spark, open flame and other possible sources of ignition. Reseal container after each use. Wear protective clothing, gloves, and goggles. May contain mineral spirits. Safe disposal of rags is necessary to avoid possibility of spontaneous combustion. Read MSDS before using product.

TECHNICAL SERVICES

1-800-TO STAIN(867-8246)
www.hc-concrete.com

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of H&C concrete coatings and The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your H&C or Sherwin-Williams representative to obtain the most recent Product Data sheet

ORDERING INFORMATION

Part Number

Gallon	50.046054
Five	50.046055

SMIS

Gallon	165-8418
Five	104-1623