ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Nov 6, 2023

30 00 [2523]

PRODUCT NUMBER

T77C35

PRODUCT NAME

SHER-WOOD® Catalyzed Lacquer (Precat), Gloss

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

T77C35 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.72 lb/gal0.934 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	11	14
Ethanol 64-17-5	N	N	N	N	5	5
2-Propanol 67-63-0	N	N	N	N	4	5
1-Butanol 71-36-3	N	Υ	Υ	N	12	13
2-Methyl-1-propanol 78-83-1	N	Υ	N	N	2	2
Acetone 67-64-1	N	Υ	N	N	6	7
Ethyl Acetate 141-78-6	N	Υ	N	N	6	6
n-Butyl Acetate 123-86-4	N	Υ	N	N	19	19
1-Methoxy-2-Propanol Acetate 108-65-6	N	N	N	N	7	7

Volatile Organic Compounds - U.S. EPA / Canada

	T77C35	
	LB/Gal	g/L
Coating Density	7.72	924
	By wt	By vol
Total Volatiles	72.3%	80.3%
Federally exempt solvents		
Water	0.0%	0.0%
Acetone	5.9%	6.9%
Organic Volatiles	66.5%	73.4%
Percent Non-Volatile	27.7%	19.7%
VOC Content	LB/Gal	g/L
Total	5.12	614
Less exempt solvents	5.50	660
Of solids	25.99	3114
Of solids	2.40 lb/lb	2.40 kg/kg
	By wt	
By wt LVP-VOC	66.3%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.04

Volatile Organic Compounds - California

	T77C35		
	LB/Gal	g/L	
Coating Density	7.72	924	
	By wt	By vol	
Total Volatiles	72.3%	80.3%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	5.9%	6.9%	
Organic Volatiles	66.5%	73.4%	
Percent Non-Volatile	27.7%	19.7%	
VOC Content	LB/Gal	g/L	
Total	5.12	614	
Less exempt solvents	5.50	660	
Of solids	25.99	3114	
Of solids	2.40 lb/lb	2.40 kg/kg	
	By wt		
By wt LVP-VOC	66.3%	_	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.96

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	T77C35	
	LB/Gal	g/L
Coating Density	7.72	924
	By wt	By vol
Total Volatiles	72.3%	80.3%
Exempt solvents		
Water	0.0%	0.0%
Acetone	5.9%	6.9%
Organic Volatiles	66.5%	73.4%
Percent Non-Volatile	27.7%	19.7%
VOC Content	LB/Gal	g/L
Total	5.12	614
Less exempt solvents	5.50	660
Of solids	25.99	3114
Of solids	2.40 lb/lb	2.40 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	T77C35	
	By wt	By vol
Total Volatiles	72.3%	80.3%
VOC Content	LB/Gal	g/L
Total	5.58	668

Volatile Organic Compounds - EU Directive 2010/75/EU

	T77C35	
	By wt	By vol
Total Volatiles	72.3%	80.3%
VOC Content	LB/Gal	g/L
Total	5.58	668

Volatile Organic Compounds - Mexico

	T77C35		
	LB/Gal	g/L	
Coating Density	7.72	924	
	By wt	By vol	
Total Volatiles	72.3%	80.3%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	5.9%	6.9%	
Organic Volatiles	66.5%	73.4%	
Percent Non-Volatile	27.7%	19.7%	
VOC Content	LB/Gal	g/L	
Total	5.12	614	
Less exempt solvents	5.50	660	
Of solids	25.99	3114	
Of solids	2.40 lb/lb	2.40 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	T77C35		
	LB/Gal	kg/L	
Volatile HAPS	0.00	0.000	
Of solids	0.00	0.000	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

6.96 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.