



**SHERWIN
WILLIAMS.**

Chemical Coatings

CC-S3

Strippable Coating

White M69W1

<u>DESCRIPTION</u>	<u>CHARACTERISTICS</u>	<u>SPECIFICATIONS</u>
<p>Strippable Coating is a fast dry vinyl coating designed to keep spray booths cleaner, brighter, and safer, and for temporary protection of polished or plated surfaces.</p> <p>Advantages:</p> <ul style="list-style-type: none"> • Labor savings on clean up of spray booths, conveyor hangers, etc. • Temporary protection of polished, plated, or unpainted metal and glass surfaces during storage and shipment. Can be peeled off when ready to market or use • Improves brightness of work area such as spray booths and conveyor lines. • Retains stripping and film strength properties after recoating with paint, enamel, varnish and lacquers • Easy spraying • Easy stripping • Free of lead and chromate hazards 	<p>Gloss: Low to Semi-Gloss Volume Solids: 17.3 ± 2% Viscosity: 25-30 seconds #2 Zahn Cup Recommended film thickness: Mils Wet apply in multiple passes Mils Dry 8.0 Spreading Rate (no application loss) 31-39 sq.ft./gal @ 8 mils DFT Drying (77°F, 45% RH): Tack Free: 20-30 minutes To Recoat: no critical recoat To Pack: 1 hour Force Dry: Do not apply heat, heat can destroy the strippable properties Flash Point: 6°F Pinsky-Martens Closed Cup Package Life: 2 years, unopened Air Quality Data: Non-photochemically reactive Volatile Organic Compounds (VOC) as packaged, maximum 3.54 lb/gal, 424 g/L An Air Environmental Data Sheet is available from your local Sherwin-Williams facility.</p>	<p>General: Substrate should be free of grease, oil, dirt, fingerprints, drawing compounds, and contamination to ensure optimum adhesion and coating performance properties.</p> <p>Metals: No special treatment or cleaning is required when the intended use is for clean up and stripping, such as in spray booths.</p> <p>Other Surfaces: When the surface to be coated is not bare metal or glass, or has a protective coating like paint, enamel, varnish, or lacquer, before applying M69W1, it should be tested in a small area for effects on the surface. The appearance of the surface might change (wrinkling, blistering, etc.) due to the strong solvency of the coating.</p> <p>Testing: Due to the wide variety of substrates, surface preparation methods, application methods, and environments, the customer should test the complete system for adhesion and compatibility prior to full scale application.</p>

APPLICATION

Typical Setups

Reduction: No reduction is required. May be reduced if needed up to 25% by volume with Acetone, R6K9.

Use multiple passes to achieve minimum 8 mil dry film.

May be applied by:

Conventional Spray:
Airless Spray
Air Assisted Airless
HVLP

Cleanup:

Clean tools/equipment immediately after use with Acetone R6K9. Follow manufacturer's safety recommendations when using any solvent.

SPECIFICATIONS

Product Limitations:

- Not intended for "mothballing".
- For interior use only.
- Do not bake or apply heat.
- Should not be applied over surfaces finished with paint, enamel, varnish or lacquer if the appearance of the undersurface is to be preserved.
- Do not apply over plastic substrate unless thoroughly tested.
- Not suitable as a masking material if the product is to be subjected to high and prolonged heat.
- Apply a minimum of 8 mils dry in multiple passes to achieve the necessary film strength for fast and complete stripping at end of service life.

CAUTIONS

Thoroughly review product label for safety and cautions prior to using this product. A Material Safety Data Sheet is available from your local Sherwin-Williams facility.

Please direct any questions or comments to your local Sherwin-Williams facility.

SEE CONTENTS STATEMENT ELSEWHERE ON LABEL.

Contents are EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. VAPOR HARMFUL. Use only with adequate ventilation. Wear an appropriate properly fitted vapor/particulate respirator (NIOSH approved) during and after application, unless air monitoring demonstrates vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet. If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing. Launder before re-use. If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention. If SWALLOWED: Do not induce vomiting. Call Poison Control Center, hospital emergency room, or physician immediately.

SPILL AND WASTE: Remove all sources of ignition. Ventilate and remove with inert absorbent. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.

Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

FOR INDUSTRIAL USE ONLY.

SEE MATERIAL SAFETY DATA SHEET. 21443-051905.

Note: Product Data Sheets are periodically updated to reflect new information relating to the product. It is important that the customer obtain the most recent Product Data Sheet for the product being used. The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, The Sherwin-Williams Company cannot make any warranties as to the end result.