

# MATERIAL SAFETY DATA SHEET

T77F61  
13 00

DATE OF PREPARATION  
Nov 28, 2009

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NUMBER**

T77F61

**PRODUCT NAME**

SHER-WOOD® Acrylic Conversion Coating, Bright Rubbed Effect

**MANUFACTURER'S NAME**

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

**Telephone Numbers and Websites**

|                                  |                |
|----------------------------------|----------------|
| <b>Regulatory Information</b>    | (216) 566-2902 |
| <b>Medical Emergency</b>         | (216) 566-2917 |
| <b>Transportation Emergency*</b> | (800) 424-9300 |

*\*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)*

## SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

| % by Weight | CAS Number | Ingredient                    | Units                 | Vapor Pressure |
|-------------|------------|-------------------------------|-----------------------|----------------|
| 7           | 64742-89-8 | <b>V. M. &amp; P. Naphtha</b> |                       |                |
|             |            | ACGIH TLV                     | 300 PPM               | 12 mm          |
|             |            | OSHA PEL                      | 300 PPM               |                |
|             |            | OSHA PEL                      | 400 PPM STEL          |                |
| 14          | 64-17-5    | <b>Ethanol</b>                |                       |                |
|             |            | ACGIH TLV                     | 1000 PPM              | 44 mm          |
|             |            | OSHA PEL                      | 1000 PPM              |                |
| 7           | 71-36-3    | <b>1-Butanol</b>              |                       |                |
|             |            | ACGIH TLV                     | 20 PPM                | 5.5 mm         |
|             |            | OSHA PEL                      | 50 PPM (Skin) CEILING |                |
| 4           | 67-64-1    | <b>Acetone</b>                |                       |                |
|             |            | ACGIH TLV                     | 500 PPM               | 180 mm         |
|             |            | ACGIH TLV                     | 750 PPM STEL          |                |
|             |            | OSHA PEL                      | 1000 PPM              |                |
| 6           | 110-12-3   | <b>Methyl Isoamyl Ketone</b>  |                       |                |
|             |            | ACGIH TLV                     | 50 PPM                | 4.5 mm         |
|             |            | OSHA PEL                      | 50 PPM                |                |
| 6           | 110-43-0   | <b>Methyl n-Amyl Ketone</b>   |                       |                |
|             |            | ACGIH TLV                     | 50 PPM                | 3.855 mm       |
|             |            | OSHA PEL                      | 100 PPM               |                |
| 5           | 108-21-4   | <b>Isopropyl Acetate</b>      |                       |                |
|             |            | ACGIH TLV                     | 250 PPM               | 47.5 mm        |
|             |            | ACGIH TLV                     | 310 PPM STEL          |                |
|             |            | OSHA PEL                      | 250 PPM               |                |
|             |            | OSHA PEL                      | 310 PPM STEL          |                |
| 27          | 123-86-4   | <b>n-Butyl Acetate</b>        |                       |                |
|             |            | ACGIH TLV                     | 150 PPM               | 10 mm          |
|             |            | ACGIH TLV                     | 200 PPM STEL          |                |
|             |            | OSHA PEL                      | 150 PPM               |                |
|             |            | OSHA PEL                      | 200 PPM STEL          |                |

## SECTION 3 — HAZARDS IDENTIFICATION

**ROUTES OF EXPOSURE**

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.  
Contains alcohols and acetates which can be absorbed through the skin.

**HMIS Codes**

|                     |   |
|---------------------|---|
| <b>Health</b>       | 2 |
| <b>Flammability</b> | 3 |
| <b>Reactivity</b>   | 0 |

**EFFECTS OF OVEREXPOSURE****EYES:** Irritation.**SKIN:** Prolonged or repeated exposure may cause irritation.**INHALATION:** Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary and blood forming systems.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

None generally recognized.

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES****EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.**SKIN:** Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.**INGESTION:** Do not induce vomiting. Get medical attention immediately.**SECTION 5 — FIRE FIGHTING MEASURES****FLASH POINT**

4 °F PMCC

**LEL**

0.9

**UEL**

19.0

**FLAMMABILITY CLASSIFICATION**

RED LABEL -- Extremely Flammable, Flash below 21 °F (-6 °C)

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

- Remove all sources of ignition. Ventilate the area.
- Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class IB

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Contents are EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

Wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT**

Use of barrier cream on exposed skin is recommended.

**OTHER PRECAUTIONS**

This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

|   |
|---|
| <b>SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES</b> |
|---|

|   |                   |  |
|---|-------------------|--|
| <b>PRODUCT WEIGHT</b>   | 7.37 lb/gal       | 882 g/l                                  |
| <b>SPECIFIC GRAVITY</b>   | 0.89              |  |
| <b>BOILING POINT</b>  | 132 - 325 °F      | 55 - 162 °C                              |
| <b>MELTING POINT</b>  | Not Available     |  |
| <b>VOLATILE VOLUME</b>  | 83%               |  |
| <b>EVAPORATION RATE</b>   | Slower than ether |  |
| <b>VAPOR DENSITY</b>  | Heavier than air  |  |
| <b>SOLUBILITY IN WATER</b>  | N.A.              |  |
| <b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b> |                   |  |
|   | 5.65lb/gal        | 678g/l                                   |
|   | 5.42lb/gal        | 649g/l                                   |
|   |                   | Less Water and Federally Exempt Solvents |
|   |                   | Emitted VOC                              |

|  |
|--|
| <b>SECTION 10 — STABILITY AND REACTIVITY</b> |
|--|

**STABILITY — Stable****CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

|   |
|---|
| <b>SECTION 11 — TOXICOLOGICAL INFORMATION</b> |
|---|

**CHRONIC HEALTH HAZARDS**

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

**TOXICOLOGY DATA**

| CAS No.    | Ingredient Name       |                      |     |                                |
|------------|-----------------------|----------------------|-----|--------------------------------|
| 64742-89-8 | V. M. & P. Naphtha    | LC50 RAT<br>LD50 RAT | 4HR | Not Available<br>Not Available |
| 64-17-5    | Ethanol               | LC50 RAT<br>LD50 RAT | 4HR | Not Available<br>7060 mg/kg    |
| 71-36-3    | 1-Butanol             | LC50 RAT<br>LD50 RAT | 4HR | 8000 ppm<br>790 mg/kg          |
| 67-64-1    | Acetone               | LC50 RAT<br>LD50 RAT | 4HR | Not Available<br>5800 mg/kg    |
| 110-12-3   | Methyl Isoamyl Ketone | LC50 RAT<br>LD50 RAT | 4HR | Not Available<br>3200 mg/kg    |
| 110-43-0   | Methyl n-Amyl Ketone  | LC50 RAT<br>LD50 RAT | 4HR | Not Available<br>1670 mg/kg    |
| 108-21-4   | Isopropyl Acetate     | LC50 RAT<br>LD50 RAT | 4HR | Not Available<br>3000 mg/kg    |
| 123-86-4   | n-Butyl Acetate       | LC50 RAT<br>LD50 RAT | 4HR | 2000 ppm<br>13100 mg/kg        |

**SECTION 12 — ECOLOGICAL INFORMATION****ECOTOXICOLOGICAL INFORMATION**

No data available.

**SECTION 13 — DISPOSAL CONSIDERATIONS****WASTE DISPOSAL METHOD**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

**SECTION 14 — TRANSPORT INFORMATION****US Ground (DOT)**

1 Gallon and Less may be Classed as CONSUMER COMMODITY, ORM-D  
Larger Containers are Regulated as:  
UN1263, PAINT, 3, PG II, (ERG#128)

**DOT (Dept of Transportation) Hazardous Substances & Reportable Quantities**

n-Butyl acetate 5000 lb RQ

**Bulk Containers may be Shipped as (check reportable quantities):**

UN1263, PAINT, 3, PG II, (ERG#128)

**Canada (TDG)**

UN1263, PAINT, CLASS 3, PG II, (ERG#128)

**IMO**

UN1263, PAINT, CLASS 3, PG II, (-16 C c.c.), EmS F-E, S-E

**SECTION 15 — REGULATORY INFORMATION****SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION**

| CAS No. | CHEMICAL/COMPOUND | % by WT | % Element |
|---------|-------------------|---------|-----------|
| 71-36-3 | 1-Butanol         | 7       |           |

**CALIFORNIA PROPOSITION 65**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION**

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.