

MATERIAL SAFETY DATA SHEET

PLS4-C0002
04 00

DATE OF PREPARATION
Nov 29, 2009

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

PLS4-C0002

PRODUCT NAME

POWDURA® TGIC Polyester Powder Coating, Legal Blue

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY
101 Prospect Avenue N.W.
Cleveland, OH 44115

Telephone Numbers and Websites

| | |
|---------------------------|----------------|
| Regulatory Information | (216) 566-2902 |
| Medical Emergency | (216) 566-2917 |
| Transportation Emergency* | (800) 424-9300 |

*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)

SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

| % by Weight | CAS Number | Ingredient | Units | Vapor Pressure |
|-------------|------------|--------------------------------|-----------------------------|----------------|
| 4 | 2451-62-9 | 1,3,5-Triglycidyl Isocyanurate | | |
| | | ACGIH TLV | 0.05 MG/M3 | |
| | | OSHA PEL | Not Available | |
| 23 | 7727-43-7 | Barium Sulfate | | |
| | | ACGIH TLV | 10 mg/m3 as Dust | |
| | | OSHA PEL | 10 mg/m3 Total Dust | |
| | | OSHA PEL | 5 mg/m3 Respirable Fraction | |
| 15 | 13463-67-7 | Titanium Dioxide | | |
| | | ACGIH TLV | 10 mg/m3 as Dust | |
| | | OSHA PEL | 10 mg/m3 Total Dust | |
| | | OSHA PEL | 5 mg/m3 Respirable Fraction | |

SECTION 3 — HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of dust.
EYE or SKIN contact with the product or dust.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.
SKIN: Prolonged or repeated exposure to dust may cause irritation.
INHALATION: Irritation of the upper respiratory system.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

May cause allergic skin reaction in susceptible persons or skin sensitization.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

HMIS Codes

| | |
|--------------|----|
| Health | 2* |
| Flammability | 1 |
| Reactivity | 0 |

SECTION 4 — FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.
If irritation persists or occurs later, get medical attention.
Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: Do not induce vomiting. Get medical attention immediately.

SECTION 5 — FIRE FIGHTING MEASURES

| | | | |
|--------------------------------------|--------------------|--------------------|--|
| FLASH POINT Not Applicable | LEL N.A. | UEL N.A. | FLAMMABILITY CLASSIFICATION Not Applicable |
|--------------------------------------|--------------------|--------------------|--|

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Dust at sufficient concentrations can form explosive mixtures with air.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

- Remove all sources of ignition.
- Sweep up material taking care not to generate airborne dust.

SECTION 7 — HANDLING AND STORAGE

STORAGE CATEGORY

Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Store in a cool, dry area out of direct sunlight.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid eye and prolonged skin contact with dust. Avoid generating or breathing airborne dust.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits.

Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PROTECTIVE EQUIPMENT

Use of barrier cream on exposed skin is recommended.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|---|----------------|--|
| PRODUCT WEIGHT | 14.11 lb/gal | 1691 g/l |
| SPECIFIC GRAVITY | 1.70 | |
| BOILING POINT | Not Applicable | |
| MELTING POINT | Not Available | |
| VOLATILE VOLUME | 0% | |
| EVAPORATION RATE | N.A. | |
| VAPOR DENSITY | N.A. | |
| SOLUBILITY IN WATER | N.A. | |
| VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged) | | |
| 0.00lb/gal | 0g/l | Less Water and Federally Exempt Solvents |
| 0.00lb/gal | 0g/l | Emitted VOC |

SECTION 10 — STABILITY AND REACTIVITY

**STABILITY — Stable
CONDITIONS TO AVOID**

High concentrations of airborne dust which may ignite explosively.

INCOMPATIBILITY

Strong oxidizers, acids or alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

SECTION 11 — TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

TOXICOLOGY DATA

| CAS No. | Ingredient Name | | | |
|------------|--------------------------------|----------|-----|---------------|
| 2451-62-9 | 1,3,5-Triglycidyl Isocyanurate | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | 188 mg/kg |
| 7727-43-7 | Barium Sulfate | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | Not Available |
| 13463-67-7 | Titanium Dioxide | LC50 RAT | 4HR | Not Available |
| | | LD50 RAT | | Not Available |

SECTION 12 — ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

SECTION 13 — DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

SECTION 14 — TRANSPORT INFORMATION

US Ground (DOT)

Not Regulated for Transportation.

Canada (TDG)

Not Regulated for Transportation.

IMO

Not Regulated for Transportation.

SECTION 15 — REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

| CAS No. | CHEMICAL/COMPOUND | % by WT | % Element |
|---------|-------------------|---------|-----------|
|---------|-------------------|---------|-----------|

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.