



**SHERWIN
WILLIAMS.**

SWP®

**EXTERIOR GLOSS OIL BASE PAINT
A2 SERIES**

<u>CHARACTERISTICS</u>	<u>SPECIFICATIONS</u>	<u>SURFACE PREPARATION</u>												
<p>SWP Exterior Gloss Oil Base Paint is our best quality oil base house and trim product. This product is recommended for use on wood siding, clapboard, shakes, shingles, plywood, rough sawn lumber, masonry, and metal.</p> <p>Color: Most colors Coverage: 350 - 400 sq ft/gal @ 4 mils wet; 2.1 mils dry Drying Time, @ 77°F, 50% RH: temperature and humidity dependent Touch: 4-6 hours Recoat: 24 hours Finish: 80 units @ 60° Flash Point: 118°F, PMCC Tinting with Blend-A-Color:</p> <table border="1"> <thead> <tr> <th>Base</th> <th>oz/gal</th> <th>Strength</th> </tr> </thead> <tbody> <tr> <td>Tinting White</td> <td>0-5</td> <td>100%</td> </tr> <tr> <td>Deep Base</td> <td>4-12</td> <td>100%</td> </tr> <tr> <td>Ultradeep Base</td> <td>4-12</td> <td>100%</td> </tr> </tbody> </table> <p>Vehicle Type: Alkyd A2W528 VOC (less exempt solvents): 371 g/L; 3.10 lb/gal Volume Solids: 53 ± 2% Weight Solids: 66 ± 2% Weight per Gallon: 9.2 lb Not OTC Compliant</p>	Base	oz/gal	Strength	Tinting White	0-5	100%	Deep Base	4-12	100%	Ultradeep Base	4-12	100%	<p>Aluminum 1 ct. Galvite HS 2 cts. SWP Exterior Gloss Oil Base Paint</p> <p>Galvanized Steel 1 ct. Galvite HS 2 cts. SWP Exterior Gloss Oil Base Paint</p> <p>Masonry/Stucco 1 ct. Loxon Masonry Primer 2 cts. SWP Exterior Gloss Oil Base Paint</p> <p>Plywood 1 ct. A-100 Exterior Latex Primer 2 cts. SWP Exterior Gloss Oil Base Paint</p> <p>Steel, alkyd primer 1 ct. All Surface Enamel Oil Primer 2 cts. SWP Exterior Gloss Oil Base Paint</p> <p>Wood, Composition Board 1 ct. A-100 Exterior Stain Blocking Oil Primer 2 cts. SWP Exterior Gloss Oil Base Paint</p>	<p>WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with PrepRite® ProBlock® Primer Sealer.</p> <p>Aluminum and Galvanized Steel Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, steel wool, or other abrading method.</p> <p>Cement Composition Siding/Panels Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 8, prime with Loxon Acrylic Primer.</p>
Base	oz/gal	Strength												
Tinting White	0-5	100%												
Deep Base	4-12	100%												
Ultradeep Base	4-12	100%												

104.02

SWP[®]

**EXTERIOR GLOSS OIL BASE PAINT
A2 SERIES**



**SHERWIN
WILLIAMS.**

SURFACE PREPARATION

Masonry, Concrete, Cement, Block

All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Acrylic Primer. Cracks, voids, and other holes should be repaired with ConSeal Patch or Sealant.

Steel

Rust and mill scale must be removed using sandpaper, steel wool, or other abrading method. Bare steel must be primed the same day as cleaned.

Wood, Plywood, Composition Board

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All patched areas must be primed.

Caulking

Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.

SURFACE PREPARATION

Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

APPLICATION

Apply at temperatures above 50°F.

No reduction needed.

Brush

Use a natural bristle brush.

Roller

Use a 3/8" - 3/4" nap synthetic cover.

Spray—Airless

Pressure 2000 psi

Tip015"-.021"

CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using mineral spirits.

CAUTIONS

For exterior use only.

Non-photochemically reactive.

Develops a chalk face in 12-18 months. Not for use on horizontal surfaces (floors, roofs, decks, etc.) where water will collect.

LABEL CAUTIONS

CAUTION contains ALIPHATIC HYDROCARBONS and CRYSTALLINE SILICA. Contents are COMBUSTIBLE. Keep away from heat and open flame. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. HOTW 04/10/2006 A02W00528 43 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.